

NILES CHEMICAL PAINT CO -- WHITE H/S EPOXY PRIMER -- 8010-01-309-0329

=====
Product Identification
=====

Product ID:WHITE H/S EPOXY PRIMER
MSDS Date:11/12/1991
FSC:8010
NIIN:01-309-0329
Kit Part:Y
MSDS Number: BMXLX
=== Responsible Party ===
Company Name:NILES CHEMICAL PAINT CO
Address:225 FORT STREET
Box:307
City:NILES
State:MI
ZIP:49120
Country:US
Info Phone Num:616-683-3377
Emergency Phone Num
:219-236-5856
Preparer's Name:MIKE LICHATOWICH
CAGE:02388

=== Contractor Identification ===
Company Name:NILES CHEMICAL PAINT
Address:225 FORT STREET
Box:307
City:NILES
State:MI
ZIP:49120
Country:US
Phone:616-683-3377/219-236-5856
CAGE:02388

=====
Composition/Information on Ingredients
=====

Ingred Name:EPOXY RESIN
CAS:25068-38-6
RTECS #:KC2100000
Fraction by Wt: 19%
Other REC Limits:NONE SPECIFIED

Ingred Name:BARIUM SULFATE
CAS:7727-43-7
RTECS #:CR0600000
Fraction by Wt: 16

%
Other REC Limits:NONE SPECIFIED
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:ISOPROPYL ALCOHOL (SARA III) (VAPOR PRESSURE 32.8 MM @ 20 C)

CAS:67-63-0
RTECS #:NT8050000
Fraction by Wt: 7%
Other REC Limits:NONE SPECIFIED
OSHA PEL:400 PPM
ACGIH TLV:400 PPM/500 PPM STEL

Ingred Name:ZINC PHOSPHATE
Fraction by Wt: 5%
Other REC Limits:NONE SPECIFIED

Ingred Name:TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 4%
Other REC Limits:NONE SPECIFIED
OSHA PEL:
200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:VM&P NAPHTHA (VAPOR PRESSURE 15 MM @ 37.7 C)
CAS:8032-32-4
RTECS #:OI6180000
Fraction by Wt: 3%
Other REC Limits:NONE SPECIFIED
OSHA PEL:300 PPM
ACGIH TLV:300 PPM/400 PPM STEL

Ingred Name:PM GLYCOL ETHER (VAPOR PRESSURE 12.5 MM @ 25 C)
CAS:107-98-2
RTECS #:UB7700000
Fraction by Wt: 2%
Other REC Limits:NONE SPECIFIED
ACGIH TLV:100 PPM/150 PPM STEL

Ingred Name:BUTYL ALCOHOL (SARA III) (VAPOR PRESSURE 4

.4 MM @ 20 C)
CAS:71-36-3
RTECS #:EO1400000
Fraction by Wt: 1%
Other REC Limits:NONE SPECIFIED
OSHA PEL:100 PPM
ACGIH TLV:S, C 50 PPM; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:XYLENE (SARA III) (VAPOR PRESSURE 7.0 MM @ 20 C)
CAS:1330-20-7
RTECS #:ZE2100000
Fraction by Wt: 1%
Other REC Limits:NONE SPECIFIED
OSHA PEL:100 PPM
ACGIH TLV:100 PPM/150 PPM STEL
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:UREA FORMALDEHYDE RESIN
Fraction by Wt: AIR
Spec Gravity:13.90 LBS/GA
L
Viscosity:70-80 KU
Evaporation Rate & Reference:SLOWER THAN ETHER.
Solubility in Water:SLIGHT.
Appearance and Odor:LIQUID, ODOR OF SOLVENTS.
Percent Volatiles by Volume:45.25

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZERS.
Stability Condition to Avoid:HIGH TEMPERATURES, SHOCK FROM DROPPING.
Hazardous Decomposition Products:CAN PRODUCE CARBON MONOXIDE AND/OR
CARBON DIOXIDE.

===== Disposal
Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH APPLICABLE LOCAL,
STATE AND FEDERAL REGULATIONS. D001.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
docu

ment should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.