View NSN Online: https://aerobasegroup.co.il/nsn/5330-01-133-0208

KLINGER RICHARD INC -- K-61 BLACK -- 5330-01-133-0208

Product ID:K-61 BLACK MSDS Date:11/20/1985

FSC:5330

NIIN:01-133-0208

MSDS Number: BNPWQ === Responsible Party ===

Company Name: KLINGER RICHARD INC

Address:2350 CAMPBELL RD

City:SIDNEY State:OH

ZIP:45365-9501 Country:US

Info Phone Num:513-498-1181

Emergency Phone Num:513-498-1181 Preparer's Name:DEREK COOMBE

R

CAGE:9U500

=== Contractor Identification ===

Company Name: C-WAY INDUSTRIES INC Address: 400 SOUTH LASALLE STREET

Box:City:SPENCER

State:WI

ZIP:54479-9558 Country:US

Phone:715-659-4461

CAGE:57386

Company Name: GERARD PACKING AND BELTING CORP

Address:24 MIDLAND AVENUE

Box:City:HICKSVILLE

State:NY ZIP:11801 Country:US

Phone:516-935-2400

CAGE:2G277

Company Name: KLINGER RICHARD INC

Address:2350 CAMPBELL RD

Box:City:SIDNEY

State:OH

ZIP:45365-9501

Country:US

Phone:937-498-1181

CAGE:9U500

Composition/Information on Ingredients ======== Ingred Name: CARBON BLACK CAS:1333-86-4 RTECS #:FF5800000 Fraction by Wt: 0.5-1.5% Other REC Limits: NONE SPECIFIED OSHA PEL:3.5 MG/M3 ACGIH TLV:3.5 MG/M3; 9192 Ingred Name:BUTADIENE-STYRENE POLYMER (RUBBER) CAS:9003-55-8 RTECS #:WL6478000 Fraction by Wt: 8-15% Other REC Limits: NONE SPECIFIED Ingred Name: ASBESTOS, CHRYSOTILE CAS:12001-29-5 RTECS #:CI6478500 Fraction by Wt: 70-90% Other REC Limits: NONE SPECIFIED OSHA PEL:0.2 FIBERS/CC **ACGIH** TLV:2 FIBERS/CC; A1;9192 ========== Hazards Identification =============== Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO Health Hazards Acute and Chronic: IN FINISHED FORM, NO KNOWN HEALTH HAZARD. A CHRONIC HEALTH HAZARD MAY BE CREATED IF FURTHER PROCESSING OF THE SHEET ALLOWS ASBESTOS FIBERS TO BE RELEASED INTO THE ATMOSPHERE. INHALATION OF FREE ASBEST OS FIBER OVER A LONG PERIOD OF TIME CANCAU LUNG CANCER & MESOTHELIOMA. Explanation of Carcinogenicity: CONTAINS CRYSOTILE ASBESTOS Effects of Overexposure:NONE Medical Cond Aggravated by Exposure: NONE GIVEN BY MANUMACTURER.

SE LUNG DISORDERS: ASBESTOSIS, PLEURAL PLAQUE,

============ Fire Fighting Measures =========================

Flash Point:NONE

Autoignition Temp: Autoignition Temp Text: NONE

Extinguishing Media: USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL.

Fire Fighting Procedures: FIRE FIGHTERS SHOULD USE NIOSH A

PPROVED
SELF-CONTAINED BREATHING APPARATUS AND EYE PROTECTION FOR THE
RUBBER FUMES.
Unusual Fire/Explosion Hazard:THE RUBBER, ONCE IGNITED, MAY NEED EXTRA COOLING TO PREVENT REIGNITION.
OCCENTO TO TREVERT REIGITITION.
========= Accidental Release Measures ===========
Spill Release Procedures:DUST FROM SHEET SHOULD BE TREATED AS FREE ASBESTOS. SECURE AREA AND CLEAN UP USING HEPA FILTERED VACUUM. OR WET SWEEP. DO NOT CLEAN UP IN A METHOD THAT GENERATES DUST INTO ATMOSPHERE. Neutralizin g Agent:NONE
Lloydling and Ctorogo
======================================
Handling and Storage Precautions:IN NORMAL HANDLING OF SHEET AND CUT GASKETS, NO SIGNIFICANT RELEASE OF ASBESTOS DUST OCCURS. DO NOT DRILL, SAW, GRIND OR SAND W/O PROTECTIVE EQUIPMENT Other Precautions:WHERE GASKET REMOVAL INVOLVES SCRAPING, WIRE BRUSHING OR OTHER POTENTIAL DUST PRODUCING OPERATIONS; LOCAL VENTILATION, AIR FILTRATION, GOOD WORK HYGIENE, AND WHERE APPLICABLE, WETTING DOWN SHOULD
BE U SED TO ENSURE NEGLIGIBLE ASBESTOS DUST.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:RESPIRATOR WILL NOT NORMALLY BE NECESSARY. USE NIOSH/MSHA APPROVED RESPIRATOR FOR ASBESTOS DUST IF EXPOSURE IS ABOVE THE TLV/PEL. SEE 29CFR1910.1001 (D)(2). Ventilation:WHERE DUST PRODUCING PROCESSES ARE USED, LOCAL VENTILATION, AIR FILTRATION AND GOOD WORK HYGIENE MUST BE USED. Protective Gloves:NONE Eye Protection:SAFETY GLASSES OR GOGGLES
Other
Protective Equipment:INDUSTRIAL-TYPE WORK CLOTHING. Work Hygienic Practices:USE GOOD INDUSTRIAL HYGIENE PRACTICE. AVOID UNNECESSARY CONTACT. WASH THOROUGHLY BEFORE EATING OR DRINKING. Supplemental Safety and Health
NO EXPOSURE TO ASBESTOS SHOULD OCCUR DURING USE SINCE IT IS

NO EXPOSURE TO ASBESTOS SHOULD OCCUR DURING USE SINCE IT IS ENCAPSULATED BY THE RUBBER. SEE 29CFR1910.1001 FOR REGULATIONS COVERING ASBESTOS.

======== Physical/Chemical Properties ==========

HCC:N1

Boiling Pt:B.P. Text:DECOMPOSES

Spec Gravity:1.75

So

lubility in Water:NEGLIGIBLE Appearance and Odor:BLACK WITH WHITE SPOTS, NO ODOR Percent Volatiles by Volume:0
========= Stability and Reactivity Data ==========
Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS, STRONG ACIDS, ALKALIS Hazardous Decomposition Products:BURNING RUBBER AND FREE ASBESTOS
======= Disposal Considerations ==========

Waste Disposal Methods:BURY IN SOLID LANDFILL AS REQUIRED BY 29CFR1910.1001 (N)(2).

Dis

claimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.