

EASTMAN KODAK COMPANY -- 830 9031, EKTACOLOR RA BLEACH FIX & REPL, WORKING SOLUTION -- 6750-01-320-6638

===== Product Identification =====

Product ID:830 9031, EKTACOLOR RA BLEACH FIX & REPL, WORKING SOLUTION

MSDS Date:03/17/1994

FSC:6750

NIIN:01-320-6638

Kit Part:Y

MSDS Number: BNQFN

=== Responsible Party ===

Company Name:EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY

Z

IP:14650

Country:US

Info Phone Num:716-722-5151

Emergency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

===== Composition/Information on Ingredients =====

Ingred Name:WATER

CAS:7732-18-5

RTECS #:ZC0110000

Fraction by Wt: 85-90%

Other REC Limits:NONE SPECIFIED

Ingred Name:AMMONI

UM THIOSULFATE

CAS:7783-18-8

RTECS #:XN6465000

Fraction by Wt: 5-10%

Other REC Limits:NONE SPECIFIED

Ingred Name:SODIUM BISULFITE (SASA III)

CAS:7631-90-5

RTECS #:VZ2000000

Fraction by Wt: 1-5%

Other REC Limits:NONE SPECIFIED

OSHA PEL:5 MG/M3

ACGIH TLV:5 MG/M3; 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:AMMONIUM FERRIC ETHYLENEDIAMINETETRAACETIC ACID

CAS:21265-50-9

Fraction by Wt: 1-5%

Other REC Limits:NONE SPECIFIED

Ingred Name:ACETIC ACID (SARA III)

CAS:64-19-7

RTECS #:AF122

5000

Fraction by Wt: 1-5%

Other REC Limits:NONE SPECIFIED

OSHA PEL:10 PPM

ACGIH TLV:10 PPM/15 STEL; 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

===== Hazards Identification =====

LD50 LC50 Mixture:LD50 (ORAL RAT) IS NOT ESTABLISHED.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALED: LOW HAZARD FOR RECOMMENDED

HANDLING. EYES: NO SPECIFIC HAZARD KNOWN. MA

Y CAUSE TRANSIENT

IRRITATION. SKIN:LOW HAZARD FOR RECOMMENDED HANDLING. INGESTION:
EXPECTED TO BE LOW INGESTED HAZARD.

Explanation of Carcinogenicity:NONE OF THE COMPOUNDS IN THIS PRODUCT IS
LISTED BY IARC, NTP, OR OSHA AS A CARCINOGEN.

Effects of Overexposure:INHALED: LOW HAZARD FOR RECOMMENDED HANDLING.

EYES: NO SPECIFIC HAZARD KNOWN. MAY CAUSE TRANSIENT IRRITATION.

SKIN:LOW HAZARD FOR RECOMMENDED HANDLING. INGESTION: EXPECTED TO BE
LOW INGESTED HAZARD.

Medical Cond Ag

gravated by Exposure:SUPPLIER DID NOT ADDRESS THIS FIELD.

=====
===== First Aid Measures =====

First Aid:INHALED: IF SYMPTOMATIC, REMOVE TO FRESH AIR. EYES: ANYTHING THAT CONTACTS THE EYE SHOULD BE WASHED OUT IMMEDIATELY WITH WATER. SKIN:IMMEDIATELY FLUSH WITH WATER. REMOVE CONTAMINATED CLOTHING AND LAUN DER BEFORE REUSE. REMOVE AND DESTROY ORTHOROUGHLY CLEAN CONTAMINATED SHOES. INGESTION:IF SWALLOWED, GIVE 1-2 GLASSES OF WATER AND GET MEDICAL ATTENTION. IF ANY SYMPTOMS OCCUR, GET MEDICAL ATTENTION.

=====
===== Fire Fighting Measures =====

Flash Point:NON-FLAMMABLE
Extinguishing Media:USE APPROPRIATE AGENT FOR SURROUNDING FIRE.
Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS & PROTECTIVE CLOTHING. FIRE OR EXCESSIVE HEAT MAY PRODUCE HAZARDOUS DECOMPOSITION PRODUCTS.
Unusual Fire/Explosion Hazard:NONE

=====
===== Accidental Release Measures =====

Spill Release Procedures:FLUSH MATERIAL TO SEWER WITH LARGE AMOUNTS OF WATER.
Neutralizing Agent:NO INFORMATION GIVEN ON MSDS BY SUPPLIER

=====
===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS TIGHTLY CLOSED AND AWAY FROM STRONG ALKALI.
Other Precautions:NONE

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:RESPIRATORY PROTECTION MAY BE NEEDED IN SPECIAL CIRCUMSTANCES.
Ventilatio

n:GOOD VENTILATION (10 ROOM VOL PER HOUR IS CONSIDERED GOOD GENERAL VENTILATION). SUPPLEMENTAL VENTILATION MAY BE NEEDED.
Protective Gloves:IMPERVIOUS
Eye Protection:SAFETY GLASSES WITH SIDE SHIELDS
Other Protective Equipment:IF PROLONGED OR REPEATED CONTACT IS NECESSARY, IMPERVIOUS GLOVES OR OTHER PROTECTION MAY BE REQUIRED.
Work Hygienic Practices:SUPPLIER DID NOT ADDRESS THIS FIELD.
Supplemental Safety and Health

KEY1:C1. THIS ENTRY DESCRIBES THE WORKING SOLUTION MADE FROM PART A AND PART B OF A TWO PART KIT. SEE THIS SAME NSN P/N IND E, FOR PART A DATA; AND P/N IND D, FOR PART B DATA. ENVIRONMENTAL STATEMENT MADE BY MFR FOR WORKING SOLUTION. SEE MOST CURRENT PARTS A & B FOR ENVIRONMENTAL INFORMATION.

===== Physical/Chemical Properties =====

HCC:C2
Boiling Pt:B.P. Text:212F,100C
Vapor Pres:18 MM
Vapor Density:0.6
Spec Gravity:1.10
pH:5.4
Solubility in Water:COMPLETE
Appearance and Odor:DARK RED LIQUID,SLIGHT AMMONIA ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG ACIDS, STRONG OXIDIZING AGENTS, BASES, SODIUM HYPOCHLORITE (BLEACH)
Stability Condition to Avoid:NO INFORMATION GIVEN BY MFR ON MSDS.
Hazardous Decomposition Products:THERMAL DECOMPOSITION WILL PRODUCE AMMONIA AND OXIDES OF SULFUR AND NITROGEN.
Conditions to Avoid Polymerization:WILL NOT OCCUR.

===== Disposal Considerations =====

Waste Dispos

al Methods:FLUSH MATERIAL TO SEWER WITH LARGE AMOUNTS OF WATER.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.