

FISKE BROTHERS REFINING CO -- 630-2, LUBRIPLATE -- 9150-01-038-6841

=====
Product Identification
=====

Product ID:630-2, LUBRIPLATE

MSDS Date:05/01/1987

FSC:9150

NIIN:01-038-6841

MSDS Number: BNRHD

=== Responsible Party ===

Company Name:FISKE BROTHERS REFINING CO

Address:129 LOCKWOOD ST

City:NEWARK

State:NJ

ZIP:07105

Country:US

Info Phone Num:201-589-9150

Emergency Phone Num:201-589-9150

Preparer

's Name:ROBERT J. SIBILIA

CAGE:9N579

=== Contractor Identification ===

Company Name:FISKE BROS REFINING CO

Address:129 LOCKWOOD ST

Box:City:NEWARK

State:NJ

ZIP:07105-4720

Country:US

Phone:201-589-9150

CAGE:73219

Company Name:FISKE BROTHERS REFINING CO

Address:1500 OAKDALE AVE

Box:City:TOLEDO

State:OH

ZIP:43605

Country:US

Phone:419-691-2491

CAGE:9N579

=====
Composition/Information on Ingredients
=====

Ingred Name:NON HAZARDOUS INGREDIENT

Ingred Name:NON HAZARDOUS INGREDIENTS

OSHA PEL:N/K
ACGIH TLV:N/K

=====
Hazards Identification
=====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.
Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:PROLONGED OR REPEATED SKIN CONTACT MAY CAUSE SKIN IRRITATION. PRODUCT CONTACTING THE EYES MAY CAUSE EYE IRRITATION. HUMAN HEALTH RISKS VARY FROM PERSON TO PERSON. AS A PRECAUTION, EXPOSURE TO LIQUIDS, VAPORS, MISTS AND FUMES SHOULD BE MINIMIZED. THIS PRODUCT HAS LOW ORDER OF ACUTE ORAL TOXICITY, (EFTS OF OVEREXP)
Explanation of Carcinogenicity:NOT RELEVANT.
Effects of Overexposure:HLTH HAZ:BUT MINUTE AMOUNTS ASPIRATED INTO THE LUNGS DURING INGESTION MAY CAUSE MILD TO SEVERE PULMONARY INJURY.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
First Aid Measures
=====

First Aid:EYE:FLUSH W/CLEAR WATER FOR AT LEAST 15 MINS OR UNTIL IRRITATION SUBSIDES. IF IRRITATION PERSISTS, CALL MD. SKIN:REMOVE ANY CONTAMINATED CLOTHING & WASH W/ SOAP & WARM WATER. IF INJECTED BY HIGH PRESSURE UNDER SKIN, REGARDLESS OF APPEARANCE OR ITS SIZE, CONTACT IMMEDIATELY. DELAY MAY CAUSE LOSS OF AFFECTED PART OF BODY. INHALATION:VAPOR PRESSURE IS VERY LOW & INHALATION AT ROOM TEMPERATURE NOT A PROBLEM. IF OVERCOME BY VAPOR FROM HOT (SUPPORT DATA)

=====
Fire Fighting Measures
=====

Flash Point Method:COC
Flash Point:400F,204C

Lower Limits:0.9%
Upper Limits:7%
Extinguishing Media:FOAM, DRY CHEMICAL, CARBON DIOXIDE OR WATER SPRAY (FOG).
Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED SCBA & FULL PROTECTIVE EQUIPMENT . COOL EXPOSED CONTAINERS WITH WATER.
Unusual Fire/Explosion Hazard:DO NOT STORE OR MIX WITH STRONG OXIDANTS. EMPTY CONTAINERS RETAIN RESIDUE. DO NOT CUT, DRILL, GRIND, OR WELD, AS THEY MAY EXPLODE.

=====
Accidental Release Measures
=====

Spill Release Procedure

ures:SCRAPE UP GREASE, WASH REMAINDER W/SUITABLE
PETROLEUM SOLV OR ADD ABSORBANT. KEEP PETROLEUM PRODUCTS OUT OF
SEWERS AND WATER COURSES.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED WHEN NOT IN
USE. DO NOT HANDLE OR STORE NEAR HEAT, SPARKS, FLAME, OR STRONG
OXIDANTS.

Other Precautions:REMOVE OIL-SOAKED CLOTHING AND LAUNDRER BEFORE REUSE.

=====
=== Exposure Controls/Personal Protection =====

Respiratory Protection:NORMALLY NOT NEEDED. NIOSH/MSHA APPROVED
RESPIRATOR APPROPRIATE FOR EXPOSURE OF CONCERN .

Ventilation:LOCAL EXHAUST TO CAPTURE FUMES AND VAPORS.

Protective Gloves:OIL RESISTANT GLOVES.

Eye Protection:CHEMICAL WORKERS GOGGLES .

Other Protective Equipment:OIL RESISTANT APRON IF NEEDED.

Work Hygienic Practices:CLEANSE SKIN THOROUGHLY AFTER CONTACT.

Supplemental Safety and Health

FIRST AID PROC:PRODUCT, IMMEDIATELY

REMOVE FROM EXPOSURE AND CALL MD.

INGEST:CALL MD IMMEDIATELY. DO NOT INDUCE VOMITING.

=====
===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:>550F,>288C

Melt/Freeze Pt:M.P/F.P Text:SEMI-SOLID

Vapor Pres:5

Spec Gravity:0.94-0.95

Evaporation Rate & Reference: