View NSN Online: https://aerobasegroup.co.il/nsn/6140-01-300-4836

EAST PENN MFG CO INC -- BATTERY WET, FILLED WITH ACID & UN 2794 PGIII -- 6140-01-300-4836

Product ID:BATTERY WET, FILLED WITH ACID & UN 2794 PGIII

MSDS Date:04/01/1994

FSC:6140

NIIN:01-300-4836

MSDS Number: BNRLF === Responsible Party ===

Company Name: EAST PENN MFG CO INC

Address:DEKA RD City:LYON STATION

State:PA ZIP:19536 Country:US

Info Phone Num:610-682-6361

Emergency Phone Num:610-682-6361/800-424-9300(CHEMTREC)

CAGE:04055

=== Contractor Identification ===

Company Name: EAST PENN MFG CO INC

Address: DEKA RD

Box:City:LYON STATION

State:PA ZIP:19536 Country:US

Phone:610-682-6361

CAGE:04055

Company Name: NORTHWESTERN MOTOR CO INC

Address:1125 STARR AVE

Box:265

City: EAU CLAIRE

State:WI ZIP:54702 Country:US

Phone:715-835-3151

CAGE:44185

====== Composition/Information on Ingredients ========

Ingred Name:LEAD (SARA III)

CAS:7439-92-1

RTECS#

:OF7525000

Fraction by Wt: 43-70%

OSHA PEL:0.05 MG/M3;1910.1025 ACGIH TLV:0.15 MG/M3;DUST 9192

EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

Ingred Name: ANTIMONY (SARA III)

CAS:7440-36-0

RTECS #:CC4025000 Fraction by Wt: 0-4% OSHA PEL:0.5 MG/M3

ACGIH TLV:0.5 MG SB/M3; 9192

EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:SULFURIC ACID (SARA III)

CAS:7664-93-9

RTECS #:WS5600000 Fraction by Wt: 20-44% OSHA PEL:1 MG/M3

ACGIH TLV:1 MG/M3; 9192 EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

=== Hazards Identification ==========

LD50 LC50 Mixture:TLV FOR SULFURIC ACID IS 1 MG/M3.

Routes of Entry: Inhalation:NO Skin:NO Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:TARGET ORGANS:EYE, CNS, SKIN. ACUTE-LEAD MAY CAUSE GI UPSET, DIARRHEA, CNS EFFECTS, CRAMPING & FATIGUE. SULFURIC ACID MAY CAUSE EYE, SKIN & RESPIRATORY TRACT IRRITATION, BURNS, CORNEAL & LUNG DAMAGE. CHRONIC- LEAD MAY CAUSE ANEMIA, KIDNEY

& NERVOUS SYSTEM DAMAGE. ACID CAN CAUSE BRONCHITIS, EROSION OF TOOTH ENAMEL.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:GI UPSET, LOSS OF APPETITE, DIARRHEA, CONSTIPATION, CRAMPING, LACK OF SLEEP, FATIGUE, IRRITATION, BURNS, CORNEAL AND LUNG DAMAGE

Medical Cond Aggravated by Exposure:LEAD AND ITS COMPOUNDS CAN AGGRAVATE CHRONIC FORMS OF KIDNEY, LIVER AND NEUROLOGIC DISEASES. CONTACT OF SULFURIC ACID WITH SKIN MAY AGGRAVATE DISEASES SUCH AS ECZEMA. ACID MI

| ST AGGRAVATES LUNG DISEASE |
|--|
| ====================================== |
| First Aid:OBTAIN MEDICAL ATTENTION IN ALL CASES OF EXPOSURE. EYES/SKIN:IMMEDIATELY FLUSH WITH WATER FOR 15 MINUTES. KEEP EYELIDS OPEN. INHALATION:MOVE TO FRESH AIR. INGESTION:DO NOT INDUCE VOMITING. IF CONSCIOU S, DRINK LARGE AMOUNT OF WATER. |
| ============= Fire Fighting Measures ============= |
| Flash Point:NON-FLAMMABLE Lower Limits:4% HYDROGEN Upper Limits:74% HYDROGEN |
| Extinguishing Media:USE CLASS ABC EXTINGUISHER, CARBON DIOXIDE, HALON. COOL OUTSIDE OF BATTERIES EXPOSED TO HEAT OF FIRE WITH WATER SPRAY. Fire Fighting Procedures:WEAR ACID-RESISTANT CLOTHING AND NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS WITH FULL FACEPIECE OPERATED IN THE POSITIVE PRESSURE MODE. Unusual Fire/Explosion Hazard:BATTERY CELLS MAY RUPTURE WHEN EXPOSED TO EXCESSIVE HEAT. THIS COULD RESULT IN RELEASE OF CORROSIVE MATERIALS. HYDROGEN GAS, IF PRESENT, IS EX PLOSIVE/FLAMMABLE. |
| ========= Accidental Release Measures =========== |
| Spill Release Procedures:WEAR PROTECTIVE EQUIPMENTS. REMOVE COMBUSTIBLES & IGNITION SOURCES (H2 MAY BE PRESENT). CONTAIN BY DIKING AND COVER SPILL WITH SODA ASH OR QUICKLIME. MIX WELL. CHECK THAT MIXTURE IS NEUTRAL. COLLECT A ND PLACE IN A DRUM. DO NOT FLUSH TO SEWER. Neutralizing Agent:SODA ASH (SODIUM CARBONATE), QUICKLIME (CALCIUM OXIDE) |
| ====================================== |
| Handling and Storage Precautions:STORE NEAR EYEWASH FOUNTAIN AND SAFETY SHOWER. STORAGE AREA SHOULD BE EQUIPPED WITH A DRAIN WHICH CAPTURES SPILLS OF ACID FOR PROPER DISPOSAL. Other Precautions:KEEP TERMINALS COVERED IN PLASTIC CASE. AVOID SHORTING BATTERIES. DO NOT CRACK OR OVERCHARGE BATTERIES. KEEP LIGHTED CIGARETTES, SPARKS, AND FLAMES AWAY FROM CHARGING BATTERIES. KEEP OUT OF REACH OF C HILDREN. |
| ====== Exposure Controls/Personal Protection |

=========

Respiratory Protection:NOT REQUIRED UNDER NORMAL USE. USE NIOSH-APPROVED ACID-MIST FILTER RESPIRATOR IF 1 MG/M3 TWA IS EXCEEDED (ACID).

Ventilation: ADEQUATE GENERAL VENTILATION

Protective Gloves: RUBBER

Eye Protection: SPLASH-PROOF CHEMICAL GOGGLES

Other Protective Equipment: RUBBER APRON AND BOOTS. EYES WASH STATION AND SAFETY SHOWER. USE ACID-PROOF CLOTHING FOR MAJOR SPILLS.

Work Hygienic Practices:REMOVE METALLIC JEWELRY-SHOCK POTENTIAL. WASH THOROUGHLY AFTER HAND

LING AND BEFORE EATING AND DRINKING.

Supplemental Safety and Health

FORMULA CHANGED. FOR PREVIOUS FORMULATION, SEE PNI A, SAME NSN.

======== Physical/Chemical Properties ===========

HCC:C1

NRC/State Lic Num:NOT RELEVANT Boiling Pt:B.P. Text:APPROX 235F

Vapor Pres:13 (H2SO4) Spec Gravity:1.220 - 1.325 Viscosity:NOT RELEVANT

Evaporation Rate & Evaporation Relevant

Solubility in Water: NOT RELEVENT

Appearance and Odor:BATTERY CONTAINING SULFURIC ACID AND LEAD.

========

===== Stability and Reactivity Data ========

Stability Indicator/Materials to Avoid:YES

COMBUSTIBLES, ORGANIC MATERIALS, METALS, REDUCING AGENTS, STRONG OXIDIZING AGENTS, WATER, BASES

Stability Condition to Avoid:HIGH HEAT (160-410C/322-770F), OPEN FLAMES, OVERCHARGING, SMOKING, SPARKS

Hazardous Decomposition Products:LEAD OXIDE, HYDROGEN, SULFUR DIOXIDE, SULFUR TRIOXIDE, ANTIMONY OXIDE

======= Disposal Considerations ===========

Waste Disposal

Methods:DISPOSE AS HAZARDOUS WASTE. OBSERVE ALL FEDERAL, STATE AND LOCAL ENVIRONMENTAL REGULATIONS FOR ACID OR LEAD SCRAP. SEND BATTERIES TO LEAD SMELTER FOR RECLAMATION FOLLOWING APPLICABLE FEDERAL, STATE AN D LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this informatio n to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.