View NSN Online: https://aerobasegroup.com/nsn/6850-01-342-6548 DOW CORNING CORP -- 111 COMPOUND -- 6850-01-342-6548 ============ Product Identification ========================= Product ID:111 COMPOUND MSDS Date:09/27/1985 FSC:6850 NIIN:01-342-6548 MSDS Number: BNRLZ === Responsible Party === Company Name: DOW CORNING CORP Address:SOUTH SAGINAW RD City:MIDLAND State:MI ZIP:48686 Country:US Info Phone Num:517-496-5900 Emergency Phone Num:517-496-5900 Preparer's Name: JACK L. SHENEBERGER CAGE:5D028 === Contractor Identification === Company Name: DOW CORNING CORP Address:3901 S SAGINAW RD Box:997 City:MIDLAND State:MI ZIP:48686-0997 Country:US Phone:517-496-6000/517-496-6315 CAGE:5D028 Company Name: DOW CORNING CORP Address:2200 W SALZBURG RD Box:City:AUBURN State:MI ZIP:48611 Country:US Phone:517-496-4388 CAGE:71984 ======= Composition/Information on Ingredients ======== Ingred Name: NON HAZARDOUS INGREDIENTS

======= Hazards Identification ========

======== LD50 LC50 Mixture: NONE SPECIFIED BY MANUFACTURER. Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:EYES:MAY CAUSE TEMP DISCOMFORT. SKIN:SINGLE, PRLNGD EXPOS CAUSES NO KNOWN ADVERSE EFFECT. INHAL:NO IRRIT TO NOSE/THROAT EXPECTED. NO INJURY IS LIKELY FROM RELATIVELY SHORT EXPOS. INGEST: AMTS TRANSFERR ED TO MOUTH BY FINGERS. ETC. DURING NORM OPERATION SHOULD NOT CAUSE INJURY. NO KNOWN ADVERSE CHRONIC (EFTS OF OVEREXP) Explanation of Carcinogenicity: NOT RELEVANT. Effects of Overexposure: HLTH HAZ: HEALTH EFFECTS, BUT UNNECESSARY EXPOSURE TO ANY CHEMICAL SHOULD BE AVOIDED. Medical Cond Aggravated by Exposure: THIS PRODUCT MAY ENHANCE ALLERGIC CNDTNS ON CERTAIN PEOPLE. WE DO NOT KNOW OF ANY MEDICAL CNDTNS THAT MIGHT BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT. First Aid:EYES:FLUSH W/WATER FO R AT LEAST 15 MINS. SKIN:WIPE OFF & FLUSH W/WATER. INHAL:REMOVE TO FRESH AIR. SUPPORT BREATHING (GIVE O\*2/ARTIFICIAL RESPIRATION) . INGEST: CALL MD IMMEDIATELY . ============ Fire Fighting Measures ========================= Flash Point Method:OC Flash Point:250F,121C Extinguishing Media:WATER FOG, CO\*2, DRY CHEMICAL & FOAM. Fire Fighting Procedures: WEAR NIOSH/MSHA APPROVED SCBA & FULL PROTECTIVE EQUIPMENT. Unusual Fire/Explosion Hazard: NONE KNOWN TO DOW CORNING. ===== Accidental Release Measures ========== Spill Release Procedures: REMOVE PRODUCT & USE ABSORBENT MATERIAL TO TAKE CARE OF ANY OIL-LIKE RESIDUES. Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

=========== Handling and Storage ============

Handling and Storage Precautions:USE REASONABLE CARE & CAUITON.

Other Precautions:TRACES OF FORMALDEHYDE & OTHER THERMAL DECOMPOSITION PRODUCTS MAY FORM AT TEMPERATURES ABOVE 150C IN THE PRESENCE OF AIR. P

Respiratory Protection: NONE SHOULD BE NEEDED. NIOSH/MSHA APPROVED RESPIRATOR APPROPRIATE FOR EXPOSURE OF CONCERN.

Ventilation: MECHANICAL (GENERAL) RECOMMENDED.

Protective Gloves: IMPERVIOUS GLOVES.

Eye Protection: CHEMICAL WORKERS GOGGLES.

Other Protective Equipment: NONE SPECIFIED BY MANUFACTURER.

Work Hygienic Practices: GOOD PRACT REQS GROSS AMOUNT O

F ANY CHEM BE

REMOVED FROM SKIN AS SOON AS PRACTICAL, ESP BEFORE EATING/SMOKING. (SUP DAT)

Supplemental Safety and Health

HYGIENE PRACT: WASHING AT MEALTIME AND END OF SHIFT IS ADEQUATE.

======== Physical/Chemical Properties ===========

Boiling Pt:B.P. Text:>300F,>149C Vapor Pres: