

INTERNATIONAL LUBRICANT CORP -- RIFLE GREASE -- 9150-00-754-0063

===== Product Identification =====

Product ID:RIFLE GREASE

MSDS Date:09/08/1992

FSC:9150

NIIN:00-754-0063

MSDS Number: BNRQX

=== Responsible Party ===

Company Name:INTERNATIONAL LUBRICANT CORP

Address:NOT KNOWN

City:NEW ORLEANS

State:LA

Country:US

Info Phone Num:804-279-4371 (DGSC-SSH)

Emergency Phone Num:504-555-1212 NOT LISTED!

Pr

Preparer's Name:DGSC-SSH

CAGE:74898

=== Contractor Identification ===

Company Name:INTERNATIONAL LUBRICANTS

Address:10363 AIRLINE HIGHWAY

Box:City:SAINT ROSE

State:LA

ZIP:70087

Country:US

Phone:504-469-0940

CAGE:74898

===== Composition/Information on Ingredients =====

Ingredient Name:PETROLEUM HYDROCARBONS

Other REC Limits:NONE SPECIFIED

OSHA PEL:5 MG/M3 (OIL MIST)

ACGIH TLV:5 MG/M3 (OIL MIST)

Ingredient Name:ADDITIVES

Other REC Limits:NONE SPECIFIED

OSHA PEL:NOT ESTABLISHED.

ACGIH TL

V:NOT ESTABLISHED.

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE- MAY CAUSE EYE IRRITATION.
PROLONGED OR REPEATED SKIN CONTACT MAY CAUSE IRRITATION. INGESTION
IS UNLIKELY. VAPORS MAY CAUSE RESPIRATORY TRACT IRRITATION.
CHRONIC- PROLONGED OR REPEATED SKIN CONTACT MAY CAUSE IRRITATION
AND DRYING OF SKIN.

Effects

of Overexposure:MAY CAUSE EYE IRRITATION. PROLONGED OR REPEATED
SKIN CONTACT MAY CAUSE IRRITATION. INGESTION IS UNLIKELY. VAPORS
MAY CAUSE RESPIRATORY TRACT IRRITATION.

Medical Cond Aggravated by Exposure:PRE-EXISTING SKIN DISORDERS MAY BE
MORE SUSCEPTIBLE TO THIS MATERIAL.

=====
===== First Aid Measures =====

First Aid:EYES:FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. SEE
DOCTOR. SKIN:REMOVE EXCESS WITH CLOTH OR PAPER. WASH SKIN WITH SOAP

AND WATER. INHALATION:REMOVE TO FRESH AIR. INGESTION:SEE DOCTOR
IMMEDIATELY. --IF PRODUCT IS INJECTED UNDER THE SKIN, SEE DOCTOR
IMMEDIATELY REGARDLESS OF APPEARANCE OR SIZE. THIS IS A SERIOUS
MEDICAL EMERGENCY.

=====
===== Fire Fighting Measures =====

Flash Point:>200F,>93C

Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY
CHEMICAL.

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A
FULL FACED SELF CONTAIN
ED BREATHING APPARATUS. WATER MAY CAUSE
FROTHING. COOL FIRE EXPOSED CONTAINERS WITH WATER.

Unusual Fire/Explosion Hazard:COMBUSTION OR HEAT OF FIRE MAY PRODUCE
HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS AND DENSE SMOKE.

=====
===== Accidental Release Measures =====

Spill Release Procedures:SCRAPE UP GREASE. WASH REMAINDER WITH SUITABLE
PETROLEUM SOLVENT. ABSORB IN INERT MATERIAL AND PLACE IN
APPROPRIATE DISPOSAL CONTAINER AND COVER. WASH AREA WITH SOAP AN

D

WATER.

=====
===== Handling and Storage =====

Handling and Storage Precautions: STORAGE- STORE IN COOL, DRY, VENTILATED, LOW FIRE RISK AREA. PROTECT FROM HEAT, OPEN FLAMES AND INCOMPATIBLE MATERIALS. KEEP CONTAINERS CLOSED.

Other Precautions: AVOID BREATHING VAPORS OR MISTS. DO NOT GET IN EYES, ON SKIN OR ON CLOTHING. WASH THOROUGHLY AFTER HANDLING AND BEFORE EATING OR DRINKING. REMOVE CONTAMINATED CLOTHING PROMPTLY. KEEP OUT OF REACH OF CHILDREN.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection: NONE NORMALLY NEEDED.

Ventilation: GENERAL ROOM VENTILATION

Protective Gloves: RUBBER/PLASTIC RECOMMENDED

Eye Protection: SAFETY GOGGLES. FACESHIELD IF HOT.

Other Protective Equipment: OIL RESISTANT APRON, EYE BATH STATION

Work Hygienic Practices: OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES.

Supplemental Safety and Health

NO MSDS WAS AVAILABLE FROM MANUFACTURER. THIS MSDS WAS PREPARED BY THE

PROFESSIONALS OF DGSC-SSH WITHOUT ANY WARRANTY. IT IS THE USER'S RESPONSIBILITY TO GATHER INFORMATION AND USE THE MATERIAL PROPERLY TO PROTECT EMPLOYEES AND ENVIRONMENT.

=====
===== Physical/Chemical Properties =====

HCC: V6

Spec Gravity: