

R.H.CARLSON COMPANY,INC. -- SILICONE SYSTEMS 982 -- 8040-01-331-7127

=====  
Product Identification  
=====

Product ID:SILICONE SYSTEMS 982

MSDS Date:01/01/1987

FSC:8040

NIIN:01-331-7127

MSDS Number: BNRTR

=== Responsible Party ===

Company Name:R.H.CARLSON COMPANY,INC.

Address:41-CHESTNUT STREET

City:GREENWICH

State:CT

ZIP:06830

Country:US

Info Phone Num:203-531-5500

Emergency Phone Num:203-531-5500/

800-424-9300 CHEMTREC

CAGE:33530

=== Contractor Identification ===

Company Name:R.H.CARLSON COMPANY,INC.

Address:41-CHESTNUT STREET

Box:1687

City:GREENWICH

State:CT

ZIP:06830-5921

Country:US

Phone:203-531-5500

CAGE:33530

=====  
Composition/Information on Ingredients  
=====

Ingred Name:NON-HAZARDOUS INGREDIENTS

Fraction by Wt: 100%

Other REC Limits:NONE SPECIFIED

=====  
Hazards Identification  
=====

Routes of Entry: Inhalation:YES Skin:UNKNOWN

Ingestion: YES

Health Hazards Acute and Chronic: WARNING! MAY CAUSE IRRITATION. AVOID CONTACT WITH SKIN, EYES AND CLOTHING, DIRECT CONTACT WITH UNCURED PRODUCT OR ITS VAPORS MAY CAUSE SLIGHT IRRITATION. INHALATION OF THE VAPORS MAY PRODUCE RESPIRATORY IRRITATION. INGESTION OF THE MATERIAL MAY PRODUCE ABDOMINAL PAIN AND DIARRHEA.

=====  
===== First Aid Measures =====

First Aid: INGEST: DON'T INDUCE VOMIT. IF VOMIT OCCURS, GIVE MORE FLUID.  
DR DET  
ERMINES INDUCE VOMIT. DON'T GIVE LIQ TO UNCONSCIOUS PERSON.  
SKIN: FLUSH W/WATER 15 MIN. REMOVE CONTAM CLOTH/SHOES. GET MED AID IF IRRIT. EYE: IMMEDIATELY FLUSH W/WATER 15 MIN. HOLD LIDS OPEN. DON'T USE CHEM TO NEUTRALIZE. OBTAIN MED AID ASAP. FLUSH 15 MIN MORE IF MED AID NOT AVAIL. INHAL: MOVE FROM AREA GET MED AID IF BREATH DIFFICULT.

=====  
===== Fire Fighting Measures =====

Flash Point Method: CC  
Flash Point: 250F, 121C  
Lower Limits: 2.6  
Upper Limits: 12.

8  
Fire Fighting Procedures: PREVENT HUMAN EXPOSURE TO FIRE, SMOKE, FUMES OR COMBUST PROD. EVACUATE NON ESSENTIAL PERSONS. WEAR FULL FACE SCBA & IMPERVIOUS CLOTH. STD FIREFIGHT TECHNIQUES.

=====  
===== Accidental Release Measures =====

Spill Release Procedures: FOLLOW GOOD INDUST HYGIENE. WEAR PROTECT CLOTH & SPLASH GOGGLES. SOAK UP LIQ W/ABSORB. SWEEP UP ABSORBED MAT'L. PLACE IN CHEM WASTE DRUM FOR DISPOSAL. WASH AREA W/DETERGENT & WATER, FLUSH W/WATER. L  
RG : DIKE & PUMP INTO DRUM.

=====  
===== Handling and Storage =====

Handling and Storage Precautions: AVOID EYE/SKIN CONTACT. USE IN WELL VENTILATED AREA. CONTACT WEARERS TAKE APPROP PRECAUTIONS. STORE IN COOL PLACE AWAY FROM HEAT, SPARKS & FLAME.  
Other Precautions: (EMERGENCY/FIRST AID PROCEDURES CONT'D) OXYGEN MAY BE DELIVERED UPON A PHYSICIAN'S ADVICE. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION, PREFERABLY MOUTH TO MOUTH.

=====  
===== Exposure

Controls/Personal Protection =====

Respiratory Protection:IF CONDITIONS GENERATE VAPOR MAT'L SHOULD BE HANDLED IN OPEN/WELL-VENTED AREA. WHERE ADEQUATE VENT NOT AVAILABLE, USE NIOSH ORGANIC VAPOR RESPIRATORS. WHEN HIGHER EXPOSURES, POSITIVE PRESSURE AIR SUPPLY RESPIRATOR IS RECOMMENDED.

Ventilation:LOCAL EXHAUST IS REQUIRED AND GOOD MECHANICAL VENTILATION IS SUGGESTED IN A CLOSED AREA.

Protective Gloves:PLASTIC FILM/RUBBER GLOVES ARE SUGGESTED

Eye Protection:SAFETY GLASSES.

Other Protective Equipment:PROTECTIVE APRON OR COVERALLS.

Work Hygienic Practices:KEEP AWAY FROM HEAT, SPARKS & FLAME. AVOID VAPOR BREATHING & CONTACT W/SKIN & EYES. WASH OR DISCARD CLOTHING & SHOES.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:N1

Vapor Pres:NEGLIGIBLE

Vapor Density:> 1

Spec Gravity:1.05

Viscosity:PASTE

Evaporation Rate & Reference: