View NSN Online: https://aerobasegroup.co.il/nsn/8010-01-333-9447

FARWEST PAINT MANUFACTURING CO. -- EXTERIOR TRIM ENAMEL BROWN 10076 8010-01-333-9447

Product ID: EXTERIOR TRIM ENAMEL BROWN 10076 MSDS Date:09/19/1991 FSC:8010 NIIN:01-333-9447 MSDS Number: BNTVW === Responsible Party === Company Name: FARWEST PAINT MANUFACTURING CO. Address:4522 S. 133RD ST. City:TUKWILA State:WA ZIP:98168 Country:US Info Phone Num:206-244-8 844 Emergency Phone Num:206-941-1619 CAGE:2F266 === Contractor Identification === Company Name: FARWEST PAINT MANUFACTURING CO Address:4522 S 133RD ST City:TUKWILA State:WA ZIP:98168 Country:US Phone:206-244-8844 CAGE:2F266 Ingred Name: ETHYLENE GLYCOL CAS:107-21-1 RTECS #:KW2975000 Fraction by Wt: 4.0% Other REC Limits:NONE SPECIFIED **OSHA PEL:50 PPM** ACGIH TLV:50 PPM EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB Ingred Name: TEXANOL (ESTER

ALCOHOL) CAS:25265-77-4 RTECS #:UF6000000 Fraction by Wt: 2.0% Other REC Limits:NONE SPECIFIED OSHA PEL:100 PPM ACGIH TLV:100 PPM

Ingred Name:VOC: 62 G/L RTECS #:9999999VO Other REC Limits:NONE SPECIFIED

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:ACUTE: INHAL: PROLONGED IN CONFINED AREAS, MAY LEAD TO MUCUS MEMBRANCE IRRIT , DIZZINESS, HEADACHE. SKIN: IRRIT OF THE SKIN. EYE: IRRITATION OF THE EYES. INGESTION: AMOUNTS INGESTED INCIDENTAL TO CONSU MER AND INDUSTRIAL HANDLING ARE NOT LIKELY TO CAUSE INJURY, HOWEVER, INGESTION OF LARGER AMTS COULD CAUSE SERIOUS INJURY Medical Cond Aggravated by Exposure:NONE, WHEN USED IN ACCORDANCE WITH SAFE HANDLING INSTRUCTIONS. (SEE SECTION VIII).

First Aid:INHAL: REMOVE TO FRESH AIR. IF RES PIRATORY SYMPTOMS DEVELOP,

SEEK MEDICAL ATTN AT ONCE. SKIN: WASH OFF QUICKLY WITH PLENTY OF WATER, THEN SOAP & WATER. REMOVE AND WASH CONTAMINATED CLOTHING BEFORE REU SE. EYE: FLUSH IMMEDIATLEY W/LARGE AMOUNTS OF WATER, ESPECIALLY UNDER LIDS, FOR AT LEAST 15 MINUTES. OBTAIN EMERGENCY MEDICAL TREATMENT. INGESTION: IF SWALLOWED, OBTAIN MEDICAL TREATMENT IMMEDIATELY.

Extinguishing Media:FOAM, DRY CHEMICAL

| , WATER OR WATER FOG Fire Fighting Procedures:WATER MAY BE USED TO COOL AND PROTECT EXPOSED CONTAINERS Unusual Fire/Explosion Hazard:WILL NOT BURN, CLOSED CONTAINERS MAY BURST IF EXPOSED TO EXTREME HEAT OR FIRE. |
|---|
| ====================================== |
| Spill Release Procedures:COMPLY WITH ALL APPLICABLE HEALTH AND ENVIRONMENTAL REGULATIONS. VENTILATE AREA. SPILLS MAY BE COLLECTED WITH ABSORBENT MATERIALS. |
| ====================================== |
| Handling and Storage Precautions:AVOID TEMPERATURES BELOW 40F. KEEP FROM FREEZING. STORE CONTAINERS WITH LIDS TIGHTLY CLOSED AND APPROPRIATELY LABELED. |
| ====================================== |
| Respiratory Protection: IF PERSONAL EXPOSURE CANNOT BE CONTROLLED BELOW APPLICABLE LIMITS BY VENTILATION, WEAR A PROPERLY FITTED ORGANIC VAPOR/PARTICULATE RESPIRATOR APPROVED BY NIOSH/OSHA FOR PROTECTION AGAINST MATERIALS IN SECTION I |
| I. Ventilation:LOCAL EXHST PREFERABLE. GEN EXHST ACCEPTABLE IF THE EXPOS TO MATLS IN SECT II IS MAINTAINED BELOW APPLICABLE EXPOS LIMIT Protective Gloves:RECOMMENDED BY GLOVE SUPPLIER Eye Protection:SFTY SPECTACLES W/UNPERFORATED SIDESHLDS Other Protective Equipment:EYE WASH, SAFETY SHOWERS, GOGGLES, SAFETY GLASSES, IMPERVIOUS GLOVES Work Hygienic Practices:KEEP WORK AREA CLEAN/FREE FROM SPILLS/LEAKS. ALWAYS WASH HANDS THOROUGHLY W/SOAP & WATER BEFORE HNDLG FOOD/DRINK/SMOKING Sup plemental Safety and Health |
| USE ONLY WITH ADEQUATE VENTILATION. AVOID BREATHING VAPOR AND SPRAY MIST. AVOID CONTACT WITH SKIN AND EYES. |
| ====================================== |
| Boiling Pt:B.P. Text:212F,100C Vapor Pres:23.8 @ 25C Vapor Density:> THAN AIR Spec Gravity:9-11 LB/GL pH:7-8 Evaporation Rate & amp; Reference:SLOWER THAN ETHER Solubility in Water:INFINITE Appearance and Odor:THIXOTROPIC LIQUID WITH SLIGHT ODOR, COLOR OF TINT. |
| <u>Stabilit</u> |

====== Stabilit

Stability Indicator/Materials to Avoid:YES OXIDIZERS AND/OR HYDROFLUORIC ACID Stability Condition to Avoid:ELEVATED TEMPERATURES, CONTACT WITH OXIDIZING AGENTS Hazardous Decomposition Products:CARBON MONOXIDE AND CARBON DIOXIDE

Waste Disposal Methods:DISPOSE OF ACCORDING TO LOCAL, STATE AND FEDERAL REGULATIONS. AVOID DISCHARGE TO NATURAL WATERS.

Disclaimer (provided with this

information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.