View NSN Online: https://aerobasegroup.co.il/nsn/6750-01-197-7895

ANITEC IMAGE CORP -- REPROLITH 220 DEV/REP, PART B -- 6750-01-197-7895

Product ID:REPROLITH 220 DEV/REP, PART B MSDS Date:01/01/1991 FSC:6750 NIIN:01-197-7895 **MSDS Number: BPCCY** === Responsible Party === Company Name: ANITEC IMAGE CORP Address:40 CHARLES ST Box:4444 City:BINGHAMTON State:NY ZIP:13902 Country:US Info Phone Num:800-234-7707 **Emergency Phone Num:80** 0-424-9300(CHEMTREC)/800-424-9300 CAGE:61263 === Contractor Identification === Company Name: ANITEC IMAGE CORP Address:40 CHARLES ST Box:4444 City:BINGHAMTON State:NY ZIP:13902 Country:US Phone:607-774-3333 CAGE:61263

Ingred Name:POTASSIUM CARBONATE CAS:584-08-7 RTECS #:TS7750000 Fraction by Wt: 10-20% Other REC Limits:NONE RECOMMENDED

Ingred Name:SODIUM CARBONATE CAS:497-19-8 RTECS #:VZ4050000 Fraction by Wt: 1-5% Other REC Limits:NONE RECOMMENDED

Ingred Name:POTASSIUM HYDROXIDE (SARA III) CAS:1310-58-3 RTECS #:TT2100000 Fraction by Wt: 0.1-1% Other REC Limits:NONE RECOMMENDED OSHA PEL:C, 2 MG/M3 ACGIH TLV:C 2 MG/M3; 9293 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name:SODIUM SULFITE CAS:7757-83-7 RTECS #:WE2150000 Fraction by Wt: >5% Other REC Limits:NONE RECOMMENDED

Routes of Entry: Inhalation:NO Skin:YES Ingestion:YES Reports of Car cinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:CAUSTIC SOLUTION MAY BE CORROSIVE TO SKIN OR EYES. Effects of Overexposure:SKIN WILL FEEL SLIPPERY OR SOAPY TO TOUCH. Medical Cond Aggravated by Exposure:SKIN RASHES OE ALLERGIES, OPEN WOUNDS.

First Aid:WASH EXPOSED SKIN OR EYES THOROUGHLY WITH WATER FOR AT LEAST 15 MINUTES. CALL APHYSICIAN IF IRRITATION PERSISTS.

======= Fire

Flash Point:NA Lower Limits:NA Upper Limits:NA Extinguishing Media:WATER, MIST, ALCOHOL FOAM, CARBON DIOXIDE, DRY CHEMICAL. Fire Fighting Procedures:AVOID BREATHING COMBUSTION FUMES.

Unusual Fire/Explosion Hazard:NONE KNOWN.

Spill Release Procedures: CONTAIN SPILL AND NEUTRALIZE WITH DILUTE ACID. ABSORB INTO INERT MATERIALS SUCH AS VERMICULITE, OR FLUSH TO CHEMICAL SEWER OR

WASTE WATER TREATMENT IF PERMITTED.

| ====================================== |
|---|
| Handling and Storage Precautions:KEEP FROM FREEZING IN COOL, DRY STORAGE AREA. |
| Other Precautions: WASH HANDS AFTER USE, BEFORE EATING, USING WASH ROOM OR SMOKING. |
| ====================================== |
| Respiratory Protection:NONE REQUIRED IF USED FOR INTENDED PURPOSES. Ventilation:MECHANICAL(GENERAL) VENTILATION RECOMMENDED. Protective Gloves:CHEMICAL GL OVES |
| Eye Protection:CHEMICAL GOGGLES |
| Other Protective Equipment: CHEMICAL APRON. |
| Work Hygienic Practices:WASH HANDS AFTER DISPENSING OR USING. Supplemental Safety and Health NONE |
| ====================================== |
| HCC:B1 Boiling Pt:B.P. Text:>200F,>93C Melt/Freeze Pt:M.P/F.P Text:SOLUTION Decomp Temp:Decomp Text:NA Vapor Pres:NA Vapor Density:NA Spec Gravity:1.3 pH:13.4 Evaporation Rate & amp; Reference:NA Solubility in Water:COMPLETE Appearance and Odor:CLEAR, COLORLESS, ODORLESS SOLUTION. Percent Volatiles by Volume:NA Corrosion Rate:NA |
| ====================================== |
| Stability Indicator/Materials to Avoid:YES DO NOT MIX WITH STRONG ACIDS. Stability Condition to Avoid:DO NOT FREEZE. Hazardous Decomposition Products:SULFUR OXIDES. |
| ====================================== |
| |

Waste Disposal Methods:DISPOSAL MUST BE MADE IN ACCORDANCE WITH APPLICABLE FEDERAL, STATE AND LOCAL REGULATIONS. Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situa tion.