

ASHLAND CHEMICAL INC -- AMMONIUM HYDROXIDE REAG ACS 4X8# CS -- 6810-00-753-4784

=====
Product Identification
=====

Product ID:AMMONIUM HYDROXIDE REAG ACS 4X8# CS

MSDS Date:06/01/1990

FSC:6810

NIIN:00-753-4784

MSDS Number: BPF DN

=== Responsible Party ===

Company Name:ASHLAND CHEMICAL INC

Box:2219

City:COLUMBUS

State:OH

ZIP:43216

Country:US

Info Phone Num:614-790-3333, 614-889-3844

Emergency Phon

e Num:800-274-5263

CAGE:5A188

=== Contractor Identification ===

Company Name:ASHLAND CHEMICAL CO

Address:5200 PAUL BLAZEL MEMORIAL PARKWAY

Box:City:DUBLIN

State:OH

ZIP:43017

Country:US

Phone:614-889-4505

CAGE:5A188

Company Name:ASHLAND CHEMICAL,ELECTRONIC AND LAB PRODUCTS DIV

Address:RD 4

Box:350

City:EASTON

State:PA

ZIP:18044

Country:US

Phone:215-258-9135

CAGE:86143

=====
Composition/Information on Ingredients
=====

Ingred Name:AMMONIUM HYDROXIDE (SARA III)

CAS:1336-21-6

RTE

CS #:BQ9625000
Fraction by Wt: 72%
Other REC Limits:35 PPM NH3 STEL
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:WATER
CAS:7732-18-5
RTECS #:ZC0110000
Fraction by Wt: 28%
Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

LD50 LC50 Mixture:LD50:ORAL RAT 350 MG/KG
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYES: CAN CAUSE SEVERE IRRITATI
ON, AND
SEVERE OR PERMANENT DAMAGE. SKIN: CAN CAUSE SEVERE IRRITATION,
BLISTERS, AND BURNS. INHALATION: MAY CAUSE IRRITATION OF
RESPIRATORY TRACT WITH SEVERE EXPOSURES R ESULTING IN PULMONARY
EDEMA. INGESTION:CAN CAUSE IRRITATION AND BURNS TO STOMACH, MOUTH,
THROAT, ETC.
Effects of Overexposure:EYES: IRRITATION, REDNESS, TEARING, BLURRED
VISION, PERMANENT DAMAGE. SKIN: IRRITATION BLISTERS, BURNS.
INHALATION: LUNG IRRITATION, COUGHING, DIFFICULTY BREATHING,
SHORTNE
SS OF BREATH, PULMONARY EDEM A. INGESTION: IRRITATION AND
BURNS TO MOUTH, THROAT, STOMACH, NAUSEA, VOMITING, DIARRHEA.
Medical Cond Aggravated by Exposure:PERSONS WITH PRE-EXISTING DISEASES
INVOLVING THE EYES, SKIN OR RESPIRATORY TRACT MAY BE AT INCREASED
RISK FROM EXPOSURE.

===== First Aid Measures =====

First Aid:EYES: FLUSH WITH LARGE AMOUNTS OF WATER. GET MEDICAL
ATTENTION. SKIN: REMOVE CONTAMINATED CLOTHING. FLUSH AREA WITH
LARGE A
MOUNTS OF WATER. GET MEDICAL ATTENTION. INHALATION: MOVE TO
FRESH AIR. IF NOT BREATHING GIVE CPR. IF BREATHING DIFFICULT GIVE
OXYGEN. GET MEDICAL ATTENTION. INGESTION: DO NOT INDUCE VOMITING.
DILUTE BY GIVING WATER. GIVE MILK OF MAGNESIA.KEEP WARM,QUIET. GET
MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Extinguishing Media:WATER FOG.
Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED SCBA WITH FULL
FACEPIECE OPERATED IN POSITIVE PRE

SSURE DEMAND MODE AND FULL BODY
PROTECTION WHEN FIGHTING FIRES.

Unusual Fire/Explosion Hazard:USE WATER TO KEEP FIRE-EXPOSED CONTAINERS
COOL UNTIL FIRE IS OUT.CLOSED CONTAINERS MAY RUPTURE OR EXPLODE DUE
TO PRESSURE BUILD-UP WHEN EXPOSED TO EXTREME HEAT.

===== Accidental Release Measures =====

Spill Release Procedures:ABSORB SMALL SPILL ON VERMICULITE, FLOOR
ABSORBENT, OR OTHER ABSORBENT MATERIAL AND TRANSFER TO HOOD. FLUSH
AREA WITH WATER. DIKE

LARGE SPILLS TO PREVENT SPREADING. RECOVER
LIQUID AND COVER RESIDUE WITH ABSORBENT. SHOVEL WASTE INTO
CONTAINERS.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP IN TIGHTLY CLOSED CONTAINERS.
STORE IN COOL, DRY, VENTILATED AREA AWAY FROM INCOMPATIBLE
MATERIALS. PROTECT AGAINST PHYSICAL DAMAGE.

Other Precautions:CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS WHEN
EMPTY,
SINCE EMPTIED CONTAINERS RETAIN PRODUCT RESIDUES (VAPOR,
LIQUID, AND/OR SOLID).

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF WORKPLACE EXPOSURE LIMITS OF PRODUCT IS
EXCEEDED, A NIOSH/MSHA APPROVED AIR-SUPPLIED RESPIRATOR IS ADVISED
IN ABSENCE OF PROPER ENVIRONMENTAL CONTROL. ENGINEERING OR
ADMINISTRATIVE CONTROLS SHOULD BE IMPLEMENTED TO REDUCE EXPOSURE.

Ventilation:PROVIDE SUFFICIENT MECHANICAL (GENERAL AND/OR LOCAL
EX

HAUST) VENTILATION TO MAINTAIN EXPOSURE BELOW TLV.

Protective Gloves:NEOPRENE, NITRILE RUBBER, BUTYL RUBBER.

Eye Protection:CHEMICAL SPLASH GOGGLES, FACESHIELD.

Other Protective Equipment:IMPERVIOUS PROTECTIVE CLOTHING TO PREVENT
REPEATED OR PROLONGED SKIN CONTACT.

Work Hygienic Practices:WASH AFTER HANDLING AND BEFORE EATING,
DRINKING, OR SMOKING. LAUNDRY CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

===

HCC:B1

Boiling Pt:B.P. Text:82.0F,27.8C

Vapor Pres:570 @ 20C

Vapor Density:0.6(AIR=1)

Spec Gravity:0.899

Evaporation Rate & Reference:SLOWER THAN ETHER.

Solubility in Water:INFINITE

Appearance and Odor:CLEAR, COLORLESS SOLUTION, AMMONIA ODOR.

Percent Volatiles by Volume:100%

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG ACIDS, HYPOCHLORITES, STRONG ALKALIES, BRASS, SILVER, COPPER,
ALKALI METALS, IRON, METALLIC

MERCURY.

Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products:EMITS TOXIC FUMES OF AMMONIA AND
NITRIC OXIDES WHEN HEATED TO DECOMPOSITION.

Conditions to Avoid Polymerization:CANNOT OCCUR.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF WASTE IN ACCORDANCE WITH LOCAL, STATE
AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is f

ormulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.