View NSN Online: https://aerobasegroup.co.il/nsn/3439-01-346-8987

Product ID:ALSOLDER 500 MSDS Date:04/01/1990 FSC:3439 NIIN:01-346-8987 Kit Part:Y MSDS Number: BPHWT === Responsible Party === Company Name: HARRIS J W CO INC Address:10930 DEERFIELD RD. City:CINCINNATI State:OH ZIP:45242-4110 Country:US Info Phone Num:513-891-2000 Emergency Phone Num:800-424-9300 CAGE: JO820

=== Contractor Identification === Company Name: J. W. HARRIS CO., INC Address:10930 DEERFIELD RD Box:City:CINCINNATI State:OH ZIP:45242-4110 Country:US Phone:513-891-2000 CAGE:JO820 Company Name: J. W. HARRIS CO., INC. Address:10930 DEERFIELD ROAD Box:City:CINCINNATI State:OH ZIP:45242-4110 Country:US Phone:513-891-2000 CAGE:27911

Ingred Name:CADMIUM (SARA III) CAS:7440-43-9 RTECS #:EU9800000 Fraction by Wt: 83% Other REC Lim its:NONE RECOMMENDED OSHA PEL:SEE 1910.1027 ACGIH TLV:0.01 MG/M3 DUST;9394 EPA Rpt Qty:10 LBS DOT Rpt Qty:10 LBS

Ingred Name:ZINC (SARA III) CAS:7440-66-6 RTECS #:ZG8600000 Fraction by Wt: 17% Other REC Limits:NONE RECOMMENDED OSHA PEL:10 MG ZNO/M3 ACGIH TLV:10 MG ZNO/M3; 9293 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:YES IARC:YES OSH A:NO

Health Hazards Acute and Chronic:ACUTE: INHALATION OF FUMES MAY CAUSE RESPIRATORY SYSTEM IRRITATION AND METAL FUME FEVER. CHRONIC: PROLONGED OR REPEATED INHALATION OF CADMIUM FUMES MAY CAUSE CANCER.
Explanation of Carcinogenicity:CADMIUM IS LISTED BY NTP AND IARC.
Effects of Overexposure:COUGHING, WHEEZING, SNEEZING, CHILLS, WEAKNESS.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

First Aid:I

NHALED: REMOVE PERSON TO FRESH AIR. GIVE RESPIRATORY SUPPORT IF NEEDED. GET IMMEDIATE MEDICAL ATENTION. EYES: FLUSH WITH LOTS OF WATER FOR 15 MINUTES WHILE HOLDING EYELIDS OPEN. SKIN: WASH WITH SOAP AND WATER. INGESTED: GET IMMEDIATE MEDICAL ATTENTION.

Extinguishing Media:MEDIA APPROPRIATE FOR SURROUNDING FIRE. Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND BUNKER GEAR. Unusual Fire/Expl osion Hazard:NONE SPECIFIED BY MANUFACTURER. Spill Release Procedures: SWEEP UP AND PLACE IN A CONTAINER FOR LATER DISPOSAL. Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER. Handling and Storage Precautions: NONE SPECIFIED BY MANUFACTURER. Other Precautions: NONE SPECIFIED BY MANUFACTURER. == Respiratory Protection: NONE NORMALLY REQUIRED. USE NIOSH/MSHA APPROVED RESPIRATOR OR AIR-SUPPLIED RESPIRATOR IN CONFINED SPACES OR IF TLV IS EXCEEDED. USE IN ACCORDANCE WITH 29 CFR 1910.134. Ventilation: USE ADEQUATE MECHANICAL VENTILATION OR LOCAL EXHAUST TO KEEP EXPOSURE BELOW TLV/PEL. Protective Gloves:WELDERS GLOVES Eye Protection: FACE SHIELD/GLASSES WITH PROPER LENSES Other Protective Equipment: OTHER SAFETY EQUIPMENT AS NEEDED. Work Hygienic Practices: WASH HANDS AFTER USE AND **BEFORE EATING**, DRINKING, OR SMOKING. Supplemental Safety and Health KEY1=N1. HCC:N1 Appearance and Odor:WIRE, GRAY TO SILVER IN COLOR. Stability Indicator/Materials to Avoid:YES NONE SPECIFIED BY MANUFACTURER. Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER. Hazardous Decomposition Products:METAL OXIDE FUMES

====== Disposal

Considerations ================

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek c ompetent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.