

PETROSOURCE REFINING CORP. -- BURNER FUEL -- 9140-00-256-8610

=====
Product Identification
=====

Product ID:BURNER FUEL

MSDS Date:01/01/1992

FSC:9140

NIIN:00-256-8610

MSDS Number: BPKLH

=== Responsible Party ===

Company Name:PETROSOURCE REFINING CORP.

Address:136 EAST SOUTH TEMPLE, SUITE 800

City:SALT LAKE CITY

State:UT

ZIP:84111

Country:US

Info Phone Num:801-350-8300

Emergency Phone Num:800-424-

9300 (CHEMTREC)

CAGE:0F7P6

=== Contractor Identification ===

Company Name:PETROSOURCE REFINING CORP.

Address:136 EAST SOUTH TEMPLE, SUITE 800

Box:City:SALT LAKE CITY

State:UT

ZIP:84111

Country:US

Phone:800-424-9300 (CHEMTREC)

CAGE:0F7P6

=====
Composition/Information on Ingredients
=====

Ingred Name:COMPLEX MIXTURE OF PARAFFINIC, OELIFINIC, NAPHTHANIC, AND
AROMATIC HYDROCARBONS

Fraction by Wt: 100%

Other REC Limits:NONE RECOMMENDED

=====
Hazards Identific
ation
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: INHALATION- CENTRAL NERVOUS
SYTEM EFFECTS. EYES- IRRITATION. SKIN- SEVERE IRRITATION. BURNS AND
BLISTERING. INGESTION- IRRITATION, BURNS, BLISTERING OF MOUTH,

ESOPHAGUS AND STOMACH. CHRONIC: NO NE SPECIFIED BY MANUFACTURER.

Explanation of Carcinogenicity:MANUFACTURER STATES POSSIBLE CARCINOGEN
FROM "DIES

EL EXHAUST".

Effects of Overexposure:INHALATION: DIZZINESS, DROWSINESS, HEADACHE, WEAKNESS, LOSS OF APPETITE. EYES: BURNING SENSATION, REDNESS. SKIN: BURNS, RASH, BLISTERS. INGESTION: BURNING OF MOUTH AND ESOPHAGUS. NAUSEA, VOMITING, STO MACH PAIN.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
===== First Aid Measures =====

First Aid:INHALATION: REMOVE TO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. GET IM
MEDIATE MEDICAL ATTENTION. EYES:
FLUSH WITH PLENTY OF WATER FOR 15 MINUTES. SEE DOCTOR. SKIN: REMOVE CONTAMINATED CLOTHES. WASH WITH SOAP AND WATER. INGESTION: DO NOT INDUCE VOMITING! SEE DOCTOR. SEE DOCTOR IF ANY SYMPTOMS PERSIST.

=====
===== Fire Fighting Measures =====

Flash Point Method:PMCC

Flash Point:125F,52C

Extinguishing Media:WATER FOG, DRY CHEMICAL, FOAM, SAND, EARTH, OR CARBON DIOXIDE.

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHI
NG APPARATUS AND

FULL PROTECTIVE GEAR. USE WATER FOG TO COOL FIRE EXPOSED CONTAINERS AND TO DIPERSE VAPORS.

Unusual Fire/Explosion Hazard:COMBUSTIBLE LIQUID. DO NOT USE SOLID STREAM OF WATER. PROTECT FROM STATIC ELECTRICITY; USE PROPER BONDING AND GROUNDING PROCEDURES.

=====
===== Accidental Release Measures =====

Spill Release Procedures:ISOLATE AND DENY ENTRY. CONTAIN SPILL. ABSORB ON SUITABLE MATERIAL, SCOOP UP AND PLACE IN CONTAINER FOR DISPOSAL.

VENTILATE AREA. USE SELF- CONTAINED BREATHING APPARATUS IN CONFINED AREA. ELIMINATE SO URCES OF IGNITION FROM SPILL AREA.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE AWAY FROM HEAT AND IGNITION SOURCES. HANDLE AND STORE IN ACCORDANCE WITH OSHA REG. 1910.106.

Other Precautions:USE ONLY AS A FUEL. NOT FOR USE AS PORTABLE HEATER OR APPLIANCE FUEL. TOXIC FUMES MAY ACCUMU

LATE AND CAUSE DEATH.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE SELF-CONTAINED BREATHING APPARATUS IF
PEL/TLV EXCEEDED AS IN A LARGE SPILL OR CONFINED AREA.

Ventilation:USE ADEQUATE MECHANICAL VENTILATION.

Protective Gloves:NITRIL, PVA, NEOPRENE

Eye Protection:SAFETY GLASSES/CHEMICAL SPLASH GOGGLES

Other Protective Equipment:EYE WASH STATION & SAFETY SHOWER

Work Hygienic Practices:USE GOOD PERSONAL HYGENE. LAUNDER CONTAMINATED
CLOTHI

NG BEFORE REUSE.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:>408F,>209C

Vapor Pres:NEGLIGIBLE

Vapor Density:>1 (AIR=1)

Spec Gravity:0.8222

Evaporation Rate & Reference: