

SHELL OIL COMPANY -- RU 2000 REGULAR UNLEADED GASOLINE -- 9130-00-148-7102

=====
Product Identification
=====

Product ID:RU 2000 REGULAR UNLEADED GASOLINE

MSDS Date:04/11/1990

FSC:9130

NIIN:00-148-7102

MSDS Number: BPLZY

=== Responsible Party ===

Company Name:SHELL OIL COMPANY

Address:1 SHELL PLAZA

Box:2463

City:HOUSTON

State:TX

ZIP:77001

Country:US

Info Phone Num:713-241-4819

Emergency Phone N

um:713-473-9461 (24 HOUR EMERGENCY)

Preparer's Name:J. C. WILLETT

CAGE:54527

=== Contractor Identification ===

Company Name:SHELL OIL COMPANY

Box:2463

City:HOUSTON

State:TX

ZIP:77210

Country:US

Phone:800-231-6950

CAGE:54527

=====
Composition/Information on Ingredients
=====

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 0-25%

Other REC Limits:NONE SPECIFIED

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LB

S

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 0-25%

Other REC Limits:NONE SPECIFIED

OSHA PEL:100 PPM/150 STEL

ACGIH TLV:100 PPM/150STEL;9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:BENZENE (SARA III)

CAS:71-43-2

RTECS #:CY1400000

Fraction by Wt: 0-5%

Other REC Limits:NONE SPECIFIED

OSHA PEL:1PPM/5STEL;1910.1028

ACGIH TLV:10 PPM; A2; 9192

EPA Rpt Qty:10 LBS

DOT Rpt Qty:10 LBS

Ingred Name:HEXANE (N-HEXANE)

CAS:110-54-3

RTECS #:

MN9275000

Fraction by Wt: 0-3%

Other REC Limits:NONE SPECIFIED

OSHA PEL:500 PPM

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Name:METHYL TERT-BUTYL ETHER (SARA III)

CAS:1634-04-4

RTECS #:KN5250000

Fraction by Wt: 0-11%

Other REC Limits:NONE SPECIFIED

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Name:ALKANES, CYCLOALKANES, ALKANES & AROMATIC HYDROCARBONS.

CAS:68475-59-2

Fraction by Wt: BALANCE

Other REC Limits:NONE RECOMMENDED

Ingred Name:CYCLOHEXANE (SARA III)

CAS:110-82-7

RTE

CS #:GU6300000
Fraction by Wt: 0-1%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:300 PPM
ACGIH TLV:300 PPM, 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:ETHYL BENZENE (SARA III)
CAS:100-41-4
RTECS #:DA0700000
Fraction by Wt: 0-3%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:100 PPM/125 STEL
ACGIH TLV:100 PPM/125STEL 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:NAPHTHALENE (SARA III)
CAS:91-20-3
RTECS #:QJ0525000
Fraction by Wt: 0-1%
Other REC Limits:NONE RECOMMENDED
O
SHA PEL:10 PPM/15 STEL
ACGIH TLV:10 PPM/15 STEL; 9293
EPA Rpt Qty:100 LBS
DOT Rpt Qty:100 LBS

Ingred Name:ALKANES, CYCLOALKANES, ALKENES AND AROMATIC HYDROCARBONS
Fraction by Wt: BALANCE
Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

LD50 LC50 Mixture:LD50 (ORAL RAT) IS >5 GM/KG
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES
Health Hazards Acute and Chronic:EYE-IRRITATION

G. SKIN-PROLONGED OR

REPEATED CONTACT CAN CAUSE DEFATTING & DRYING, RESULTING IN SKIN IRRITATION & DERMATITIS. INHALE-IRRITATION TO THE NOSE, THROAT & RESPIRATORY TRACT & MAY PRODUCE LIVER & KIDNEY DAMAGE. INGEST-MAY BE HARMFUL/FATAL IF SWALLOWED, RESULTING IN VOMITING OR ASPIRATION PNEUMONITIS.

Explanation of Carcinogenicity:BENZENE IS SUSPECTED OF CARCINOGENIC (LUKEMIA) POTENTIAL IN MAN AND IS LISTED BY IARC, NTP AND OSHA.
Effects of Overexposure:GIDDINESS, HEADACHE, D

IZZINESS AND NAUSEA; IN

EXTREME CASES, UNCONCIOUSNESS AND DEATH MAY OCCUR. ASPIRATION PNEUMONITIS CAN SHOW AS COUGHING, LABORED BREATHING AND CYANOSIS. OTHER SIGN ARE CHANGES IN URINE OUTPUT, APPEARANCE OR EDEMA, LOSSOF APPETITE, JAUNDICE AND PAIN IN THE UPPER ABDOMEN ON THE RIGHT SIDE.

Medical Cond Aggravated by Exposure:PREEXISTING EYE, SKIN AND RESPIRATORY DISORDERS MAY BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT. IMPAIRED LIVER AND KIDNEY FUNCTIONS FROM PREEXISTING DISORDERS MAY BE AGGRAVATED BY EXPOSURE.

===== First Aid Measures =====

First Aid:EYE-FLUSH WITH WATER FOR 15 MINUTES. GET MEDICAL ATTENTION. SKIN-FLUSH WITH WATER, REMOVE SOILED CLOTHES/SHOES. WASH WITH SOAP & WATER. INHALE-REMOVE TO FRESH AIR & PROVIDE OXYGEN IF HARD TO BREATH. G IVE CPR IF NOT BREATHING. GET MEDICAL ATTENTION. INGEST-DO NOT INDUCE VOMITING. IF VOMITING OCCURS SPONTANEOUSLY KEEP HEAD BELOW HIPS TO PREVENT ASPIRAT ION OF LIQUID INTO LUNGS. GET MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:-40F,-40C
Autoignition Temp:Autoignition Temp Text:UNK
Lower Limits:1.0
Upper Limits:7.8
Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, DRY CHEMICAL. DO NOT USE WATER DIRECTLY, PRODUCT WILL FLOAT & REIGNITE ON SURFACE.
Fire Fighting Procedures:DO NOT ENTER CONFINED FIRE SPACE WITHOUT FULL BUNKER GEAR INCLUDING A NIOSH POSITIVE PRESSURE SELF CONTAINED BREATHING APPARATUS. COOL CONTAINERS WITH WATER.
Unusual Fire/Explosion Hazard:VAPORS ARE HEAVIER THAN AIR ACCUMULATING IN LOW AREAS & TRAVELING ALONG THE GROUND AWAY FROM THE HANDLING SITE. DO NOT WELD, HEAT OR DRILL NEAR CONTAINER.

===== Accidental Release Measures =====

Spill Release Procedures:WEAR PROTECTIVE EQUIPMENT, ELIMINATE SOURCES OF IGNITION, ISOLATE AREA & DENY ENTRY. DIKE TO RETAIN LARGE SPILL. REMO

VE WITH VACUUM TRUCK OR PUMP TO STORAGE/SALVAGE VESSEL. SOAK UP RESIDUE WITH INERT MATERIAL & FLUSH AREA WITH WATER TO REMOVE RESIDUE

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL, DRY, WELL VENTILATED AREA AWAY FROM SOURCES OF IGNITION. ALL HANDLING EQUIPMENT MUST BE GROUNDED TO PREVENT SPARKING.

Other Precautions:DANGER. EXTREMELY FLAMMABLE. AVOID ALL IGNITION SOURCES & STRONG OXIDIZING AGENTS. HARMFUL OR FATAL IF SWALLOWED.

DO NOT SIPHON GAS BY MOUTH. FOR USE AS A MOTOR FUEL ONLY. DO NOT USE AS A CLEANING SOL VENT OR FOR OTHER NON-MOTOR FUEL USE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:UNDER CONDITIONS OF POTENTIAL HIGH EXPOSURE, USE A NIOSH/MSHA APPROVED RESPIRATOR IS RECOMMENDED, PER CURRENT 29 CFR 1910.134 OR 29 CFR 1910.1028 USE EITHER AN ATMOSPHERE-SUPPLYING RESPIRATOR OR AIR-P URIFYING RESPIRATOR FOR ORGANIC VAPOR

S.

Ventilation:USE EXPLOSION-PROOF VENTILATION AS REQUIRED TO CONTROL VAPOR CONCENTRATIONS.

Protective Gloves:NITRILE RUBBER, VITON/NEOPRENE

Eye Protection:WEAR CHEMICAL GOGGLES.

Other Protective Equipment:SAFETY SHOWER AND EYE BATH. WEAR IMPERVIOUS PROTECTIVE TYPE WORK CLOTHING (NITRILE RUBBER, POLYVINYL ALCOHOL, NEOPRENE)

Work Hygienic Practices:WASH AFTER HANDLING & BEFORE EATING, DRINKING, SMOKING OR USING TOILET. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental S

afety and Health

NOTE TO PHYSICIAN: IF MORE THAN 2.0 ML PER KG HAS BEEN INGESTED & VOMITING HAS NOT OCCURRED, EMESIS SHOULD BE INDUCED WITH MEDICAL SUPERVISION. KEEP VICTIM'S HEAD BELOW HIPS TO PREVENT ASPIRATION. IF SYMPTOMS SUCH AS LOSS OF GAG REFLEX, CONVULSION, ETC OCCUR BEFORE EMESIS, GASTRIC LAVAGE SHOULD BE CONSIDERED.

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:100F,38C

Vapor Pres:7-14.5 PSI

Vapor Density:3.5

Spec Gra

vity:0.72-0.76

Solubility in Water:NEGLIGIBLE

Appearance and Odor:BRONZE COLOR; CLEAR AND BRIGHT LIQUID. HYDROCARBON
ODOR.

Percent Volatiles by Volume:100

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:AVOID HEAT, SPARKS, OPEN FLAMES. PREVENT
VAPOR ACCUMULATION.

Hazardous Decomposition Products:CARBON MONOXIDE AND OTHER UNIDENTIFIED
ORGANIC COMPOUNDS CAN BE FORMED U
PON COMBUSTION.

===== Disposal Considerations =====

Waste Disposal Methods:PRODUCT RECOVERY & RECYCLING IS RECOMMENDED.
DISPOSE OF IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE AND
LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this informa
tion to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.