View NSN Online: https://aerobasegroup.co.il/nsn/2530-01-171-4324

Product ID:BRAKE LINING, NON ASBESTOS FRICTION MATERIAL MSDS Date:03/31/1989 FSC:2530 NIIN:01-171-4324 **MSDS Number: BPPGC** === Responsible Party === Company Name: CARLISLE CORP, MOTION CONTROL INDUSTRIES DIV Address: GILLIS AVE Box:P City:RIDGEWAY State:PA ZIP:15853 Country:US Info Phone Num:814-773-3185 Emergency Phone Num:814-773-3185 Preparer's Name: ROBERT M.TAMI CAGE:65176 === Contractor Identification ===

Company Name:CARLISLE CORP,MOTION CONTROL INDUSTRIES DIV Address:GILLIS AVE Box:P City:RIDGEWAY State:PA ZIP:15853 Country:US Phone:814-773-3185 CAGE:65176

Ingred Name:ALPHA-ALUMINA (ALUMINUM OXIDE) (EPA LISTS ONLY FIBROUS FORMS) (SARA III) CAS:1344-28-1 RTECS #:BD 1200000 Other REC Limits:NONE SPECIFIED OSHA PEL:15 MG/M3 TDUST ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:MINERAL WOOL FIBERS Other REC Limits:SEE ABOVE OSHA PEL:10 MG/M3 TDUST(MFG) ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:BARIUM SULFATE CAS:7727-43-7 RTECS #:CR0600000 Other REC Limits:NONE SPECIFIED OSHA PEL:15 MG/M3 TDUST ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:GROUND COAL Other REC Limits:NONE SPECIFIED OSHA PEL:0.1 MG/M3 RDUST ACGIH TLV:2 MG/M3 RDUST 9192

Ingred Name:CALCIUM CARBO NATE (MARBLE) (LIMESTONE) CAS:1317-65-3 RTECS #:EV9580000 Other REC Limits:NONE SPECIFIED OSHA PEL:15 MG/M3 TDUST ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:GRAPHITE, NATURAL CAS:7782-42-5 RTECS #:MD9659600 Other REC Limits:NONE SPECIFIED OSHA PEL:15 MPPCF RDUST ACGIH TLV:2 MG/M3 RDUST; 9293

Ingred Name:GLASS FIBERS Other REC Limits:NONE SPECIFIED OSHA PEL:5 MG/M3 RDUST ACGIH TLV:10 MG/M3 TDUST; 9192

Ingred Name:MAN MADE FIBERS Other REC Limits:5 MG/M3 (MFG)

Ingred Name: IRON OXIDE (IRON POWD

ERS) CAS:1309-37-1 RTECS #:NO7400000 Other REC Limits:NONE SPECIFIED OSHA PEL:10 MG/M3 (FE) ACGIH TLV:5 MG/M3(FE),B2; 9293

Ingred Name:CELLULOSE (PAPER FIBER) CAS:9004-34-6 RTECS #:FJ5691460 Other REC Limits:NONE SPECIFIED OSHA PEL:15 MG/M3 TDUST ACGIH TLV:10 MG/M3; 9293

Ingred Name:CASHEW/PHENOLIC RESINS Other REC Limits:5 MG/M3 TDUST (MFG) OSHA PEL:10 MG/M3 TDUST ACGIH TLV:10 MG/M3 TDUST 9192

LD50 LC50 Mixture:NONE SPEC

IFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:NON ASBESTOS BRAKE LINING WHEN HANDLED PROPERLY DOES NOT PRESENT A KNOWN HEALTH RISK. WHEN GRINDING, DRILLING, OR REWORKING NECESSARY PRECAUTIONS SHOULD BE TAKEN TO AVOID CREATING DUST. DUST MAY CAUSE EYE, SKIN, NOSE, THROAT, RESPIRATORY, AND PHYSICAL IRRITATION AND PERHAPS ANTHROCOSILICOSIS AND PNEUMOCONIOSIS.

Е

ffects of Overexposure:EYE, SKIN, NOSE, THROAT, AND RESPIRAORY TRACT IRRITATION. RASH MAY DEVELOP ON EMPLOYEES WITH SENSITIVE SKIN. DRYNESS OF THE THROAT AND SHORTNESS OF BREATH INDICATES OVEREXPOSURE TO DUST.

Medical Cond Aggravated by Exposure:NONE KNOWN.

First Aid:SHOULD NOT BE NECESSARY FROM REASONABLE HANDLING OF PRODUCT.

Extinguishing Med

ia:WATER. EXTINGUISHER CLASS A,B,AND C. Fire Fighting Procedures:WEAR POSITIVE PRESSURE, SELF CONTAINED BREATHING APPARATUS.
Unusual Fire/Explosion Hazard:FLAMMABLE ONLY IN OXYGEN RICH ATMOSPHERE.
======================================
<ul> <li>Spill Release Procedures: AVOID CREATING DUST. AVOID SWEEPING OR OTHERWISE GENERATING AIRBORNE PARTICULATE. USE APPROVED VACUUM METHODS FOR CLEANING OR REMOVING DUST FROM BRAKE DRUMS. DO NOT USE COMPRESSED AIR. AVOID B</li> <li>REATHING DUST. USE RESPIRATOR IF DUST BECOMES AIRBORNE.</li> <li>Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.</li> </ul>
======================================
Handling and Storage Precautions:AVOID CREATING EXCESSIVE DUST. USE DUST COLLECTION IF GRINDING, DRILLING, OR ALTERING PRODUCT IN ANY WAY.
Other Precautions: PROTECTIVE CREAMS AND SLEEVES MAY BE NECESSARY FOR EMPLOYEES WITH SENSITIVE SKIN.
======================================
Respiratory Protection:NIOSH APPROVED FOR PNEUMOCONIOSIS AND FIBROSIS PRODUCING DUSTS WITH TLV'S NOT LESS THAN 0.05 MG/M3. SUCH AS 3M 8710. FOLLOW RESPIRATOR STANDARD 1910.34. Ventilation:LOCAL EXHAUST, PER ANSI 29.2-1971 RECOMMENDED TO AVOID CONTACT WITH DUST. Protective Gloves:AS NEEDED.
Eye Protection:OSHA APPROVED SAFETY GLASSES. Other Protective Equipment:PROTECTIVE SLEEVES AND CREAMS FOR EMPLOYEES WITH SENSITIVE SKIN. Work Hygienic Practices:WASH AFTER HANDLING AND BEFOR
E EATING, DRINKING, OR SMOKING. LAUNDER CONTAMINATED CLOTHING SEPARATELY AND BEFORE REUSE. Supplemental Safety and Health
DO NOT REMOVE DUST USING COMPRESSED AIR. WHETHER THE EFFECTS OF SMOKING AND EXPOSURE TO MINERAL WOOL FIBER ARE MORE THAN ADDITIVE IS UNCLEAR, BUT SMOKING BY THESE WORKERS WAS FOUND TO CONTRIBUTE TO TH E HIGHER INCIDENCE OF LUNG CANCER. BECAUSE OF THIS IT IS RECOMMENDED THAT PEOPLE HANDLING MINERAL WOOL NOT SMOKE.

========== Physical/Chemical

Properties ================

HCC:N1 Spec Gravity:1.8-3.5 Evaporation Rate & amp; Reference:0 Solubility in Water:NONE Appearance and Odor:SOLID. LIGHT TAN TO DARK GREY COLOR. SLIGHT SOUR ODOR.

Stability Indicator/Materials to Avoid:YES NONE KNOWN. Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER. Hazardous Decomposition Products:NONE KNOWN. Conditions to Avoid Polymerization:WILL NOT OCCUR.

\_\_\_\_\_

Waste Disposal Methods:DISPOSE OF WASTE IN LANDFILL IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizi ng this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.