View NSN Online: https://aerobasegroup.co.il/nsn/6550-01-238-2385

MICROSCAN -- N,N, DIMETHYLALPHA NAPHTHYLAMINE 0.5% -- 6550-01-238-2385

Product ID:N,N, DIMETHYLALPHA NAPHTHYLAMINE 0.5% MSDS Date:03/09/1987 FSC:6550 NIIN:01-238-2385 **MSDS Number: BPSZB** === Responsible Party === Company Name: MICROSCAN Address:1584 ENTERPRISE BLVD. **City:WEST SACRAMENTO** State:CA ZIP:95691 Country:US Info Phone Num:800-631-7216 **Emergency Phone Nu** m:800-631-7216 CAGE:NO031 === Contractor Identification === Company Name: MICROSCAN Address:1584 ENTEPRISE BLVD **City:WEST SACRAMENTO** State:CA ZIP:95691 Country:US Phone:916-372-1900 CAGE:NO031 Ingred Name:N,N, DIMETHYL-ALPHA-NAPHTHYLAMINE CAS:85-56-6 RTECS #:QM2825000 Fraction by Wt: 0.5% Ingred Name:WATER CAS:7732-18-5 RTECS #:ZC0110000 Fraction by Wt: 72% Ingred Name: ACETIC ACID (GLACIAL) CAS:64-19-7 RTECS #:AF1225000 Frac

tion by Wt: 28% OSHA PEL:10 PPM ACGIH TLV:25 MG/CUM EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

INHALATION: IF BREATHIN G HAS STOPPED, GIVE ARTIFICIAL RESPIRATION. INGESTION: IF SWALLOWED, GIVE WATER IF CONSCIOUS. OBTAIN MEDICAL ATTENTION IN AL L CASES.

Flash Point Method:CC Flash Point:104F Lower Limits:4% Upper Limits:16% Extinguishing Media:ALCOHOL FOAM, WATER SPRAY, DRY-CHEMICAL OR CO2 Fire Fighting Procedures:WEAR APPROVED SELF-CONTAINED BREATHING APPARATUS. COOL FIRE-EXPOSED CONTAINERS W/WATER SPRAY & DILUTE SPILLS W/WATE

R TO NON-FLAMMABLE CONCENTRATIONS.
Unusual Fire/Explosion Hazard:PRODUCES FLAMMABLE VAPOR >140F TOXIC
ORGANIC NITROGEN OXIDES RELEASED DURING NORMAL BREAKDOWN.

Spill Release Procedures:WEAR SUITABLE PROTECTIVE CLOTHES AND MASK. ABSORB SPILL ONTO ABSORBENT MATERIAL SUCH AS VERMICULITE. NEUTRALIZE. WASH SPILL AREA W/SOAP & WATER.

Handling and Stora

ge Precautions: KEEP CONTAINERS TIGHTLY CLOSED, AWAY

FROM HEAT & PROTECTED FROM BREAKAGE. NO SMOKING OR EATING IN STORAGE AREA.

Other Precautions:STORE BETWEEN 65 & 90F. CHEMICAL BREAKDOWN MIGHT PRO DUCE NAPHTHYLAMINE, A CARCINOGEN.

Respiratory Protection:APPROVED ORGANIC VAPOR CARTRIDGE RESPIRATOR Ventilation:LOCAL EXHAUST/MECHANICAL: RECOMMENDED Protective Gloves:IMPERVIOUS Eye Protection:SAFETY GOGGLES Other Pr otective Equipment:APPROVED WORK CLOTHES Work Hygienic Practices:REMOVE/WASH CONTAMINATED CLOTHING BEFORE REUSE. WASH HANDS AFTER USING & BEFORE EATING/SMOKING. Supplemental Safety and Health

Boiling Pt:B.P. Text: 215F Vapor Pres: 25 Vapor Density: 1.8 Spec Gravity: 1.1 Solubility in Water:COMPLETE Appearance and Odor:CLEAR, COLORLESS W/PUNGENT ODOR

Sta

bility Indicator/Materials to Avoid:YES METALS, STRONG OXIDIZERS Stability Condition to Avoid:TEMPERATURES >100F, HEAT Hazardous Decomposition Products:TOXIC ORGANIC NITROGEN

Waste Disposal Methods: HAVE EPA-APPROVED VENDOR REMOVE TO LANDFILL. ALTERNATIVELY MIX W/FLAMMABLE SOLVENT AND INCINERATE. FOLLOW FEDERAL, STATE, & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This in

formation is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.