

OMEGA CHEMICAL PRODUCTS GROUP/FIVE ORGANICS CORP -- 512-15 / OMEGA 2775 --
8030-00-524-9487

=====
Product Identification
=====

Product ID:512-15 / OMEGA 2775

MSDS Date:02/01/1992

FSC:8030

NIIN:00-524-9487

MSDS Number: BPTZV

=== Responsible Party ===

Company Name:OMEGA CHEMICAL PRODUCTS GROUP/FIVE ORGANICS CORP

Address:6935 WEST 62ND STREET

City:CHICAGO

State:IL

ZIP:60638

Country:US

Info Phone Num

:312-586-8000

Emergency Phone Num:800-255-3924

Preparer's Name:PAUL ZALANTIS

CAGE:0B5U9

=== Contractor Identification ===

Company Name:OMEGA CHEMICAL PROD GP, FINE ORGANICS CORP

Address:6935 WEST 62ND STREET

City:CHICAGO

State:IL

ZIP:60638

Country:US

Phone:312-586-8000, 800-424-9300

CAGE:0B5U9

=====
Composition/Information on Ingredients
=====

Ingred Name:PETROLEUM HYDROCARBON

CAS:64475-85-0

RTECS #:PY8240000

Fraction by Wt: 43%

Other REC Limits:NONE SPECIFIED

OSHA PEL:100 PP

M
ACGIH TLV:100 PPM

Ingred Name:PETROLEUM HYDROCARBON
CAS:64742-94-5
RTECS #:SE7546500
Fraction by Wt: 7%
Other REC Limits:NONE SPECIFIED
OSHA PEL:100 PPM
ACGIH TLV:100 PPM

Ingred Name:VOLATILE ORGANIC COMPOUNDS: 3.6 LBS/GAL; 500 GRAMS/LITER
RTECS #:9999999VO
Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Health Hazards Acute and Chronic:ACUTE: HIGH CONCENTRATIONS IRRITATING
TO
EYES AND RESPIRATORY TRACT. HEADACHES, DIZZINESS, NAUSEA.
CHRONIC: MAY CAUSE LOSS OF CONSCIOUSNESS, BURNING TO EYES, SKIN
IRRITATION. INGESTION MAY BE FATAL.
Effects of Overexposure:IRRITATION TO SKIN OR EYES, REDNESS.
Medical Cond Aggravated by Exposure:NONE KNOWN

===== First Aid Measures =====

First Aid:WASH AREAS OF CONTACT WITH GENEROUS AMOUNTS OF WARM WATER AND
MILD SOAP. FOR EYES, FLUSH THOROUGHLY WITH WATER AND SEEK MEDICAL
ATTENTION
IMMEDIATELY. IF INHALED, REMOVE FROM EXPOSURE AND SEEK
MEDICAL ATTENTION IF NECESSARY. IF SWALLOWED, DO NOT INDUCE
VOMITING. CALL A PHYSICIAN IMMEDIATELY.

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:145F,63C
Extinguishing Media:CO2, FOAM, DRY CHEMICAL
Fire Fighting Procedures:TREAT AS HYDROCARBON FIRE
Unusual Fire/Explosion Hazard:NONE

===== Accidental Release Measures =====

Spill Release Proced

ures:IF OUTDOORS, ADD SAND, EARTH OR OTHER SUITABLE
ABSORBENT TO SPILL AREA. KEEP PRODUCT OUT OF SEWERS AND WATER
COURSES BY DIKING OR IMPOUNDING. INSIDE SPILLAGE, ELIMINATE ALL
IGNITION SOURCES AND REMOVE WITH ABSORBENT MATERIAL.

===== Handling and Storage =====

Handling and Storage Precautions:REASONABLE CARE AND PRECAUTIONS WHEN
HANDLING THIS MATERIAL ARE STRONGLY RECOMMENDED.

Other Precautions:REMOVE AND LAUNDRER CONTAMINATED CLOTHING BEFO
RE
REUSE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:CARTRIDGE TYPE FOR SOLVENTS

Ventilation:MECHANICAL, GENERAL; SHOULD BE SUFFICIENT TO REDUCE LEVELS
BELOW TLV.

Protective Gloves:NEOPRENE

Eye Protection:FACE SHIELD AND/OR GOGGLES

Other Protective Equipment:APRON AND/OR SPLASH GUARD

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V4

Boiling Pt:B.P. Text:360F,182C

Melt/Freeze Pt:M.

P/F.P Text:-20F,-29C

Vapor Density: