View NSN Online: https://aerobasegroup.com/nsn/5970-00-223-7275

Product ID:22-204 PRINT KOTE CONFORMAL COATING MSDS Date:07/01/1991 FSC:5970 NIIN:00-223-7275 MSDS Number: BPZHG === Responsible Party === Company Name: GC ELECTRONICS CO, SUB OF HOUSEHOLD INTERNATIONAL C Address:1801 MORGAN ST Box:1209 City:ROCKFORD State :IL ZIP:61105-1209 Country:US Info Phone Num:815-968-9661 Emergency Phone Num:815-968-9661/800-424-9300(CHEMTREC) Preparer's Name:V. HAGEMAN CAGE:EO032 === Contractor Identification === Company Name: GC ELECTRONICS CO, SUB OF HOUSEHOLD INTERNATIONAL C Address:1801 MORGAN ST Box:1209 City:ROCKFORD State:IL ZIP:61105-1209 Country:US Phone:815-968-9661 CAGE:EO032 Company Name: GC THORSEN Address:1801 MORGAN STREET Box:City:ROCKFORD State:IL ZIP:61105 Country:US Phone:815-968-9661 CAGE:72653 Company Na

me:J.G.B. ENTERPRISES Address:115 METROPOLITAN DR Box:209 City:LIVERPOOL State:NY ZIP:13088 Country:US Phone:315-451-2770 CAGE:61125

Ingred Name:SILICONE RESIN Fraction by Wt: 18% Other REC Limits:NONE RECOMMENDED

Ingred Name:TOLUENE (SARA III) CAS:108-88-3 RTECS #:XS5250000 Fraction by Wt: 52% Other REC Limits:NONE RECOMMENDED OSHA PEL:200 PPM/150 STEL ACGIH TLV:50 PPM; 9293 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingre d Name:ISOBUTANE (PROPELLANT) CAS:75-28-5 RTECS #:TZ4300000 Fraction by Wt: SEE # 4% Other REC Limits:1000 PPM

Ingred Name:PROPANE (PROPELLANT) (% SHOWN IS FOR INGREDIENTS 3 AND 4) CAS:74-98-6 RTECS #:TX2275000 Fraction by Wt: 30% Other REC Limits:NONE RECOMMENDED OSHA PEL:1000 PPM ACGIH TLV:ASPHYXIANT; 9293

Ingred Name:BENZENE (SARA III) CAS:71-43-2 RTECS #:CY1400000 Fraction by Wt: 120F MAY CAUSE BURSTING.

Spill Release P

rocedures: IF CONTAINER BEGINS TO LEAK, ALLOW IT TO DISCHARGE COMPLETELY IN A WELL VENTILATED AREA. PICK UP MATERIAL THAT HAS NOT EVAPORATED WITH AN INERT ABSORBENT AND PLACE IN A SEALED METAL CONTAINER FOR DISP OSAL. Handling and Storage Precautions: STORE IN COOL, WELL VENTILATED AREAS. AVOID HIGH TEMPERATURES AND IGNITION SOURCES. DO NOT STORE AT **TEMPERATURES ABOVE 120F.** Other Precautions: KEEP AT ROOM TEMP ERATURE AS EXPOSURE TO SUNLIGHT MAY CAUSE BURSTING. AVOID INHALATION AND REPEATED OR PROLONGED SKIN CONTACT. Respiratory Protection: NIOSH/MSHA-APPROVED RESPIRATOR OR SCBA AS APPROPIATE FOR EXPOSURE OF CONCERN IF TLV IS EXCEEDED. Ventilation: GENERAL MECHANICAL VENTILATION OR LOCAL EXHAUST AS REQUIRED TO KEEP EXPOSURE LEVELS BELOW PEL. Protective Gloves:BUTYL RUBBER. Eye Protection: GOGGLES OR SAFETY GLASSES. Othe r Protective Equipment: AS REQUIRED TO PREVENT PROLONGED CONTACT. EYE WASH STATION AND SAFETY SHOWER. Work Hygienic Practices: WASH THOROUGHLY AFTER HANDLING. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. Supplemental Safety and Health NONE. HCC:V3 Boiling Pt:B.P. Text:N/R,AEROSOL Vapor Pres:4637 Vapor Density:>1 Spec Gravity:0.86

Evaporation Rate & amp; Reference: 1.5 (NO REFERENCE GIVEN)

Solubility in Water: INSOLUBLE Appea

rance and Odor:CLEAR, COLORLESS AEROSOL. TOLUENE ODOR. Percent Volatiles by Volume:91

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:HIGH HEAT, OPEN FLAMES AND OTHER SOURCES OF IGNITION

Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE, INCOMPLETELY BURNED CARBON PRODUCTS.

Waste Disposal

Methods: MANUFACTURER RECOMMENDS INCINERATION OF THE ABSORBED MATERIAL. HMIS RECOMMENDS NOT TO PUNCTURE OR INCINERATE CONTAINERS. DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims

all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.