

ARCOS ALLOYS DIV OF HOSKINS MFG. CO. -- 502 -- 3439-00-204-4512

=====  
Product Identification  
=====

Product ID:502

MSDS Date:11/25/1985

FSC:3439

NIIN:00-204-4512

MSDS Number: BQDHM

=== Responsible Party ===

Company Name:ARCOS ALLOYS DIV OF HOSKINS MFG. CO.

Box:308

City:MT.CARMEL

State:PA

ZIP:17851

Country:US

Info Phone Num:717-339-5200

Emergency Phone Num:717-339-5200

CAGE:03805

=== Contractor I

dentification ===

Company Name:ARCOS ALLOYS DIV OF HOSKINS MFG CO

Address:#1 ARCOS DRIVE

Box:308

City:MTCARMEL

State:PA

ZIP:17851

Country:US

Phone:717-339-5200, CHEMTREC 800-424-9300

CAGE:03805

=====  
Composition/Information on Ingredients  
=====

Ingred Name:CHROMIUM (SARA III)

CAS:7440-47-3

RTECS #:GB4200000

Other REC Limits:NONE RECOMMENDED

OSHA PEL:1 MG/M3

ACGIH TLV:0.5 MG/M3; 9293

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Name:NICKEL (SARA III)

CAS:7440-02-0

RTECS #:QR595

0000  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:1 MG/M3  
ACGIH TLV:1 MG/M3; 9293

=====  
===== Hazards Identification =====

LD50 LC50 Mixture:UNCLASSIFIED WELDING FUMES=5MG/M3 PEL  
Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO  
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO  
Health Hazards Acute and Chronic:CHROMIUM: MAY CAUSE LUNG CHANGES.  
COBALT: MAY CAUSE RESPIRATORY IRRITATION & DISEASE. IRON: MAY CAUSE  
X-RAY CHANGES OF THE LUNGS. MANGANESE  
: MAY CAUSE METAL FUME FEVER,  
AFFECT THE NERVOUS SYSTEM & RES PIRATORY SYSTEM DISEASE.  
MOLYBDENUM: MAY CAUSE IRRITATION. NICKEL: MAY CAUSE RESPIRATORY  
DISEASE & ALLERGIC SKIN RASH.  
Explanation of Carcinogenicity:NICKEL, COBALT-CHROMIUM ALLOYS, AND  
CHROMIUM HAVE BEEN IDENTIFIED BY IARC AND/OR NTP AS POTENTIAL  
CANCER CAUSING AGENTS.  
Effects of Overexposure:EXPOSURE TO WELDING FUMES MAY CAUSE METAL FUME  
FEVER WITH SYMPTOMS OF CHILLS, FEVER, NAUSEA, COUGH, DRY THROAT,  
WEA  
KNESS, MUSCLE ACHES, AND A SWEET OR METALLIC TASTE IN THE MOUTH.  
PROLONGED OR REPEATE D EXPOSURE MAY CAUSE DIFFICULTY IN WALKING,  
WEAKNESS OR CRAMPS IN THE LEGS, HOARSENESS, MEMORY LOSS, SKIN  
SENSITIZATION.  
Medical Cond Aggravated by Exposure:PRE-EXISTING CHRONIC SKIN, EYE OR  
RESPIRATORY DISORDERS MAY BE AGGRAVATED IF INDIVIDUALS ARE  
REPEATEDLY OVEREXPOSED TO FUMES AND DUST.

=====  
===== First Aid Measures =====

First Aid:INHALATION: REMOVE TO  
FRESH AIR. IF RESPIRATORY SYMPTOMS  
DEVELOP, CONSULT A PHYSICIAN. EYE: FLUSH IMMEDIATELY WITH LARGE  
AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. GET MEDICAL ATTENTION.  
SKIN: WASH WIT H SOAP AND WATER. IF IRRITATION PERSISTS, GET  
MEDICAL ATTENTION. INGESTION: INGESTION OF LARGE ENOUGH QUANTITIES  
TO CAUSE HEALTH EFFECTS IS UNLIKELY. GET MEDICAL ATTENTION IF  
NECESSARY.

=====  
===== Fire Fighting Measures =====

Extinguishing Media:USE WATER FOG, CARB

ON DIOXIDE, FOAM, OR DRY  
CHEMICAL.

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A  
FULL FACED SELF CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:NONE

===== Accidental Release Measures =====

Spill Release Procedures:CLEAN UP ANY GRINDING DUST OR WASTE RESIDUES  
AND PLACE IN SUITABLE DOT APPROVED CONTAINERS AND DISPOSE OF IN  
FULL COMPLIANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS. AVOID  
INHALATION AND SKIN EXP  
OSU RE.

===== Handling and Storage =====

Handling and Storage Precautions:WEAR GLOVES AND FLAME RETARDANT  
CLOTHING WHEN CUTTING, GRINDING OR WELDING. DO NOT EXPOSE SKIN TO  
RADIATION WHEN HOT CUTTING OR WELDING.

Other Precautions:PROVIDE PROTECTIVE SCREENS TO SHIELD OTHERS. WHEN  
ELECTRODES AND FLUXES ARE CONSUMED, THE FUME AND GAS DECOMPOSITION  
PRODUCTS GENERATED ARE DIFFERENT IN FORM FROM THE INGREDIENTS  
LISTED. NEW COMPOUNDS NOT IN THE E  
LECTRODES MAY FORM.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:WEAR NIOSH APPROVED RESPIRATORS FOR PROTECTION  
AGAINST AIRBORNE DUST OR FUMES. RESPIRATORS SHOULD BE USED IN  
ACCORDANCE WITH 29CFR 1910.134.

Ventilation:USE LOCAL AND GENERAL VENTILATION TO KEEP AIRBORNE  
CONCENTRATIONS OF DUST OR FUMES BELOW THE TLV DURING USE.

Protective Gloves:WELDERS LEATHER GLOVES

Eye Protection:OSHA APPROVED GOGGLES/FACE SHIELD W/LENS

Other Protective

Equipment:BARRIER CREAMS MAY BE NECESSARY TO PREVENT  
SKIN SENSITIZATION AND DERMATITIS.

Work Hygienic Practices:WASH THOROUGHLY BEFORE EATING OR SMOKING.  
LAUNDRER CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

WELDING AND HOT CUTTING FUMES & GASES CANNOT BE CLASSIFIED SIMPLY.  
THEIR COMPOSITION AND QUANTITY ARE DEPENDENT ON THE METAL BEING  
WELDED, THE PROCEDURES, PROCESSES AND THE TYPE OF WIRE OR  
ELECTRODES USED. OTHER INFLUENCING FACTORS ARE THE PRESENCE O

F

CONTAMINANTS. CHLORINATED SOLVENTS MAY DECOMPOSE TO TOXIC GASES.

===== Physical/Chemical Properties =====

HCC:N1

Vapor Pres:0

Solubility in Water:NEGLIGIBLE

Appearance and Odor:STEEL ROD

Percent Volatiles by Volume:0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:HIGH HEAT, OPEN FLAMES AND OTHER SOURCES  
OF IGNITION

Hazardous Decomposition

Products:WELDING AND CUTTING OPERATION MAY

INCLUDE OXIDES OF THE METALS, CHROMATES, FLUORIDES, COMPLEX  
METALLICS, AND OZONE.

===== Disposal Considerations =====

Waste Disposal Methods:RECYCLE OR DISPOSE IN ACCORDANCE WITH FEDERAL,  
STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no mann

er whatsoever,

expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.