View NSN Online: https://aerobasegroup.com/nsn/6810-00-006-4205

Product ID: ETHYLENE GLYCOL TECH MSDS Date:05/31/1989 FSC:6810 NIIN:00-006-4205 **MSDS Number: BQLYP** === Responsible Party === Company Name: ASHLAND CHEMICAL COMPANY Box:2219 City:COLUMBUS State:OH ZIP:43216-2219 Country:US Info Phone Num:800-274-5263 Emergency Phone Num:800-274-5263 CAGE:34897 === Contractor Identification === Company Name: ASHLAND CHEMICAL CO Box:2219 City:COLUMBUS State:OH ZIP:43216-2219 Country:US Phone:614-790-3333/800-274-5263 CAGE:34897 **Company Name: TEXAS INSTRUMENTS INC DEFENSE SYSTEM & ELECTRONICS** Address:8505 FOREST LN Box:660246 City:DALLAS State:TX ZIP:75266-0246 Country:US CAGE:96214

Ingred Name:ETHYLENE GLYCOL (SARA III) CAS:107-21-1 RTECS #:KW2975000 Fraction by Wt: 100% Other REC Limits: NONE SPECIFIED OSHA PEL:C 50 PPM ACGIH TLV:C 50 PPM,VAPOR; 9192 EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

LD50 LC50 Mixture:PEL=50PPM;TLV=50PPM (BOTH CEILING)
Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYES:IRRITANT.SKIN:SLIGHT
IRRITANT.INHAL:NASAL AND RESPIRATORY IRRITATION.INGEST:CAN CAUSE GASTROINTESTINAL IRRITATION.CHRONIC E
FFECTS ARE BIRTH
DEFECTS,KIDNEY AND LIVER DAMAGE AND CENTRAL NERVOUS SYS TEM EFFECTS.
Explanation of Carcinogenicity:RTECS 92-4 SHOWS MONOGRAPHS ON ETHYLENE GLYCOL AS A MUTAGEN,TUMORIGEN,REPRODUCTIVE EFFECTOR.
Effects of Overexposure:INGEST:NAUSEA,VOMITING,DIARRHEA.
Medical Cond Aggravated by Exposure:HMIS SUGGESTS THAT PERSONS WITH A HISTORY OF KIDNEY OR LIVER DISORDERS MAYBE AT INCREASED RISK FROM EXPOSURE.

First Aid:EYE:FLUSH W/ WATER 15 MIN HOLD LIDS OPEN. SKIN:REMOVE CONTAMINATED CLOTHING AND LAUNDER BEFORE REUSE. WASH WITH SOAP & WATER. INHALED:REMOVE TO FRESH AIR. RESTORE BREATHING IF NECESSARY. INGESTED:GIVE 2 GLASSES WATER AND INDUCE VOMITING(BYIPECAC OR FINGER DOWN THROAT). GIVE NOTHING BY MOUTH IF UNCONSCIOUS. GET IMMEDIATE MEDICAL CARE. IF IRRITATION PERSISTS,OR IS SEVERE,SEE A DOCTOR.

Flas h Point Method:TCC Flash Point:232F,111C Lower Limits:3.2 Upper Limits:15.3 Extinguishing Media:USE CARBON DIOXIDE, DRY CHEMICAL, OR WATER FOG.WATER OR FOAM MAY CAUSE FROTHING. Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS. EVACUATE AREA. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY. Unusual Fire/Explosion Hazard:CONTAINERS ARE AN EXPLOSION HAZARD.

Spill Release Procedures:WIPE/SOAK UP WITH PAPER TOWEL OR INERT ABSORBENT. PUT IN DISPOSAL CONTAINER. FLUSH RESIDUE WITH WATER. LARGE SPILL: VENTILATE AREA. IF POSSIBLE, STOP LEAK. DIKE TO RETAIN RUN OFF. VACUUM UP FREE LIQUI D. FLUSH RESIDUE WITH WATER. Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling and Storage Precautions: STORE IN A COOL, DRY, WELL VENTILATED AREA. KEEP CONTAINERS TIGHTLY CL OSED WHEN NOT IN USE. PROTECT CONTAINERS FROM PHYSICAL DAMAGE. Other Precautions: 'EMPTY' CONTAINERS MAY CONTAIN RESIDUE OR VAPOR. DO NOT PRESSURIZE, CUT, WELD, BRAZE, ETC. NEAR THEM. Respiratory Protection: RESPIRATOR WILL NOT NORMALLY BE NECESSARY. USE NIOSH/MSHA APPROVED RESPIRATOR FOR ORGANIC DUST/MIST IF EXPOSURE IS ABOVE THE TLV/PEL. SEE 29 CFR 1910.134 FOR REGULATIONS PERTAINING TO RESPIRATOR USE. Ventilat ion:NORMAL VENTILATION IS USUALLY SUFFICIENT. SUPPLEMENT WITH LOCAL EXHAUST IF PEL/TLV IS EXCEEDED. Protective Gloves: NEOPRENE, NITRILE, PVC OR NATURAL RUBBER Eye Protection: SAFETY GLASSES OR SPLASH GOGGLES Other Protective Equipment: EYE WASH STATION AND SAFETY SHOWER. AVOID PROLONGED AND/OR REPEATED CONTACT BY USING APPROPRIATE CLOTHING. Work Hygienic Practices: USE GOOD CHEMICAL HYGIENE PRACTICE. AVOID UNNECESSARY CONTACT. WASH THOROUGHLY BEFORE EATING OR DRINKING. Supplemental Safe ty and Health POISONOUS. 

HCC:V5 Boiling Pt:=192.8C, 379.F Vapor Pres:0.1 Vapor Density:2.2 Spec Gravity:1.115 Evaporation Rate & amp; Reference:

===