View NSN Online: https://aerobasegroup.co.il/nsn/6810-01-008-4316

ASHLAND CHEMICAL COMPANY -- ETHYLENE GLYCOL TECH -- 6810-01-008-4316

========= Product Identification ============

Product ID:ETHYLENE GLYCOL TECH

MSDS Date:05/31/1989

FSC:6810

NIIN:01-008-4316

MSDS Number: BQMHV === Responsible Party ===

Company Name: ASHLAND CHEMICAL COMPANY

Box:2219

City:COLUMBUS

State:OH

ZIP:43216-2219 Country:US

Info Phone Num:800-274-5263

Emergency Phone Num:800-274-5263

CAGE:34897

=

== Contractor Identification ===

Company Name: ASHLAND CHEMICAL CO

Box:2219

City:COLUMBUS

State:OH

ZIP:43216-2219

Country:US

Phone:614-790-3333/800-274-5263

CAGE:34897

Company Name: TEXAS INSTRUMENTS INC DEFENSE SYSTEM & ELECTRONICS

Address:8505 FOREST LN

Box:660246 City:DALLAS State:TX

ZIP:75266-0246 Country:US CAGE:96214

======= Composition/Information on Ingredients ========

Ingred Name: ETHYLENE GLYCOL (SARA III)

CAS:107-21-1

RTECS #:KW2975000 Fraction by Wt: 100% Other REC Limit

s:NONE SPECIFIED OSHA PEL:C 50 PPM
ACGIH TLV:C 50 PPM,VAPOR; 9192
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB
========== Hazards Identification ===========
LD50 LC50 Mixture:PEL=50PPM;TLV=50PPM (BOTH CEILING) Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:EYES:IRRITANT.SKIN:SLIGHT IRRITANT.INHAL:NASAL AND RESPIRATORY IRRITATION.INGEST:CAN CAUSE GASTROINTESTINAL IRRITATION.CHRONIC EFFECTS ARE BIRTH DEFECTS,KIDNEY AND LIVER DAMAGE AND CENTRAL NERVOUS SYS TEM
EFFECTS.
Explanation of Carcinogenicity:RTECS 92-4 SHOWS MONOGRAPHS ON ETHYLENE GLYCOL AS A MUTAGEN,TUMORIGEN,REPRODUCTIVE EFFECTOR. Effects of Overexposure:INGEST:NAUSEA,VOMITING,DIARRHEA. Medical Cond Aggravated by Exposure:HMIS SUGGESTS THAT PERSONS WITH A HISTORY OF KIDNEY OR LIVER DISORDERS MAYBE AT INCREASED RISK FROM EXPOSURE.
======================================
====
First Aid:EYE:FLUSH W/ WATER 15 MIN HOLD LIDS OPEN. SKIN:REMOVE CONTAMINATED CLOTHING AND LAUNDER BEFORE REUSE. WASH WITH SOAP & WATER. INHALED:REMOVE TO FRESH AIR. RESTORE BREATHING IF NECESSARY. INGESTED:GIVE 2 GLASSES WATER AND INDUCE VOMITING(BYIPECAC OR FINGER DOWN THROAT). GIVE NOTHING BY MOUTH IF UNCONSCIOUS. GET IMMEDIATE MEDICAL CARE. IF IRRITATION PERSISTS,OR IS SEVERE,SEE A DOCTOR.
============= Fire Fighting Measures ==============
FI ash Point Method:TCC Flash Point:232F,111C Lower Limits:3.2 Upper Limits:15.3 Extinguishing Media:USE CARBON DIOXIDE, DRY CHEMICAL, OR WATER FOG.WATER OR FOAM MAY CAUSE FROTHING.
Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS. EVACUATE AREA. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY.

Unusual Fire/Explosion Hazard: CONTAINERS ARE AN EXPLOSION HAZARD.

======== Accidental Release Measures ========

Spill Release Procedures:WIPE/SOAK UP WITH PAPER TOWEL OR INERT ABSORBENT. PUT IN DISPOSAL CONTAINER. FLUSH RESIDUE WITH WATER. LARGE SPILL: VENTILATE AREA. IF POSSIBLE, STOP LEAK. DIKE TO RETAIN RUN OFF. VACUUM UP FREE LIQUI D. FLUSH RESIDUE WITH WATER. Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

========== Handling and Storage ==============

Handling and Storage Precautions:STORE IN A COOL, DRY, WELL VENTILATED AREA. KEEP CONTAINERS TIGHTLY

CLOSED WHEN NOT IN USE. PROTECT CONTAINERS FROM PHYSICAL DAMAGE.

Other Precautions: EMPTY' CONTAINERS MAY CONTAIN RESIDUE OR VAPOR. DO NOT PRESSURIZE, CUT, WELD, BRAZE, ETC. NEAR THEM.

===== Exposure Controls/Personal Protection ========

Respiratory Protection:RESPIRATOR WILL NOT NORMALLY BE NECESSARY. USE NIOSH/MSHA APPROVED RESPIRATOR FOR ORGANIC DUST/MIST IF EXPOSURE IS ABOVE THE TLV/PEL. SEE 29 CFR 1910.134 FOR REGULATIONS PERTAINING TO RESPIRATOR USE.

Ventil

ation:NORMAL VENTILATION IS USUALLY SUFFICIENT. SUPPLEMENT WITH LOCAL EXHAUST IF PEL/TLV IS EXCEEDED.

Protective Gloves: NEOPRENE, NITRILE, PVC OR NATURAL RUBBER

Eye Protection: SAFETY GLASSES OR SPLASH GOGGLES

Other Protective Equipment: EYE WASH STATION AND SAFETY SHOWER. AVOID PROLONGED AND/OR REPEATED CONTACT BY USING APPROPRIATE CLOTHING.

Work Hygienic Practices: USE GOOD CHEMICAL HYGIENE PRACTICE. AVOID UNNECESSARY CONTACT. WASH THOROUGHLY BEFORE EATING OR DRINKING.

Supplemental Sa fety and Health

PÓISONOUS.

HCC:V5

Boiling Pt:=193.C, 379.4F

Vapor Pres:0.1 Vapor Density:2.2 Spec Gravity:1.115

Evaporation Rate & Deference: