View NSN Online: https://aerobasegroup.co.il/nsn/6830-01-111-8264

MINE SAFETY APPLIANCES CO -- MSA P/N 473583 STEEL CYLINDER AND VALVE ASS

1045-01-111-8264

Product ID:MSA P/N 473583 STEEL CYLINDER AND VALVE ASS

MSDS Date:03/01/1990

FSC:1045

NIIN:01-111-8264

MSDS Number: BQMKN === Responsible Party ===

Company Name: MINE SAFETY APPLIANCES CO

Address:3880 MEADOWBROOK RD

City:MURRYSVILLE

State:PA

ZIP:15668-1753 Country:US

Inf

o Phone Num:412-325-1313

Emergency Phone Num:412-325-1313

CAGE:55799

=== Contractor Identification ===

Company Name: MINE SAFETY APPLIANCES CO DBA MSA

Address:3880 MEADOWBROOK RD

Box:City:MURRYSVILLE

State:PA

ZIP:15668-1753 Country:US

Phone:724-733-9272

CAGE:55799

======= Composition/Information on Ingredients ========

Ingred Name: OXYGEN

CAS:7782-44-7

RTECS #:RS2060000 Fraction by Wt: 21% %

Other REC Limits: NONE SPECIFIED

Ingred Name:NITROGEN

CAS:7727-37-9

RTECS #:QW9700000

Fracti

Other REC Limits: NONE SPECIFIED ACGIH TLV:ASPHYXIANT; 9192 ============= Hazards Identification ======================== LD50 LC50 Mixture:LD50 (ORAL RAT) IS NOT APPLICABLE. Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: ACUTE: PHYSICAL INJURY DUE TO RUPTURE/ EXPLOSION OF CONTAINER. INJECTION OF COMPRESSED AIR INTO THE BLOOD STREAM. Explanation of Carcinogenicity: NONE OF THE COMPOUNDS IN THIS PRODUCT IS LISTED BY IARC, N TP, OR OSHA AS A CARCINOGEN. Effects of Overexposure:NONE Medical Cond Aggravated by Exposure: NONE First Aid:GET IMMEDIATE MEDICAL CARE FOR THOSE INJURED BY EXPLODING CYLINDERS OR IF AIR IS SUSPECTED TO HAVE BEEN INJECTED INTO THE BLOOD STREAM. Flash Point: NON-FLAMMABLE Extinguishing Media: PRODUCT IS NON FLAMMABLE. EXTINGUISH FIRE WITH MEDIA AP PROPRIATE FOR SOURCE OF FIRE. Fire Fighting Procedures: WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY. Unusual Fire/Explosion Hazard: CONTAINS AIR UNDER 2200 PSI. CONTAINERS EXPOSED TO HEAT MAY RUPTURE OR EXPLODE. ======== Accidental Release Measures ============ Spill Release Procedures: NONE Neutralizing Agent: NOT APPLICABLE.

on by Wt: 79% %

Handling and Storage Precautions:PROTECT CYLINDERS FROM PHYSICAL DAMAGE. STORE AWAY FROM EXTREME HEAT (BELOW 125F). KEEP CYLINDER VALVES CLOSED WHEN NOT IN USE AND WHEN EMPTY.

Other Precautions:DO NOT DEFACE CYLINDERS OR LABELS. USE ALL RECOMMENDED SAFETY PROCEDURES WHEN HANDLING CYLINDERS. READ AND OBEY ALL INSTRUCTIONS ON LABEL.

====== Exposure Controls/Personal Protection ========

Protective Gloves: WORK GLOVES FOR HANDLING CYLINDERS.

Eye P

rotection: APPROVED SAFETY GLASSES OR FACE SHIELD.

Other Protective Equipment: SAFETY SHOES AND HEARING PROTECTION.

Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. USE PROPER CARE WHEN HANDLING AND STORING CYLINDERS.

Supplemental Safety and Health

THIS IS BREATHING AIR.

======== Physical/Chemical Properties ===========

HCC:G3

Boiling Pt:B.P. Text:-318F,-194C

Vapor Density:1.0

Solubility in Water:1.87%
Appearance and Odor:COLO
RLESS, ODORLESS GAS

Percent Volatiles by Volume:100

======== Stability and Reactivity Data ===========

Stability Indicator/Materials to Avoid:YES

NOT RELAVENT

Stability Condition to Avoid: HIGH HEAT, OPEN FLAMES

Hazardous Decomposition Products:NONE

======= Disposal Considerations ==========

Waste Disposal Methods:RELEASE PRESSURE SAFELY BEFORE DISPOSAL OF CYLINDER. DISPOSEMUST BE IN ACCORDANCE WITH FEDERAL, STATE, LOCAL REGULATIONS.

Disclai

mer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.