

PRATT AND LAMBERT INC -- LAC SPRAYING RED 11105 ID 793102 -- 8010-00-577-4524

=====  
Product Identification  
=====

Product ID:LAC SPRAYING RED 11105 ID 793102

MSDS Date:07/15/1992

FSC:8010

NIIN:00-577-4524

MSDS Number: BQWBY

=== Responsible Party ===

Company Name:PRATT AND LAMBERT INC

Address:16116 E 13TH ST

Box:2153

City:WICHITA

State:KS

ZIP:67201

Country:US

Info Phone Num:316-733-1361

Emergency P

hone Num:716-873-6000

Preparer's Name:W. A. ELLISON

CAGE:61196

=== Contractor Identification ===

Company Name:PRATT AND LAMBERT INC

Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

=====  
Composition/Information on Ingredients  
=====

Ingred Name:VM&P NAPHTHA (SOLVENT) (VAPOR PRESSURE 40 MM HG @ 20 C)  
(LFL 1.0; UFL 6.0)

CAS:8030-30-6

RTECS #:DE3030000

Fraction by Wt: 5%

Other REC Limits:NONE SPECIFIED

OSHA PEL:300 PPM/STEL 400 PPM

ACGI

H TLV:300 PPM/1350 MG/M3

Ingred Name:ISOBUTYL ALCOHOL (SOLVENT) (VAPOR PRESSURE 10 MM HG @ 20C)  
(LFL 1.0 / UFL 11.0)

CAS:78-83-1

RTECS #:NP9625000

Fraction by Wt: 5%

Other REC Limits:NONE SPECIFIED

OSHA PEL:100 PPM

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:PROPYLENE GLYCOL /METHYL ETHER ACETATE (SOLVENT) (VAPOR  
PRESSURE 2 MM HG @ 20 C)

CAS:108-65-6

RTECS #:AI8925000

Fraction by Wt: 10%

Other REC Limits:NONE SPECIFIED

OSHA PEL:NONE ESTABLISHED

ACGIH TL

V:NONE ESTABLISHED

Ingred Name:DI(2-ETHYLHEXYL)PHTHALATE (ADDITIVE) (SARA 313)

CAS:117-81-7

RTECS #:TI0350000

Fraction by Wt: THAN AIR

Spec Gravity:0.9

pH:4-7STD

Viscosity:15-35 SEC

Evaporation Rate & Reference:SLOWER THAN DIETHYL ETHER

Solubility in Water:SLIGHT

Appearance and Odor:LIQUID, SOLVENT ODOR

Percent Volatiles by Volume:76%

Corrosion Rate:NA

=====  
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG ACIDS OR ALKALINE M

ATERIALS. OXIDIZING MATERIALS.

Stability Condition to Avoid:EXCESSIVE HEAT (>115F (46 C) AND SOURCES OF IGNITION.

Hazardous Decomposition Products:BURNING-INCLUDING WHEN HEATED BY WELDING/CUTTING, PRODUCES SMOKE-CARBON MONOXIDE-CARBON DIOXIDE-POSS OXIDES OF NITROGEN.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE W/FEDERAL-STATE-LOCAL LAWS/REGS. INCINERATE ONLY IN EPA FACILITY. DO NOT INCINERATE CLOSED CNTNRS

. OBSERVE PRECAUTIONS FOR DISPOSAL OF FLAMMABLE MATERIALS. DISPOSE CONTAMINATED A BSORBANT IN HAZARDOUS WASTE LANDFILL. RCRA-D001.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should

seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.