

MINNESOTA MINING AND MFG CO -- SOF-LEX XT FINISHING AND POSLISHING DISCS --
6520-01-327-4843

===== Product Identification =====

Product ID:SOF-LEX XT FINISHING AND POSLISHING DISCS

MSDS Date:04/16/1992

FSC:6520

NIIN:01-327-4843

MSDS Number: BQWPY

=== Responsible Party ===

Company Name:MINNESOTA MINING AND MFG CO

Address:3M CTR 224-2S-25

City:ST. PAUL

State:MN

ZIP:55144-1000

Country:US

Info Phon

e Num:612-733-1341/612-733-1110

Emergency Phone Num:612-733-1341

CAGE:76381

=== Contractor Identification ===

Company Name:MINNESOTA MINING AND MFG CO, DBA 3M

Address:3M CENTER BLDG 224-5S-04

Box:City:SAINT PAUL

State:MN

ZIP:55144-1000

Country:US

Phone:866-556 5712 / 612-733-1110

CAGE:76381

===== Composition/Information on Ingredients =====

Ingred Name:POLYESTER FILM

Fraction by Wt: 33 - 90%

Other REC Limits:NONE RECOMMENDED

Ingred Name:ALUMINUM OXIDE GRIT AND BINDER

Fracti

on by Wt: 10 - 67%

Other REC Limits:NONE RECOMMENDED

=====
===== Hazards Identification =====

LD50 LC50 Mixture:LD50 (ORAL RAT) NOT KNOWN

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE- MECHANICAL EYE AND SKIN

IRRITATION. NONVOLATILE. NO ADVERSE EFFECTS EXPECTED IF INHALED.

INGESTION IS UNLIKELY. CHRONIC- UNKNOWN.

Effects of Overexposure:EYE AND SKIN IRRITATION,

REDNESS, ITCHING,

SCRATCHING OF THE CORNEA AND TEARING

Medical Cond Aggravated by Exposure:PRE-EXISTING SKIN DISORDERS MAY BE

MORE SUSCEPTIBLE TO THIS MATERIAL.

=====
===== First Aid Measures =====

First Aid:GET MEDICAL ATTENTION IF SYMPTOMS PERSIST. EYE:FLUSH WITH

WATER FOR 15 MINUTES. HOLD EYELIDS OPEN. SKIN:WASH WITH SOAP AND

WATER. INHALED/INGESTED:NOT RELEVANT

=====
===== Fire Fighting Measures =====

Extinguish

ing Media:WATER

Fire Fighting Procedures:WEAR NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:NONE

=====
===== Accidental Release Measures =====

Spill Release Procedures:PLACE IN AN APPROVED METAL CONTAINER AND SEAL

Neutralizing Agent:NOT RELEVANT

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN SEALED CONTAINERS.

Other Precautions:WASH THOROUGHLY AFTER HANDLING MATERIAL.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY REQUIRED.

Ventilation:ADEQUATE

Protective Gloves:NONE REQUIRED

Eye Protection:AVOID EYE CONTACT

Other Protective Equipment:EYE WASH STATION

Work Hygienic Practices:WASH HANDS BEFORE EATING OR DRINKING.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:N1

Melt/Freeze Pt:M.P/F.P Text:NOT KNOWN

Spec Gravity:NOT KNOWN

Viscosity:NOT RELEVANT

Evaporation Rate & Reference:NOT RELEVANT

Solubility in Water:NOT KNOWN

Appearance and Odor:SOLID ABRASIVE DISCS 3/8", 1/2" IN DIAMETER, YELLOW
TO RED-BROWN COLOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NONE

Stability Condition to Avoid:EXCESSIVE HEAT

Hazardous Decomposition Products:NOT KNOWN

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH

LOCAL, STATE AND

FEDERAL REGULATIONS. RECOMMENDED METHOD IS BY SANITARY LANDFILL.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department

of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

ass

ume responsibility for the suitability of this information to their particular situation.