View NSN Online: https://aerobasegroup.co.il/nsn/8520-01-303-6439

SPECIALTY MINERALS, INC -- PRECIPITATED CALCIUM CARBONATE -- 8520-01-303-6439

Product ID: PRECIPITATED CALCIUM CARBONATE MSDS Date:10/23/1992 FSC:8520 NIIN:01-303-6439 **MSDS Number: BQYNT** === Responsible Party === Company Name: SPECIALTY MINERALS, INC Address:235 E 42ND STREET **City:NEW YORK** State:NY ZIP:10017 Country:US Info Phone Num:413-743-0598/ 413-743-0591 Е mergency Phone Num:413-743-0591/800-424-9300 CHEMTREC Preparer's Name:M.G. LARSON CAGE:SPCMN === Contractor Identification === Company Name: PFIZER INC ROERIG DIV Address:235 E 42 ST Box:City:NEW YORK State:NY ZIP:10017-5703 Country:US CAGE:1L435 Company Name: SPECIALTY MINERALS INC Address:235 EAST 42ND ST Box:556 City:NEW YORK State:NY ZIP:10017 Country:US Phone:212-573-2156;619-248-7334 CAGE:SPCMN

Ingred Name:CALCIUM CARBONA

TE CAS:471-34-1 RTECS #:FF9335000 Fraction by Wt: 100% Other REC Limits:\* TOTAL DUST OSHA PEL:5MG/M3/RESP 15MG/M3\* ACGIH TLV:10 MG/M3 \*

LD50 LC50 Mixture:RAT, ORAL LD50: 6450 MG/KG Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Health Hazards Acute and Chronic: ACUTE: DUST INHALATION MAY CAUUASE SNEEZING, COUGHING, AND NOSE IRRITATION. DUST MAY CAUSE IRRITATION TO UPPER RESPIRATORY TRACT. SKIN CONTACT MAY BE **IRRITATING. EYE** CONTACT PRODUCES MECHANICAL IRRITA TION AND PAIN, WATERING EYES, AND EYELID INFLAMMATION. ABRASION MAY CAUSE EYE AND SKIN IRRITATION. Effects of Overexposure: CHRONIC; NO KNOWN CHRONIC HEALTH EFFECTS. First Aid: EYE CONTACT: FLUSH EYES WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. IF IRRITATION PERSISTS, SEEK MEDICAL ATTENTION. SKIN CONTACT: WASH FROM SKIN WITH MILD SOAP AND WATER. INHALATION 2 REMOVE FROM THE EXPOSURE AREA. INGESTION: IF CONSCIOUS, GIVE LARGE QUANTITIES OF WATER TO INDUCE VOMITING. GET MEDICAL ATTENTION Flash Point:NON-COMBUSTIBLE Autoignition Temp: Autoignition Temp Text: NONE Extinguishing Media:NON-COMBUSTIBLE. AS APPROPRIATE FOR SURROUNDING COMBUSTIBLES Fire Fighting Procedures: FIREFIGHTERS SHOULD USE SELF-CONTAINED BREATHING EQUIPMENT TO PROTECT AGAINST THE PRODUCTS OF COMBUST ION. AVOID EXCESSIVE DUST GENERATION. Unusual Fire/Explosion Hazard:CALCIUM CARBONATE IS GENERALLY NON-FLAMMABLE, BUT IGNITES ON CONTACT WITH FLUORINE. Spill Release Procedures: USE RESPIRATORY PROTECTION FOR AIRBORNE DUST. VACUUM OR SCOOP UP SPILLED MATERIAL FOR RECOVERY OR DISPOSAL, AVOID DUSTING CONDITIONS AND USING GOOD VENTILATION. WETTING THE SPILL WITH A WATER SPRAY MA Y HELP TO KEEP THE AIRBORNE DUST

## LEVELSDOWN.

Handling and Storage Precautions:AVOID PHYSICAL DAMAGE TO CONTAINERS. STORE IN A COOL, DRY, WELL-VENTILATED AREA AWAY FROM ACIDS.
Other Precautions:THIS IS PREFERABLY ACHIEVED THROUGH THE PROVISION OF AEQUATE VENTILATION WHERE NECESSARY. WHERE DUST CANNOT BE CONTROLLED IN THIS WAY, PERSONAL RESPIRATORY PROTECTION SHOULD BE EMPLOYED.

======= Exposure Controls/Personal Protection =========

==

Respiratory Protection: IF EXPOSURE LIMITS ARE EXCEEDED, AN APPROPRIATE NIOSH APPROVED DUST RESPIRATOR SHOULD BE USED.

Ventilation:PROVIDE EXHAUST VENT TO MEET TLV REQUIREMENTS. EXHAUST FILTER SYSTEM MAY BE REQUIRED TO AVOID ENVIRONMENTAL CONTAMINATN. Protective Gloves:LEATHER OR RUBBER GLOVES

Eye Protection: SAFETY GLASSES OR DUST-TIGHT GOGGLES

Other Protective Equipment: EYEWASH STATION SHOULD BE AVAILABLE TO AREA OF USE. NEVER EAT, OR SMOKE IN WORK AREAS.

Work Hygienic Practices:

PRACTICE GOOD PERSONAL HYGIENE AFTER USING,

ESPECIALLY BEFORE EATING, DRINKING, SMOKING, USING TOILET, APPLYING COSMETICS.

Supplemental Safety and Health

CALIFORNIA PROPOSITION 65: THERE ARE EXTREMELY SMALL, BUT DETECTABLE AMOUNTS OF SUBSTANCES REGULATED UNDER CALIFORNIA'S SAFE DRINKING WATER & TOXIC ENFORCEMENT ACT. ARSENIC: < 1 PPM; BERYLLIUM: < 1 PP M; CADMIUM: < 1 PPM; CHROMIUM (VI): < 0.1 PPM; LEAD: 1 PPM; MERCURY: < 1 PPM; NICKEL: < 2 PPM; CRYSTALLINE SILICA: