

DEXTER CORPORATION -- EPK 11C PART B HARDENER -- 8040-01-004-1031

===== Product Identification =====

Product ID:EPK 11C PART B HARDENER

MSDS Date:02/16/1989

FSC:8040

NIIN:01-004-1031

Kit Part:Y

MSDS Number: BRFQZ

=== Responsible Party ===

Company Name:DEXTER CORPORATION

Address:ONE DEXTER DRIVE

City:SEABROOK

State:NH

ZIP:03874

Country:US

Info Phone Num:603-474-5541

Emergency Phone Num:603-926-091

0

Preparer's Name:DR SHELDON CLARK

CAGE:79436

=== Contractor Identification ===

Company Name:DEXTER CORP DEXTER ELECTRONIC MATERIALS

Address:15051 E DON JULIAN RD

Box:City:INDUSTRY

State:CA

ZIP:91746-1282

Country:US

Phone:626-968-6511

CAGE:79436

Company Name:DEXTER CORP THE HYSOL DIV

Address:1 DEXTER DR

Box:City:SEABROOK

State:NH

ZIP:03874

Country:US

Phone:603-474-5541/FAX: 603-474-5545

CAGE:1JB33

===== Composition/Information on Ingredients =====

Ingred Name:TALC(FILLER PART

ICLES ARE THOROUGHLY WETTED BY
VEHICLE)AIRBORNE EXPOSURE IF CURED MATERIAL IS MACHINED, GROUND OR
SANDED

CAS:14807-96-6

RTECS #:WW2710000

Other REC Limits:NONE SPECIFIED

OSHA PEL:0.2 FIBERS/CC

ACGIH TLV:2 FIBERS/CC

Ingred Name:SILICA, AMORPHOUS

CAS:112945-52-5

RTECS #:VV7310000

Other REC Limits:NONE SPECIFIED

OSHA PEL:20 MPPCF

Ingred Name:DIETHYLENETRIAMINE

CAS:111-40-0

RTECS #:IE1225000

Other REC Limits:NONE SPECIFIED

ACGIH TLV:1 PPM

=====
===== Hazards Identification =====
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:MATERIAL IS CORROSIVE TO SKIN. MAY
CAUSE CHEMICAL BURNS TO SKIN AND EYES. REPEAT CONTACT MAY CAUSE
SENSITIZATION.
Effects of Overexposure:SKIN RASH, IRRITATION

=====
===== First Aid Measures =====
=====

First Aid:FLUSH SKIN AND EYE CONTACT WITH PLENTY OF WATER. WASH SKIN
THOROUGHLY WITH SOAP AND
WATER, RUBBING ALCOHOL, OR HAND CLEANER.
DO NOT USE SOLVENTS. REMOVE SOILED CLOTHING AND WASH BEFORE REUSE.
IF IRRITATION PERSISTS, SEE PHYSICIAN.

=====
===== Fire Fighting Measures =====
=====

Flash Point Method:COC
Flash Point:215F,102C
Extinguishing Media:DRY CHEMICAL OR HALON FIRE EXTINGUISHER, OR WATER
SPRAY, FOAM OR FOG
Fire Fighting Procedures:USE SELF-CONTAINED BREATHING APPARATUS WHEN
FIGHTING FIRES IN CONFINED AREAS.
Unusual Fire/Explosion Hazard

d:DENSE SMOKE AND TOXIC GASSES MAY BE
LIBERATED.

===== Accidental Release Measures =====

Spill Release Procedures:SCRAPE UP AND TRANSFER TO METAL CONTAINER.
WIPE UP REMAINING RESIDUE WITH SOLVENTS, OBSERVING SOLVENT
FLAMMABILITY CAUTIONS, OR USE DETERGENT.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP COOL IN ACCORDANCE WITH LABEL
INSTRUCTIONS. FOLLOW RECOMMENDED CURING SCHEDULE

=====

==== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT REQUIRED WITH GOOD INDUSTRIAL VENTILATION;
ORGANIC RESPIRATOR

Ventilation:LOCAL EXHAUST RECOMMENDED, MECHANICAL ACCEPTABLE.

Protective Gloves:IMPERVIOUS PLASTIC OR RUBBER

Eye Protection:SAFETY GLASSES OR GOGGLES

Other Protective Equipment:AS NEEDED TO PROTECT SKIN AND CLOTHING

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:404F,207

C

Vapor Pres:1 LB TOTAL. DONT HEAT MATERIAL UNLESS CURING SURFACES TO
BE BONDED.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF AS HAZARDOUS WASTE ACCORDING TO DOT
HAZARD CLASS. IF NOT REGULATED BY DOT DISPOSE OF AS ORM-E. DISPOSAL
METHOD CAN BE LAND BURIAL OR CHEMICAL INCINERATION.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department

of

Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.