View NSN Online: https://aerobasegroup.com/nsn/6850-00-965-2359 FINE ORGANICS CORP -- OMEGA OS -- 6850-00-965-2359 ============= Product Identification ======================== Product ID: OMEGA OS MSDS Date:11/01/1991 FSC:6850 NIIN:00-965-2359 MSDS Number: BRGYL === Responsible Party === Company Name: FINE ORGANICS CORP Address:6935 W 62ND ST City:CHICAGO State:IL ZIP:60638 Country:US Info Phone Num:312-586-8000 Preparer's Name: PAUL ZATANTIS CAGE:0W138 === Contractor Identification === Company Name: FINE ORGANICS CORP Address:6935 W 62ND ST Box:City:CHICAGO State:IL ZIP:60638 Country:US Phone:312-586-8000 CAGE:0W138 ======= Composition/Information on Ingredients ======== Ingred Name: KEROSENE CAS:8008-20-6

RTECS #:OA5500000 Fraction by Wt: 45%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:100 PPM

ACGIH TLV:100 PPM 9091

LD50 LC50 Mixture: NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:Y

ES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:IRRITATION TO EYES AND SKIN. Effects of Overexposure:ACUTE: HIGH CONCENTRATIONS IRRITATING TO EYES AND RESPIRATORY TRACT. HEADACHES, DIZZINESS, NAUSEA. CHRONIC: MAU CAUSE LOSS OF CONCIOUSNESS, BURNING TO EYES, SKIN IRRITATION. INGESTION MAY BE FATAL. Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.
======================================
First Aid:WASH AREAS OF CONTACT WITH GENEROUS AMOUNTS OF WARM WATER AND MILD SOAP. FOR EYES, FLUSH THOROUGHLY WITH WATER AND SEEK MEDICAL ATTENTION IMMEDIATELY. IF INHALED, REMOVE FROM EXPOSURE AND SEEK MEDICAL ATTENTION IF NECESSARY. IF SWALLOWED, DO NOT INDUCE VOMITING. CALL A PHYSICIAN IMMEDIATELY.
======================================
Flash Point Method:TCC Flash Point:125F,52C Extinguishing Media:CARBON DIOXIDE, FOAM, OR DRY C HEMICAL. Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS. Unusual Fire/Explosion Hazard:NONE SPECIFIED BY MANUFACTURER.
======== Accidental Release Measures ==========
Spill Release Procedures:IF OUTDOORS, ADD SAND, EARTH, OR OTHER SUITABLE ABSORBENT TO SPILL AREA. KEEP PRODUCT OUT OF SEWERS AND WATER COURSES BY DIKING OR IMPOUNDING. INSIDE SPILLAGE, ELIMINATE ALL IGNITION SOURCES AND REMOV E WITH ABSORBENT MATERIAL. Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.
=========== Handling and Storage ============
Handling and Storage Precautions:REASONABLE CARE AND PRECAUTIONS WHEN HANDLING THIS MATERIAL ARE STRONGLY RECOMMENDED. Other Precautions:REMOVE AND LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:CARTRIDGE TYPE FOR SOLVENTS Ventilation:MECHANICAL, GENERA

HCC:F4
Boiling Pt:B.P. Text:212F,100C
Vapor Density:>1
Spec Gravity:0
.9

Evaporation Rate & Dry Reference: