

FLAMEMASTER CORP THE CHEM SEAL DIV -- CS 3204, PART A -- 8030-00-753-5005

=====
Product Identification
=====

Product ID:CS 3204, PART A

MSDS Date:06/15/1990

FSC:8030

NIIN:00-753-5005

MSDS Number: BRKHC

=== Responsible Party ===

Company Name:FLAMEMASTER CORP THE CHEM SEAL DIV

Address:11120 SHERMAN WAY

City:SUN VALLEY

State:CA

ZIP:91352-4949

Country:US

Info Phone Num:818-982-1650 FAX 818-765-5603

Emergency Phone Num:818-982-1650

Preparer's Name:HERBERT MOORE

CAGE:14439

=== Contractor Identification ===

Company Name:FLAMEMASTER CORP THE CHEM SEAL DIV

Address:11120 SHERMAN WAY

Box:City:SUN VALLEY

State:CA

ZIP:91352-4949

Country:US

Phone:818-982-1650

CAGE:14439

=====
Composition/Information on Ingredients
=====

Ingred Name:LIQUID POLYSULFIDE POLYMER (NONE PER 29 CFR 1910.1200)

CAS:68611-50-7

Other REC Limits:NONE SPECIFIED

Ingred Name:VOC: 9 GRAMS/LITER

RTECS #:9999999

VO
Other REC Limits:NONE SPECIFIED

=====
Hazards Identification
=====

Routes of Entry: Inhalation:NO Skin:NO Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:NOT ESTABLISHED. POSSIBLE SKIN
IRRITATION AFTER PROLONGED CONTACT WITH RESULTING DERMATITIS. NOT
CONSIDERED TO BE A PRIMARY SKIN IRRITANT.
Effects of Overexposure:SKIN OR EYE IRRITATION. TARGET ORGANS: CENTRAL
NERVOUS SYSTEM, LIVER, KIDNEY.

M
Medical Cond Aggravated by Exposure:NONE KNOWN

=====
First Aid Measures
=====

First Aid:EYES: FLUSH WITH LARGE AMOUNTS OF WATER, CONSULT PHYSICIAN.
SKIN: WASH WITH SOAP AND WATER. INGESTION: INDUCE VOMITING, CONSULT
PHYSICIAN.

=====
Fire Fighting Measures
=====

Flash Point Method:TCC
Flash Point:>200F,>93C
Extinguishing Media:DRY CHEMICAL, FOAM, WATER, CO2
Fire Fighting Procedures:NONE
Unusual Fire/Explosion Hazard:
d:NONE

=====
Accidental Release Measures
=====

Spill Release Procedures:SCOOP UP AND TRANSFER TO CONTAINER FOR
REACTION WITH CURING AGENT. CLEAN UP RESIDUE WITH 1,1,1
TRICHLOROETHANE THEN WITH SOAP AND WATER.

=====
Handling and Storage
=====

Handling and Storage Precautions:STORE IN COOL DRY AREA AWAY FROM
STRONG ACIDS. HARMFUL IF SWALLOWED. CAUSES EYE & SKIN IRRITATION.
USE SUITABLE EYE PROTECTION. AVOID BREATHIN

G VAPOR.

Other Precautions:WASH HANDS BEFORE EATING, SMOKING OR DRINKING AFTER HANDLING THIS PRODUCT. WASH CLOTHING BEFORE REUSE. DO NOT REUSE CONTAINER. AVOID CONTACT WITH EYES, SKIN AND CLOTHING.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT REQUIRED
Ventilation:LOCAL EXHAUST: AIR. MECHANICAL (GENERAL): FAN.
Protective Gloves:RUBBER
Eye Protection:SAFETY GLASSES
Other Protective Equipment:APPROPRIATE TO AVOID PROLONGED CONTACT.
Work Hygienic Practices:TRAIN EMPLOYEES IN SAFE HANDLING OF THIS PRODUCT.
Supplemental Safety and Health
KEY1:N1.

=====
===== Physical/Chemical Properties =====

HCC:B3
Melt/Freeze Pt:M.P/F.P Text:LIQ@RM TEMP
Vapor Pres:NIL
Vapor Density:NIL
Spec Gravity:1.52 (WATER=1)
pH:8.5
Viscosity:12,000 POISES
Evaporation Rate & Reference:NIL
Solubility in Water:NEGLIGIBLE
Appearance and Odor:WHITE PASTE, POLYSULFIDE ODOR
Percent Volatiles by Volume:3.0

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
AVOID STRONG OXIDIZING AGENTS AND STRONG ACIDS
Stability Condition to Avoid:OPEN FLAME
Hazardous Decomposition Products:H2S, CO, CO2, SO2, SMOKE

=====
===== Disposal Considerations =====

Waste Disposal Methods:REACT WITH CURING AGENT AND DISPOSE AS SOLID WASTE PER FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This in

formation is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.