Product ID:RTV ADHESIVE SEALANT-CLEAR, 3145, FOR RK0 MSDS Date:03/04/1991 FSC:1560 NIIN:01-061-8530 Kit Part:Y MSDS Number: BRQGB === Responsible Party === Company Name: DOW CORNING CORP Address:3901 SOUTH SAGINAW ROAD Box:997 City:MIDLAND State:MI ZIP:48686 Country:US Info Phone Num: 517-496-6000/6315/8577 (DISP/TRANS) Emergency Phone Num:517-496-5900/800-424-9300(CHEMTREC) Preparer's Name: JACK L. SHENEBERGER CAGE:5D028 === Contractor Identification === Company Name: ARROWHEAD INDUSTRIES (817-244-3032) CAGE:6Z898 Company Name: DOW CORNING CORP Address:3901 S SAGINAW RD Box:997 City:MIDLAND State:MI ZIP:48686-0997 Country:US Phone:517-496-6000/517-496-6315 CAGE:5D028 Company Name: DOW CORNING CORP Address:2200 W SALZBURG RD Box:City:AUBURN State:MI ZIP:48611 Country:US Phone:517

-496-4388 CAGE:71984 Company Name:NORTHRUP GRUMMAN CORP MILITARY AIRCRAFT DIVISION Address:1 HORNET WAY Box:City:EL SEGUNDO State:CA ZIP:90245-2804 Country:US Phone:310-331-6653 CAGE:76823 Company Name:SONFARREL INC Box:UNKNOW CAGE:09036 Company Name: WINDING SPECIALISTS CO INC Address:1225 WELLINGTON PL Box:City:WICHITA State:KS ZIP:67203-3898 Country:US Phone:316-265-9358 CAGE:30150

Ingred Name:TRIMETHYLATED SILICA CAS:68909 -20-6 Fraction by Wt: 22% Other REC Limits:NONE RECOMMENDED

Ingred Name:METHYLTRIMETHOXYSILANE CAS:1185-55-3 Fraction by Wt: 7% Other REC Limits:200 PPM TWA

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:ACUTE: INHALATION MAY CAUSE CENTRAL NERVOUS SYSTEM DEPRESSION AND RESPIRATORY IRRITATION, DAMAGE NERVES. CONTACT MAY CAUS DOCTOR. EYES: FLUSH WITH LOTS OF WATER FOR 15 MINUTES, HOLD LIDS OPEN. SEE DOCTOR. SKIN: WIPE OFF AND FLUSH WITH WATER. INGESTED: GET IMMEDIATE M EDICAL ATTENTION. IF CONSCIOUS, INDUCE VOMITING. LIE DOWN, KEEP WARM AND COVER EYES.

Flash Point Method:CC Flash Point:>212F,>100C Extinguishing Media:WATER FOG, CARBON DIOXIDE, DRY CHEMICAL, OR FOAM Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE GEAR. Unusual Fire/Explosion Hazard:NONE KNOWN

Spill Release Procedures:REMOVE PRODUCT; ASBSORB ANY RESIDUE WITH INERT MATERIL. PLACE IN ACONTAINER FOR LATER DISPOSAL. Neutralizing Age nt:NONE SPECIFIED BY MANUFACTURER.

Handling and Storage Precautions:STORE IN A COOL, DRY PLACE BELOW 90F.
KEEP AWAY FROM STRONG OXIDIZING AGENTS, ACIDS, AND WATER.
Other Precautions:PRODUCT EVLOVES METHYL ALCOHOL ON CONTACT WITH WATER, PROVIDE ADEQUATE VENTILATION DURING USE TO CONTROL METHANOL EXPOSURE. CURED ITEMS MADE FROM THIS PRODUCT MAY FORM TRACE OF FORMALDEHYDE (CARCINOGE N) IF HEATED.

====== E

xposure Controls/Personal Protection =========

Respiratory Protection:NONE NORMALLY REQUIRED. IF ENGINEEERING CONTROLS FAIL OR NON-ROUTINE USE OR EMERGENCY OCCURS; USE NIOSH/MSHA APPROVED SUPPLIED AIR RESPIRATOR OR SCBA, AS REQUIRED. USE IAW 29 CFR 1910.134.

Ventilation: USE ADEQUATE MECHANICAL VENTILATION OR LOCAL EXHAUST TO MAINTAIN EXPOSURE BELOW PEL/TLV.

Protective Gloves:NONE NORMALLY REQUIRED.

Eye Protection:SAFETY GLASSES

Other Protective Equipment:NONE SPECIFIED BY M

ANUFACTURER.

Work Hygienic Practices: WASH HANDS AFTER USE AND BEFORE EATING, DRINKING, OR SMOKING. LAUNDER CONTAMINATED CLOTHES BEFORE REUSE. Supplemental Safety and Health

KEY1=V5. KIT FOR REPAIR OF F5E CANOPY. THIS MSDS FOR PART B OF DOW COMPONENT. MSDS FOR OTHER COMPONENTS ARE UNDER THIS NSN AND FOLLOWING CAGES: 5W425 AND 9A232. KIT COMPILED BY ARROWHEAD AND DISTRIBUT ED BY NOTRTHRUP.

HCC:F2

NRC/State Lic N um:NOT RELEVANT Spec Gravity:1.12 (WATER=1) Solubility in Water:NEGLIGIBLE Appearance and Odor:CLEAR TO HAZY VISCOUS LIQUID; SWEET ODOR Percent Volatiles by Volume: