

HERNON MANUFACTURER INCORPORATED -- PRIMER 10 -- 8030-00-082-2508

=====  
Product Identification  
=====

Product ID:PRIMER 10

MSDS Date:02/01/1992

FSC:8030

NIIN:00-082-2508

MSDS Number: BRQMF

=== Responsible Party ===

Company Name:HERNON MANUFACTURER INCORPORATED

Address:121 TECH DRIVE

City:SANFORD

State:FL

ZIP:32771

Country:US

Info Phone Num:407-322-4000

Emergency Phone Num:407-322-4000

CAGE:DO346

=

== Contractor Identification ==

Company Name:HERNON MANUFACTURING

Address:121 TECH DRIVE

Box:City:SANFORD

State:FL

ZIP:32771

Country:US

Phone:407-322-4000/800-255-3924

CAGE:61603

Company Name:HERNON MANUFACTURING INC.

Address:865 ESSEX STREET

City:BROOKLYN

State:NY

ZIP:11208-5220

Phone:718-649-3000

CAGE:DO346

=====  
Composition/Information on Ingredients  
=====

Ingred Name:ISOPROPYL ALCOHOL

CAS:67-63-0

RTECS #:NT8050000

Fraction by Wt: 4-9%

Other REC Limits:NONE SPECIFIED

ACGI

H TLV:400 PPM

Ingred Name:METHYL CHLOROFORM (1,1,1-TRICHLOROETHANE) (SARA III)

CAS:71-55-6

RTECS #:KJ2975000

Fraction by Wt: 87-93%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:350 PPM

ACGIH TLV:350 PPM/450STEL;9394

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ozone Depleting Chemical:1

Ingred Name:N,N-DIALKYL TOLUIDINE

CAS:99-97-8

Fraction by Wt: 1-2%

Other REC Limits:NONE SPECIFIED

Ingred Name:M. B. T.

CAS:149-30-4

RTECS #:DL6475000

Fraction by Wt: 1-2%

Other REC Limits:NONE SPECIFIED

=====

===== Hazards Identification =====

Health Hazards Acute and Chronic:MILD TRANSIENT EYE IRRITATION IS POSSIBLE. SKIN MAY BE STAINED BY CONTACT.

===== First Aid Measures =====

First Aid:SKIN: FLUSH WITH WATER. EYE: FLUSH WITH WATER; SEEK MEDICAL ATTENTION. INHALATION: REMOVE TO FRESH AIR. IF SYMPTOMS PERSIST, SEEK MEDICAL ATTENTION. INGESTION: DO NOT INDUCE VOMITING. SEEK MEDICAL ATTENTION. TLV 350 PPM.

=====

===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:NONE

Extinguishing Media:FOAM, DRY CHEMICAL, CO2

Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS (SCBA) & PROTECTIVE CLOTHING SHOULD BE WORN IN FIGHTING FIRES INVOLVING CHEMICALS.

===== Accidental Release Measures =====

Spill Release Procedures:ALLOW SOLVENT TO EVAPORATE WITH GOOD VENTILATION. SOAK UP RESIDUE WITH INERT MATERIAL. STORE IN CLOSED

CONTAINER UNITL DISPOSAL.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:AVOID PROLONGED SKIN CONTACT AND PROLONGED BREATHING OF THE VAPOR. STORE BELOW 100F.

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:NOT NECESSARY

Ventilation:LOCAL EXHAUST - MAINTAIN VAPOR CONCENTRATIONS BELOW 350 PPM.

Protective Gloves:PLASTIC OR RUBBER RECOMMENDED

Eye Protection:SAFETY GLASSES RECOMMENDED

Work Hyg

enic Practices:WASH ANY AREA THAT HAS COME IN CONTACT WITH MATERIAL.

Supplemental Safety and Health

=====  
Physical/Chemical Properties  
=====

HCC:T4

Boiling Pt:B.P. Text:170 TO 180F

Vapor Pres:100 @ 68F

Vapor Density:4.5 AIR=1

Spec Gravity:1.32 (WATER=1)

Evaporation Rate & Reference:> 1 (BUTYL ACETATE = 1)

Solubility in Water:NOT SOLUBLE

Appearance and Odor:YELLOW LIQUID, CHLOROFORM LIKE ODOR

=====  
Stability and Reactivity Data  
=====

==

Stability Indicator/Materials to Avoid:YES

WILL ATTACK PAINT, ENAMEL, ETC.

Hazardous Decomposition Products:NONE

=====  
Disposal Considerations  
=====

Waste Disposal Methods:INCINERATE OR BURY. FOLLOW LOCAL, STATE & FEDERAL REGULATIONS.

=====

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defe

nse. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.