View NSN Online: https://aerobasegroup.co.il/nsn/2530-01-068-6451

## BENDIX CORP THE FRICTION MATERIALS DIV -- BENDIX FRICTION MATERIAL -- 2530-01-068-6451

Product ID:BENDIX FRICTION MATERIAL

MSDS Date:03/01/1988

FSC:2530

NIIN:01-068-6451

MSDS Number: BRTCD === Responsible Party ===

Company Name: BENDIX CORP THE FRICTION MATERIALS DIV

Address: GREEN ISLAND

Box:238 City:TROY State:NY ZIP:12181 Country:US

Info Phone Num:518-270-020

Λ

Emergency Phone Num:518-270-0200

Preparer's Name: E.L. ROGERS

CAGE:76126

=== Contractor Identification ===

Company Name: BENDIX CORP THE FRICTION MATERIALS DIV-ALLIED CORP

Address: GREEN ISLAND

Box:238 City:TROY State:NY ZIP:12181 Country:US

Phone:518-273-6550/518-270-0200

CAGE:76126

Company Name: KALMAR AC HANDLING SYSTEMS INC

Address:777 MANOR PARK DR

Box:City:COLUMBUS

State:OH ZIP:43228 Country:US CAGE:0AHU0

====== Composition/Information on Ingredients ========

Ingred Name: ASBE

STOS, CHRYSOTILE CAS:12001-29-5 RTECS #:CI6478500

Other REC Limits: NONE RECOMMENDED

OSHA PEL:0.2 FIBERS/CC

ACGIH TLV:2 FIBERS/CC; A1;9293

Ingred Name: SILICA, ALPHA QUARTZ

CAS:14808-60-7 RTECS #:VV7330000

Other REC Limits: NONE RECOMMENDED

OSHA PEL:SEE TABLE Z3

ACGIH TLV:0.1 MG/M3 RDUST;9293

Ingred Name:SILICATE(S)

CAS:14407-96-6

Other REC Limits: NONE RECOMMENDED

OSHA PEL:10 MG/M3 ACGIH TLV:10 MG/M3

Ingred Name: CARBON BLACK

CAS:1333-86-4

RTECS #:FF5800000

Other REC Limits: NONE RECOMMENDED

**OSHA** 

PEL:3.5 MG/M3

ACGIH TLV:3.5 MG/M3; 9293

Ingred Name:COKE-PETROLEUM DERIVED Other REC Limits:NONE RECOMMENDED

Ingred Name: PHENOLIC AND CASHEW RESINS, CURED

Other REC Limits: NONE RECOMMENDED

OSHA PEL:10 MG/M3 ACGIH TLV:10 MG/M3

Ingred Name: GRAPHITE

CAS:7782-42-5

RTECS #:MD9659600

Other REC Limits: NONE RECOMMENDED

OSHA PEL:15 MPPCF RDUST ACGIH TLV:2 MG/M3 RDUST; 9293

Ingred Name:IRON CAS:7439-86-6

RTECS #:NO6925000

Other REC Limits: NONE RECOMMENDED

Ingred Name: IRON OXIDE

CAS:1309-37-1 RTECS #:N O7400000

Other REC Limits: NONE RECOMMENDED

OSHA PEL:10 MG/M3 (FE)

ACGIH TLV:5 MG/M3(FE),B2; 9293

Ingred Name:ZINC (SARA III)

CAS:7440-66-6

RTECS #:ZG8600000

Other REC Limits: NONE RECOMMENDED

OSHA PEL:10 MG ZNO/M3

ACGIH TLV:10 MG ZNO/M3; 9293

EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name:ZINC OXIDE

CAS:1314-13-2

RTECS #:ZH4810000

Other REC Limits:NONE RECOMMENDED OSHA PEL:15MG/M3 TDUST/5 FUME ACGIH TLV:10MG/M3 TDUST; 9293

Ingred Name: ALUMINUM (SARA III)

CAS:7429-90-5

RTECS #:BD0330000

Other REC Limits: NONE RECOMMENDED

OSHA PEL:15MG/M3 DUST/5 FUME ACGIH TLV:10MG/M3 DUST; 9293

Ingred Name: ALUMINUM OXIDE

CAS:1302-74-5

RTECS #:GN0231000

Other REC Limits: NONE RECOMMENDED

========== Hazards Identification ===========================

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES

Health Hazards Acute and Chronic:SKIN:PARTIALLY CURED PHENOLIC OR CASHEW RESIN MAY CAUSE DERMATITIS.INHAL:SILICA DUST MAY CAUSE

SILICOSIS.ASBESTOS CAN CAUSE ASBESTOSIS,LUNG CANCER,MESOTHELIOMA. METAL DUST MAY CAUSE IRRITATION.EYES:MAY CAUSE IRRITATION.INGEST:MAY CAUSE GASTROINTESTINAL DISTURBANCES. PEOPLE WHO SMOKE ARE AT INCREASED RISK FROM ASBESTOS.

Explanation of Carcinogenicity: CONTAINS A [1332-21-4] WHICH IS LISTED BY NTP AND IARC AND REGULATED BY OSHA AS A CARCINOGEN. Effects of Overexposure: PARTIALLY CURED CASHEW RESINS-SKIN ERUPTIONS RESEMBLING POISON IVY. ASBESTOS/SILICA-COUGHING, WHE

OF BREATH,IMPAIRED PULMONARY FUNCTION. DUSTS IN EYE MAY CAUSE IRRITATION. G/I DISTURBANCE S ARE POSSIBLE FROM INGESTION.  Medical Cond Aggravated by Exposure:SMOKERS ARE AT INCREASED RISK IN WORKING WITH AIRBORNE ASBESTOS FIBERS.
======================================
First Aid:MANUFACTURER STATES THAT NONE SHOULD BE NESCESSARY WITH THE PROPER HANDLING OF THIS MATERIAL.
======================================
Extinguishing Media:WATER(TYPE A,B,C EXTINGUISHER),FOG,FOAM. Fire Fighting Procedures:"N/A" (NONE SPECIFIED BY MANUFACTURER.) Unusual Fire/Explosion Hazard:"N/A" (ONE SPECIFIED BY MANUFACTURER.)
======== Accidental Release Measures =========
Spill Release Procedures:HMIS: PICK UP PIECES. IF ASBESTOS DUST HAS BEEN PRODUCED, WEAR HEPA FILTERED RESPIRATOR AND FOLLOW REGULATION 29CFR1900.1001, ASBESTOS STANDARD. CLEAN BY WET METHODS AND/OR HEPA VACUUM.
Ne utralizing Agent:NO INFORMATION GIVEN ON MSDS BY MFR.
============== Handling and Storage =========================
Handling and Storage Precautions:DO NOT BREATH ASBESTOS DUST! Other Precautions:NONE
====== Exposure Controls/Personal Protection ========
Respiratory Protection:NOT NORMALLY NEEDED. IF AIRBORNE ASBESTOS DUSTS ARE BEING PRODUCED, WEAR NIOSH APPROVED HEPA RESPIRATOR OR SUPPLIED AIR RESPIRATOR.  Ventilation:LOCAL EXHAUST IS PREFERRED.  Protective Gloves: COTTON OR CANVAS GLOVES. Eye Protection:SAFETY GLASSES. Other Protective Equipment:USE CLOTHING TO COVER THE SKIN AGAINST CONTACT FROM DUST.  Work Hygienic Practices:USE PROPER DUST CONTROL MEASURES.USE A HEPA VACUUM;DO NOT DRY SWEEP.WET CLEAN SURFACES. SEE 29CFR1910.1001 Supplemental Safety and Health KEY2:KT
========= Physical/Chemical Properties ==========
HCC:T6 NRC/State Lic Num:NONE Spec Gravity:1.6-3.7 Evaporation Rate & Description Rate &

EZING, SHORTNESS

Ар

pearance and Odor:SOLID,ODORLESS,LIGHT TAN TO DARK GREY COLOR.

## Waste

Corrosion Rate: UNKNOWNN

Disposal Methods:PLACE IN PROPER RECEPTACLES.DISPOSE OF IN AUTHORIZED LANDFILLS IN ACCORDANCE WITH FEDERAL,STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document sh

ould seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.