

ENGELHARD CORP., CHEMICAL CATALYSTS GROUP -- DESICCITE 25 -- 6850-01-079-0889

=====
Product Identification
=====

Product ID:DESICCITE 25

MSDS Date:05/19/1995

FSC:6850

NIIN:01-079-0889

MSDS Number: BSVZW

=== Responsible Party ===

Company Name:ENGELHARD CORP., CHEMICAL CATALYSTS GROUP

Address:600 E. MCDOWELL ROAD

City:JACKSON

State:MS

ZIP:39204

Country:US

Info Phone Num:800-458-8650 OR 800-654-40

39

Emergency Phone Num:800-458-8650/800-424-9300(CHEMTREC)

CAGE:0NH81

=== Contractor Identification ===

Company Name:ENGELHARD CORP

Address:600 E. MCDOWELL ROAD

Box:City:JACKSON

State:MS

ZIP:39204

Country:US

Phone:800-458-6850 / 601-948-3966

CAGE:0NH81

=====
Composition/Information on Ingredients
=====

Ingred Name:BENTONITE (INCLUDES INGREDIENTS 2 AND 3.)

CAS:1302-78-9

RTECS #:CT9450000

Fraction by Wt: SEE 2&3%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:5 MG/M3 (DUST)

ACGIH T

LV:5 MG/M3 (DUST)

Ingred Name:SILICA, CRYSTALLINE - QUARTZ

CAS:14808-60-7

RTECS #:VV7330000

Fraction by Wt: 1 - 3%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:SEE TABLE Z-3

ACGIH TLV:0.1 MG/M3 RDUST;9495

Ingred Name:ALUMINUM SILICATE,

CAS:12141-46-7

Fraction by Wt: 97%

Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

LD50 LC50 Mixture:LD50 (ORAL, RAT) IS NOT KNOWN.

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Reports of Carcinoge

nicity:NTP:YES IARC:YES OSHA:NO

Health Hazards Acute and Chronic:TARGET ORGANS:EYE, SKIN, RESPIRATORY

TRACT. ACUTE- EYES:MAY CAUSE IRRITATION & DISCOMFORT. SKIN:MAY

CAUSE IRRITATION, REDNESS. INHALE:CAUSES RESPIRATORY TRACT

IRRITATION & MAY CAUSE DISABLING, PROGRES SIVE PULMONARY FIBROSIS

(SILICOSIS). ORAL:NO ADVERSE EFFECTS EXPECTED. CHRONIC- INHALATION

MAY CAUSE LUNG DAMAGE.

Explanation of Carcinogenicity:CONTAINS CRYSTALLINE SILICA (QUARTZ).

Effects of Overexposure:IR

RITATION, COUGH, DYSPNEA, WHEEZING, CHEST

DISCOMFORT

Medical Cond Aggravated by Exposure:BREATHING OF DUST MAY AGGRAVATE

EXISTING MEDICAL CONDITIONS SUCH AS RESPIRATORY AILMENTS.

===== First Aid Measures =====

First Aid:GET MEDICAL CARE IF SYMPTOMS PERSIST. EYES:IMMEDIATELY FLUSH

WITH WATER FOR 15 MINUTES, HOLDING EYELIDS OPEN. SKIN:FLUSH WITH

PLENTY OF WATER. INHALED:REMOVE TO FRESH AIR. PROVIDE CPR/OXYGEN IF

NEEDED . SWALLOWED:IF LARG

E QUANTITIES INGESTED, CONTACT PHYSICIAN.

NOTE TO PHYSICIAN:DESICCANT GENERATES HEAT AS IT ADSORBS WATER. USED PRODUCT CAN CONTAIN HAZARDOUS CHEMICALS.

===== Fire Fighting Measures =====

Flash Point:NONE

Extinguishing Media:UNUSED MATERIAL WILL NOT BURN. USE WATER, CARBON DIOXIDE OR FOAM FOR SURROUNDING FIRE.

Fire Fighting Procedures:WEAR PROTECTIVE CLOTHING AND NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS. USED MATERIAL MAY PRODUCE HAZ

ARDOUS DECOMPOSITION PRODUCTS.

Unusual Fire/Explosion Hazard:NONE

===== Accidental Release Measures =====

Spill Release Procedures:WEAR PROTECTIVE EQUIPMENT. CAREFULLY SWEEP OR VACUUM THE SPILL AREA. COLLECT AND PLACE THE SPILLED MATERIAL IN A WASTE DISPOSAL CONTAINER. AVOID DUSTING.

Neutralizing Agent:NOT RELEVANT

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN DRY PLACE, IN TIGHTLY CLOSED

CONTAINER, AWAY FROM INCOMPATIBLE MATERIALS. KEEP OUT OF REACH OF CHILDREN.

Other Precautions:WEAR GOGGLES IF DUST CAUSES EYE DISCOMFORT. WEAR A PROPERLY FITTED NIOSH-APPROVED DUST RESPIRATOR FOR DUSTY CONDITIONS. USE WITH ADEQUATE VENTILATION. WASH THOROUGHLY AFTER HANDLING. AVOID CONTACT WITH EYES. OPEN CONTAINER SLOWLY.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF ENGINEERING CONTROLS ARE INADEQUATE TO CONTROL DUST CONCEN

TRATIONS TO AN ACCEPTABLE LEVEL, A

NIOSH-APPROVED DUST RESPIRATOR SHOULD BE WORN IF NEEDED. IF RESPIRATORS ARE USED, A PROGRAM SHOULD BE INSTITUTED TO COMPLY WITH OSHA.

Ventilation:USE GENERAL OR LOCAL EXHAUST VENTILATION TO MEET TLV REQUIREMENTS.

Protective Gloves:COTTON/RUBBER/LATEX FOR REPEATED CONTACT

Eye Protection:SAFETY GOGGLES FOR DUSTY CONDITIONS

Other Protective Equipment:LONG SLEEVE WORK CLOTHING, EYE WASH FOUNTAIN

Work Hygienic Practices:WASH THOROUGHLY BEFORE EATING

, DRINKING OR
SMOKING. VACUUM UP ANY DUST. LAUNDER CLOTHING BEFORE REUSE.

Supplemental Safety and Health

THE MANUFACTURER STATES THAT INDUSTRIAL HYGIENE SAMPLING HAS SHOWN THE
RESPIRABLE FRACTION OF CRYSTALLINE SILICA QUARTZ TO BE ONLY 0.1 -
0.115%.

===== Physical/Chemical Properties =====

HCC:N1

NRC/State Lic Num:NOT RELEVANT

Melt/Freeze Pt:M.P/F.P Text:NOT KNOWN

Spec Gravity:2.0

Viscosity:NOT RELEVANT

Evaporation Rate & Reference:NOT RELEVANT

Solub

ility in Water:NEGLIGIBLE

Appearance and Odor:GREY TO OFF-WHITE GRANULES; ODORLESS

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG ALKALI, STRONG OXIDIZING AGENTS

Stability Condition to Avoid:MOISTURE

Hazardous Decomposition Products:NONE

===== Disposal Considerations =====

Waste Disposal Methods:DISCARD ANY PRODUCT (INCLUDING ANY RETAINED
MATERIALS OF USE), DISPOSABLE CONTAINERS OR LINE

R IN AN

ENVIRONMENTALLY ACCEPTABLE MANNER, IN FULL COMPLIANCE WITH LOCAL,
STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professiona

I advice to verify and
assume responsibility for the suitability of this information to their
particular situation.