View NSN Online: https://aerobasegroup.co.il/nsn/8010-01-270-3637

Product ID:CEE-BEE STRIPPER A-458 MSDS Date:09/26/1991 FSC:8010 NIIN:01-270-3637 **MSDS Number: BSYZZ** === Responsible Party === Company Name: MCGEAN-ROHCO INC, CEE-BEE CHEMICAL DIV Address:9520 E CEE BEE DR City:DOWNEY State:CA ZIP:90241-5501 Country:US Info Phone Num:216-441-4900 Emergency Phone Num:216-441-4900 CAGE:71361 === Contractor Identification === Company Name: MCGEAN-ROHCO INC Address:9520 E CEE BEE DR Box:City:DOWNEY State:CA ZIP:90241-5501 Country:US Phone:562-803-4311/FAX: 562-803-6701 CAGE:71361

Ingred Name:METHYLENE CHLORIDE (SARA III) (SUSPECTED CARCINOGEN) CAS:75-09-2 RTECS #:PA8050000 Fraction by Wt: 70-90% Other REC Limits:TWA: 500 PPM EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingre

d Name:ETHANOL CAS:64-17-5 RTECS #:KQ6300000 Fraction by Wt: 10-15% Other REC Limits:TWA: 1900 MG/M3

Ingred Name:TRIETHYL PHOSPHITE CAS:122-52-1 RTECS #:TH1130000 Fraction by Wt: 2-5% Other REC Limits:NONE RECOMMENDED

Health Hazards Acute and Chronic:SUMMARY OF RISKS: SARA HAZARD, ACUTE & CHRONIC. TARGET ORGANS: LIVER, KIDNEY, BLOOD, SKIN, EYES, CVS, CNS. ACUTE EFFECTS: IRRITATION. CHRONIC EFFECTS: AFFECT ALL TARGET ORGANS.

Explanation of Carcinogenicity:METHYLENE CHLORIDE SUSPECTED CARCINOGEN. Effects of Overexposure:EYE CONTACT: IRRITATION, PAIN. SKIN CONTACT:

PROLONGED CONTACT COULD CAUSE IRRITATION, INFLAMMATION OR BURNS. INHALATION: DIZZINESS, DRUNKENNESS, FATIGUE, HEADACHE. INGESTION: NAUSEA, VOMITING.

Medical Cond Aggravated by Exposure:DERMATITIS, LIVER, AND KIDNEY DISEASES.

First Aid:EYE CONTACT: FLUSH WITH W ATER FOR AT LEAST 15 MINUTES. GET

MEDICAL ATTENTION. SKIN CONTACT: WASH OFF IN FLOWING WATER. THEN WASH WITH SOAP AND WATER. INHALATION: REMOVE TO FRESH AIR. CALL A PHYSICIAN. INGESTION: GIVE A LARGE QUANTITY OF WATER. DO NOT INDUCE VOMITING. CALL AND/OR TAKE TO EMERGENCY MEDICAL FACILITY.

Flash Point:NONE Extinguishing Media:IF INVOLVED IN FIRE-WATER FOG. Fire Fighting Procedures:POSITIVE PRESSURE SELF-CONTAI

NED BREATHING	
APPARATUS AND FULL PROTECTIVE GEAR SHOULD BE WORN.	
Unusual Fire/Explosion Hazard:FLAMMABLE VAPOR-AIR MIXTURES POSSIBLE	

Spill Release Procedures: MOP, WIPE UP, OR SOAK UP IMMEDIATELY WITH ABSORBENTS. WEAR PROPER PROTECTIVE EQUIPMENT. SEE CONTROL MEASURES.

Handling and Storage Precautions:STORE IN A COOL, DRY, WELL VENTILATED AREA AT 3

2 TO 90 F. OPEN CONTAINERS SLOWLY AND WITH CAUTION TO VENT IN CASE THERE WAS PRESSURE BUILD UP.

======= Exposure Controls/Personal Protection ==========

Ventilation:SUFFICIENT TO KEEP BELOW TWA LIMITS. Protective Gloves:NEOPRENE Eye Protection:CHEMICAL GOGGLES AND FACE SHIELD Other Protective Equipment:SUFFICIENT TO PREVENT SKIN CONTACT. EYE WASH STATION & SAFETY SHOWERS. Supplemental Safety and Health

HC C:T4 Boiling Pt:B.P. Text:110F,43C Vapor Density:2.9 Spec Gravity:1.2 Evaporation Rate & amp; Reference:> BUTYL ACETATE Solubility in Water:SLIGHT Appearance and Odor:HAZY, LIGHT COLORED LIQUID. ODOR: SOLVENT Percent Volatiles by Volume:90

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZERS Hazardous Decomposition Products:OPEN FLAMES CAN CAUSE THERMAL DEGRADATION GIVING OFF HYDROGEN CHLORIDE AND CHLORINE.

=======

Waste Disposal Methods:SEND TO AN APPROVED WASTE DISPOSAL FACILITY. FOLLOW ALL LOCAL, STATE, AND FEDERAL REGULATIONS. RCRA# (IF DISPOSED AS RECEIVED): F002.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.