

BOW SOLDER PRODUCTS CO. -- SOLDER, TIN ALLOY -- 3439-01-007-5491

===== Product Identification =====

Product ID:SOLDER, TIN ALLOY

MSDS Date:09/01/1986

FSC:3439

NIIN:01-007-5491

MSDS Number: BTCMS

=== Responsible Party ===

Company Name:BOW SOLDER PRODUCTS CO.

Address:900 HOBSON STREET

Box:488

City:UNION

State:NJ

ZIP:07083

Country:US

Info Phone Num:(201) 686-6040

Emergency Phone Num:(201) 686-6040

Preparer's Name:DGSC-SSH

CAGE:52329

=== Contractor Identification ===

Company Name:BOW ELECTRONIC SOLDERS

Address:1 CROSSMAN ROAD

Box:City:SAYREVILLE

State:NJ

ZIP:08872

Country:US

Phone:732-316-2100/ FAX: 732-316-2177

CAGE:52329

===== Composition/Information on Ingredients =====

Ingred Name:TIN

CAS:7440-31-5

RTECS #:XP7320000

Fraction by Wt: 63.5%

Other REC Limits:NONE SPECIFIED

OSHA PEL:2 MG/M3

ACGIH TLV:2 MG/M3; 9394

Ingred Name:LEAD (SARA III)

CAS:7439-92-1

RTECS #:OF75

25000
Fraction by Wt: 35.53%
Other REC Limits:NONE SPECIFIED
OSHA PEL:SEE 1910.1025
ACGIH TLV:0.15 MG/M3,DUST;9394
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:ANTIMONY (SARA III)
CAS:7440-36-0
RTECS #:CC4025000
Fraction by Wt: 0.5%
Other REC Limits:NONE SPECIFIED
OSHA PEL:0.5 MG/M3
ACGIH TLV:0.5 MG (SB)/M3; 9394
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:BISMUTH
CAS:7440-69-9
RTECS #:EB2600000
Fraction by Wt: 0.25%
Other REC Limits:NONE SPECIFIED

Ingred Name:COPPER (SARA III)
C
AS:7440-50-8
RTECS #:GL5325000
Fraction by Wt: 0.08%
Other REC Limits:1 MG(CU)/M3 (DUST)
OSHA PEL:0.1MG/M3 FUME/1 DUST
ACGIH TLV:0.2 MG/M3 FUME; 9394
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ARSENIC (SARA III)
CAS:7440-38-2
RTECS #:CG0525000
Fraction by Wt: 0.03%
Other REC Limits:NONE SPECIFIED
OSHA PEL:SEE 1910.1018
ACGIH TLV:0.01 MG/M3, A1; 9394
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:IRON
CAS:7439-89-6
RTECS #:NO4565500
Fraction by Wt: 0.02%
Other REC Limits:NONE SPECIFI

ED
OSHA PEL:5 MG/M3
ACGIH TLV:10 MG/M3 AS FE2O3

Ingred Name:ALUMINUM (SARA III)
CAS:7429-90-5
RTECS #:BD0330000
Fraction by Wt: 0.005%
Other REC Limits:NONE SPECIFIED
OSHA PEL:15MG/M3 DUST/5 FUME
ACGIH TLV:10MG/M3 DUST; 9394

Ingred Name:ZINC (SARA III)
CAS:7440-66-6
RTECS #:ZG8600000
Fraction by Wt: 0.005%
Other REC Limits:NONE SPECIFIED
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:ROSIN ACID
CAS:8050-09-7
Other REC Limits:NONE SPECIFIED

Ingred Name:CADMIUM (SARA III)
CAS:7440-43-9
RTECS #:EU9800000
Fraction by Wt: 0.08%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:0.2 MG/M3 DUST; Z-2
ACGIH TLV:0.01 MG/M3 DUST;9394
EPA Rpt Qty:10 LBS
DOT Rpt Qty:10 LBS

===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:SKIN: BURNS. INGESTION: LEAD POISONING
& METALLIC TASTE IN MOUTH. INHALATI

ON: ABDOMINAL PAIN, NAUSEA,
JOINT OR MUSCLE PAIN, WEAKNESS, LOSS OF WEIGHT, MENTAL CONFUSION, &
LEAD-LINE ON GUMS.

Explanation of Carcinogenicity:LEAD & ARSENIC ARE SUSPECTED HUMAN
CARCINOGENS.

Effects of Overexposure:SKIN: BURNS. INGESTION: LEAD POISONING &
METALLIC TASTE IN MOUTH. INHALATION: ABDOMINAL PAIN, NAUSEA, JOINT
OR MUSCLE PAIN, WEAKNESS, LOSS OF WEIGHT, MENTAL CONFUSION, OR
LEAD-LINE ON GUMS.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:INHALATION: REMOVE TO FRESH AIR. SKIN: DON'T ATTEMPT TO
REMOVE ROSIN FROM SECOND OR THIRD DEGREE BURNS. USE SOLVENTS TO
REMOVE ROSIN FROM MINOR FIRST DEGREE BURNS. INGESTION: OBTAIN
MEDICAL ATTENTION IN ALL CASES.

===== Fire Fighting Measures =====

Flash Point:>300F,>149C

Lower Limits:NOT GIVEN

Upper Limits:NOT GIVEN

Extinguishing Media:NONFLAMMABLE. USE MEDIA SUITABL
E FOR SURROUNDING
FIRE.

Fire Fighting Procedures:WEAR SELF-CONTAINED RESPIRATORY SYSTEM.

Unusual Fire/Explosion Hazard:MODERATE HAZARD WHEN HIGH CONCENTRATION
OF VERY FINE METALLIC DUST IS EXPOSED TO HEAT. MOLTEN METAL MAY
REACT VIOLENTLY WITH WATER.

===== Accidental Release Measures =====

Spill Release Procedures:VACUUM OR WET SWEEP USING A RESPIRATOR &
PROTECTIVE CLOTHING.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== H
andling and Storage =====

Handling and Storage Precautions:STORE IN A CLOSED CONTAINER. AVOID
INHALATION OF DUSTS OR FUMES. DON'T SMOKE OR EXPOSE FOOD TO DUST.
KEEP AREA CLEAN.

Other Precautions:NONE SPECIFIED BY MANUFACTURER.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF VENTILATION DOES NOT MAINTAIN INHALATION
EXOSURES BELOW PEL (TLV), USE NIOSH/MSHA APPROVED RESPIRATOR AS PER
CURRENT 29 CFR 1910.134, INSTRUCT

IONS/WARNINGS AND NIOSH RESPIRATOR
SELECTION.

Ventilation:LOCAL EXHAUST: FUME HOOD OVER AREA. MECHANICAL: 200 FT/MIN.
AIR VELOCITY INTO HOOD OPENING TO KEEP 1700F,>927

Melt/Freeze Pt:M.P/F.P Text:NOT GIVEN

Vapor Pres:0.000016

Vapor Density:NOT GIVEN

Spec Gravity:7.3-11.3

Evaporation Rate & Reference:NOT GIVEN

Solubility in Water:INSOLUBLE

Appearance and Odor:METALLIC COLOR, SOLID, GRAY TO SHINY SILVERY GRAY.

Percent Volatiles by Volume:NIL

===== Stability and Reactivity

Data =====

Stability Indicator/Materials to Avoid:YES

ACIDS, BASES, OXIDIZERS, & WATER

Stability Condition to Avoid:EXTREME TEMPERATURES

Hazardous Decomposition Products:TOXIC FUMES

===== Disposal Considerations =====

Waste Disposal Methods:SCRAP DRIPPINGS & DROSSES SHOULD BE STORED IN A
CLOSED CONTAINER & RETURNED TO A LEAD RECYCLER. FOLLOW FEDERAL,
STATE, & LOCAL REGULATIONS REGARDING DISPOSAL.

Disclaimer (provided with this information
by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.