

NILES CHEMICAL PAINT CO -- N-5564S GLOSS RED SILICONE ENAMEL -- 8010-01-349-9006

=====  
Product Identification  
=====

Product ID:N-5564S GLOSS RED SILICONE ENAMEL

MSDS Date:11/23/1993

FSC:8010

NIIN:01-349-9006

MSDS Number: BTCPN

=== Responsible Party ===

Company Name:NILES CHEMICAL PAINT CO

Address:225 FORT STREET

Box:307

City:NILES

State:MI

ZIP:49120

Country:US

Info Phone Num:616-683-3377

Emergenc

y Phone Num:219-236-5856

Preparer's Name:MICHAEL LICHATOWICH

CAGE:02388

=== Contractor Identification ===

Company Name:NILES CHEMICAL PAINT

Address:225 FORT STREET

Box:307

City:NILES

State:MI

ZIP:49120

Country:US

Phone:616-683-3377/219-236-5856

CAGE:02388

=====  
Composition/Information on Ingredients  
=====

Ingred Name:HIGH SOLIDS SILICONE (VAPOR PRESSURE 1.5 MM HG @ 20C)

Fraction by Wt: 39%

Other REC Limits:NONE RECOMMENDED

Ingred Name:GROUND LIMESTONE

CAS:1317-65-3

RTECS #:E

V9580000

Fraction by Wt: 24%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:10 MG/M3

ACGIH TLV:10 MG/M3

Ingred Name:MINERAL SPIRITS (VAPOR PRESSURE 0 MM HG @20C)

CAS:8052-41-3

RTECS #:WJ8925000

Fraction by Wt: 18%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM

ACGIH TLV:100 PPM

Ingred Name:VM&P NAPHTHA HI FLASH (VAPOR PRESSURE 15 MM HG @ 37.7C)

Fraction by Wt: 10%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:500 PPM

ACGIH TLV:350 PPM

Ingred Name:COBALT COMPOUNDS (AS CO) (SARA III)

CAS:7440-48-4

RTECS #:GF8750000

Fraction by Wt: AIR

Spec Gravity:1.169

Viscosity:100 KU MAX

Evaporation Rate & Reference:SLOWER THAN ETHER

Solubility in Water:SLIGHT

Appearance and Odor:LIQUID, ODOR OF SOLVENTS

Percent Volatiles by Volume:41.52

Corrosion Rate:MINIMAL

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZERS

Hazardous Decomposition Products:CAN PRODUCE CARBON MONOXIDE AND/OR  
CARBON DIOXIDE

Conditions to Avoid Poly

merization:HIGH TEMPERATURES, SHOCK FROM  
DROPPING

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH APPLICABLE LOCAL,  
STATE, AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be acc  
urate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.