View NSN Online: https://aerobasegroup.com/nsn/6810-00-201-0904

Product ID:DENATURED ALCOHOL MSDS Date:05/08/1989 FSC:6810 NIIN:00-201-0904 MSDS Number: BTKPK === Responsible Party === Company Name: STARTEX CHEMICAL INC. Box:687 City:CONROE State:TX ZIP:77305 Country:US Info Phone Num:409-539-6244 Emergency Phone Num:409-539-6244 CAGE:OYFV5 === Contractor Identifi cation === Company Name: CHEMICAL SPECIALISTS AND DEVELOPMENT INC Address:2210 HACKBERRY LN Box:687 City:CONROE State:TX ZIP:77305 Country:US Phone:409-756-1065 CAGE:4N760 **Company Name: STARTEX CHEMICAL INC** Address:5 HACKBERRY LANE Box:3087 City:CONROE State:TX ZIP:77305 Country:US Phone:800-424-9300(CHEMTREC)/936-539-6244 CAGE:OYFV5

Ingred Name:ETHYL ALCOHOL (ETHANOL) CAS:64-17-5 RTECS #:KQ6300000 Fraction by Wt: 89% Other REC Limits:NONE RECOMMENDED OSHA PEL:1000 PPM ACGIH TLV:1000 PPM; 9394

Ingred Name:ETHYL ACETATE (SARA III) CAS:141-78-6 RTECS #:AH5425000 Fraction by Wt: 5% Other REC Limits:NONE RECOMMENDED OSHA PEL:400 PPM ACGIH TLV:400 PPM; 9394 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:METHYL ALCOHOL (METHANOL) (SARA III) CAS:67-56-1 RTECS #:PC1400000 Fraction by Wt: 4% Other REC Limits:NONE RECOMMENDED OSHA PEL:S, 200 PPM ACGIH TLV:S,200PPM/250STEL; 94 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:N-HEPTANE CAS:142-82-5 RTECS #:MI7700000 Fraction by Wt: 1% Other REC Limits:NONE RECOMMENDED OSHA PEL:500 PPM ACGIH TLV:400 PPM/500STEL;9394

Ingred Name:METHYL ISOBUTYL KETONE (SARA III) CAS:108-10-1 RTECS #:SA9275000 Fraction by Wt: 1% Other REC Limits:NONE RECOMMENDED OSHA PEL:100 PPM ACGIH TLV:50 PPM/75 STEL; 9394 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Routes of Entry: Inhalation:YES Skin:YES Ingestio

n:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALED:HIGH VAPOR CONCENTRATIONS MAY CAUSE UPPER RESPIRATROYIRRITATION AND NARCOSIS (SLEEPINESS, DIZZINESS). EYE:LIQUID & VAPOR CAUSE IRRITATION. SKIN:LOW HAZARD FOR USUAL INDUSTRIAL HANDLING.

Explanation of Carcinogenicity:HMIS:THIS PRODUCT CONTAINS NO INGREDIENT AT 0.1% OR GREATER THAT IS LISTED BY IARC, NTP OR OSHA AS A CARCINOGEN.

Effects of Overexposure: INHALED: HIGH VAPOR CONCENT RATIONS MAY CAUSE

UPPER RESPIRATROYIRRITATION AND NARCOSIS (SLEEPINESS, DIZZINESS). EYE:LIQUID & VAPOR CAUSE IRRITATION. SKIN:LOW HAZARD FOR USUAL INDUSTRIAL HANDLING.

Medical Cond Aggravated by Exposure:NO INFORMATION GIVEN ON MSDS BY MFR.

First Aid:INHALED:REMOVE TO FRESH AIR. TREAT SYMPTOMATICALLY. IF BREATHING IS DIFFICULT GIVE OXYGEN. GET MEDICAL ATTENTION IF SYMPTOMS PERSIST. EYE:IMMEDIATELY FLUS

H W/PLENTY OF WATER FOR AT LEAST 15 MINUTES AN D GET MEDICAL ATTENTION IF SYMPTOMS AREPRESENT AFTER WASHING.

Flash Point Method:TCC

Flash Point:=13.3C, 56.F

Lower Limits:3.53

Upper Limits:21.2

Extinguishing Media:USE WATER SPRAY, CARBON DIOXIDE, ALCOHOL FOAM, OR DRY CHEMICAL.

Fire Fighting Procedures:WEAR SCBA AND PROTECTIVE CLOTHING TO PREVENT CONTACT W/SKIN & EYES. WATER MAY BE INEFFECTIVE. USE WATER SPRAY T O

COOL FIRE EXPOSED CONTAINERS.

Unusual Fire/Explosion Hazard:FLAMMABLE LIQUID & VAPOR. VAPORS ARE HEAVIER THAN AIR AND MAY TRAVEL ALONG GROUND OR FLOOR, THEN 'FLASH BACK' FROM A DISTANT IGNITION SOURCE.

Spill Release Procedures: ELIMINATE IGNITION SOURCES. SMALL SPILLS MAY BE COLLECTED USING ABSORBENT MATERIALS. USE WATER SPRAY TO DISPERSE VAPORS AND DILUTE TO A NON-FLAMMABLE MIXTURE. PREVENT RUNOFF FROM

ENTERING DRAINS, SEWE RS, STREAMS. Neutralizing Agent:NO INFORMATION GIVEN ON MSDS BY MFR.

Handling and Storage Precautions: FLAMMABLE LIQUID. KEEP AWAY FROM HEAT, SPARKS & FLAME. KEEP CONTAINER CLOSED. USE W/ADEQUATE VENTILATION. Other Precautions: COMPLY W/ALL FEDERAL, STATE & LOCAL CODES PERTAINING TO STORAGE, HANDLING, DISPENSING & DISPOSING OF FLAMMABLE LIQUIDS. 'EMPTY' CONTAINERS MAY CONTAIN RESIDUE OR VAPORS . TREAT THEM WITH ALL THE PRECA UTIONS DUE FULL ONES. Respiratory Protection: AN APPROPRIATE NIOSH APPROVED RESPIRATOR FOR ORGANIC VAPOR MUST BE WORN IF EXPOSURE WILL LIKELY EXCEED RECOMMENDED LIMITS. IF RESPIRATORS ARE USED A PROGRAM SHOULD BE ESTABLISHED TO ASSURE COMPLIANCE W/OSHA STANDARD 29CFR1910.134. Ventilation: GOOD GENERAL VENTILATION (TYPICALLY 10 AIR CHANGES PER HOUR) SHOULD BE USED. VENTILATION RATES SHOULD MATCH CONDITIONS. Protective Gloves: IMPERVIOUS Eye Protection: SAFETY GLASSES W/SIDE SHIELDS OR GOGGLES Other Protective Equipment: EYE WASH STATION AND SAFETY SHOWER. Work Hygienic Practices:MFR: ? HMIS:USE GOOD CHEMICAL HYGIENE PRACTICE. AVOID UNNECESSARY CONTACT. WASH THOROUGHLY BEFORE EATING OR DRINKING. Supplemental Safety and Health LOCAL EXHAUST VENTILATION OR AN ENCLOSED HANDLING SYSTEM MAY BE NEEDED TO CONTROL AIRBORNE LEVELS BELOW RECOMMENDED EXPOSURE LIMITS.

HCC:F5 NRC/State Lic Num:NOT RELEVANT Boiling Pt:=77.8C, 172.F Vapor Pres:40 MM Vapor Density:1.59 Spec Gravity:0.79 Solubility in Water:APPRECIABLE Appearance and Odor:CLEAR LIQUID, ALCOHOL ODOR Percent Volatiles by Volume:100

Stability Indicator/Materials to Avoid:YES OXIDIZING MATERIALS MEY CAUSE A VIGOROUS REACTION. Stability Condition to Avoid:NO INFORMA TION GIVEN ON MSDS BY MFR. Hazardous Decomposition Products: AS W/ANY THER ORGANIC MATERIAL, COMBUSTION WILL PRODUCE CARBON DIOXIDE AND PROBABLY CARBON MONOXIDE. Conditions to Avoid Polymerization: WILL NOT OCCUR

Waste Disposal Methods:MIX WITH COMPATIBLE CHEMICAL WHICH IS LESS FLAMMABLE AND INCINERATE. OBSERVE ALL FEDERAL, STATE AND LOCAL LAWS CONCERNING HEALTH AND ENVIRONMENT.

Disclaimer (provided with this i

nformation by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.