

METAL LBRICANTS CO, GRAFO COLLOIDS DIV -- GRAFO MIL-L-3572, GRADE C -- 9150-00-235-5587
===== Product Identification =====

Product ID:GRAFO MIL-L-3572, GRADE C

MSDS Date:01/21/1994

FSC:9150

NIIN:00-235-5587

MSDS Number: BTKQB

=== Responsible Party ===

Company Name:METAL LBRICANTS CO, GRAFO COLLOIDS DIV

Address:105 8TH ST

City:EMLENTON

State:PA

ZIP:16373

Country:US

Info Phone Num:412-867-5000

Em

ergency Phone Num:412-867-5000, 800-255-3924

Preparer's Name:ANAND KAKAR

CAGE:KO752

=== Contractor Identification ===

Company Name:METAL LBRICANTS CO, GRAFO COLLOIDS DIV

Address:105 8TH ST

Box:City:EMLENTON

State:PA

ZIP:16373

Country:US

Phone:412-867-5000

CAGE:KO752

Company Name:METAL LUBRICANTS CO GRAFO COLLOIDS DIV

Address:105 8TH

Box:City:EMLENTON

State:PA

ZIP:16373

Country:US

Phone:412-867-5000

CAGE:4M367

Company Name:SALATHE OIL CO INC

Address:2226 PETERS RD

Box:City:HARVEY

State:LA

ZIP:700

58
Country:US
Phone:504-366-4542
CAGE:0T5C6

=====
Composition/Information on Ingredients
=====

Ingred Name:GRAPHITE, NATURAL
CAS:7782-42-5
RTECS #:MD9659600
Fraction by Wt: 10.0%
Other REC Limits:NONE SPECIFIED BY M.
OSHA PEL:15 MPPCF; Z-3
ACGIH TLV:2 MG/M3 RDUST; 9394

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE- MAY CAUSE IRRITATION TO THE
EYES AND SKIN. INHALATION OF DUST MAY CAUSE PULMONARY TRACT
IRRITATION. CHRONIC-NOT GIVEN.
Effects of Overexposure:EYES:IRRITATION, REDNESS, PAIN.
SKIN:IRRITATION.
Medical Cond Aggravated by Exposure:NONE KNOWN.

=====
First Aid Measures
=====

First Aid:INHALATION:REMOVE TO FRESH AIR, PROVIDE CPR/OXYGEN IF NEEDED.
EYE CONTACT:FLUSH WITH WATER FOR 15 MINUTES. GET MEDICAL HELP. SKIN
CONTACT:WASH WITH SOAP AND WATER. GET MED ATTENTION IF SYMPTOMS
PERSIST. INGESTION:DO NOT INDUCE VOMITING, DRINK 1-2 GLASSES OF
WATER. GET MEDICAL HELP IMMEDIATELY.

=====
Fire Fighting Measures
=====

Flash Point Method:COC
Flash Point:350F,177C
Lower Limits:1%
Upper Limits:6%
Extinguishing Media:FOAM, DRY CHEMICAL, CO2, WATER SPRAY OR FOG.
Fire Fighting Procedures:USE AIR-SUPPLIED RESCUE EQUIPMENT FOR ENCLOSED
AREA. COOL HEAT EXPOSED CONTAINERS WITH WATER.
Unusual Fire

e/Explosion Hazard:DO NOT STORE OR MIX WITH STRONG OXIDANTS.

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE IGNITION SOURCES. STOP LEAK.
EVACUATE AREA.DO NOT TOUCH SPILLAGE. SM SPILL:ABSORB W. INERT
ABSORBENT. PLACE IN CLOSED CONTAINER. LG SPILL: DIKE AHEAD, RECOVER
BY VACUUMING. NOTIFY AUTHORITIE S. KEEP OUT OF WATERWAYS&STREAMS
Neutralizing Agent:NONE

===== Handling and Storage =====

Hand
ling and Storage Precautions:STORE AWAY FROM HEAT & OPEN FLAMES.
KEEP COVERED WHEN NOT IN USE
Other Precautions:MAY CAUSE BLACK STAINS ON FABRICS WHICH ARE DIFFICULT
TO REMOVE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:AIR-SUPPLIED EQUIPMENT IF EXPOSED TO HOT FUMES.
Ventilation:LOCAL EXHAUST IF NEEDED TO REMOVE HOT FUMES.
Protective Gloves:OIL-RESISTANT GLOVES
Eye Protection:SAFETY GOGGLES
Other Protective Equipment:OIL-RESISTANT APRON/C
OAT FOR PROTECTION OF
PERSONAL CLOTHING
Work Hygienic Practices:DO NOT EAT, DRINK OR SMOKE WHILE WORKING WITH
THIS PRODUCT.
Supplemental Safety and Health
AVOID CONTACT.

===== Physical/Chemical Properties =====

HCC:V6
Vapor Pres:UNK
Vapor Density:UNK
Spec Gravity:0.95
Evaporation Rate & Reference:1 (BUT ACETATE=1)
Solubility in Water:IMMISCIBLE
Appearance and Odor:BLACK LIQUID WITH PETROLEUM OIL ODOR.
Percent Volatiles by Volume:UNK

===== S

tability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES
STRONG OXIDANTS (OXYGEN, CHLORINE)
Hazardous Decomposition Products: OXIDES OF CARBON

===== Disposal Considerations =====

Waste Disposal Methods: INCINERATE IN APPROVED INCINERATOR OR DISPOSE OF
IN APPROVED CHEMICAL DUMP IN ACCORDANCE WITH LOCAL, STATE & FEDERAL
REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information

is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.