

OCTAGON PROCESS INC. -- O-S-809E AM.1, TYPE 1, CLASS 2 -- 6810-01-031-4652

=====
Product Identification
=====

Product ID:O-S-809E AM.1, TYPE 1, CLASS 2

MSDS Date:08/02/1993

FSC:6810

NIIN:01-031-4652

MSDS Number: BTRKL

=== Responsible Party ===

Company Name:OCTAGON PROCESS INC.

Address:596 RIVER ROAD

City:EDGEWATER

State:NJ

ZIP:07020-1105

Country:US

Info Phone Num:201-313-1187/FAX -1057 (CAROL)

Emergency Phone Num:201-945-9400/800-424-9300(CHEMTREC)

Preparer's Name:J.J. BURGARD

CAGE:82925

=== Contractor Identification ===

Company Name:OCTAGON PROCESS INC.

Address:596 RIVER ROAD

Box:City:EDGEWATER

State:NJ

ZIP:07020

Country:US

Phone:201-945-9400

CAGE:82925

=====
Composition/Information on Ingredients
=====

Ingred Name:SULFURIC ACID (SARA III)

CAS:7664-93-9

RTECS #:WS5600000

Fraction by Wt: 93-95%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:1 MG/M3

ACGIH TLV:1 MG/M3;

9394
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:WATER
CAS:7732-18-5
RTECS #:ZC0110000
Other REC Limits:NONE RECOMMENDED

=====
===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.
Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:CHRONIC: INHALATION OF VAPORS MAY
CAUSE SEVERE IRRITATION OR BURNS OF THE RESPIRATORY SYSTEM,
PUL
MONARY EDEMA, OR LUNG INFLAMMATION. MAY CAUSE SEVERE BURNS TO
SKIN OR EYES. INGESTION MAY CAUSE SEVERE BURNS TO MOUTH, THROAT,
AND STOMACH. MAY AFFECT KIDNEY FUNCTION. CHRONIC: MAY DAMAGE LUNGS.
Explanation of Carcinogenicity:THIS PRODUCT IS NOT LISTED BY IARC, NTP,
OR OSHA AS A CARCINOGEN.
Effects of Overexposure:SEVERE IRRITATION OR BURNS TO EYES, NOSE AND
THROAT. PULMONARY EDEMA, BRONICAL EMPHYSEMA, CONJUNCTIVITIS,
STOMATITIS, DENTAL EROSION, NAUSEA AND VOMITING.
Medical
Cond Aggravated by Exposure:OPEN WOUNDWS AND SORES. RESPIRATORY
AILMENTS SUCH AS EMPHYSEMIA AND BRONCHITIS.

=====
===== First Aid Measures =====

First Aid:INHALATION: REMOVE TO FRESH AIR. RESUSCITATE IF NOT
BREATHING. GET MEDICAL ATTENTION. EYES: IMMEDIATELY FLUSH WITH
WATER FOR AT LEAST 15 MINUTES HOLDING EYELIDS OPEN. GET MEDICAL
ATTENTION. SKIN: REMOVE CONTAMINATED CLOTHING. WASH WITH WATER FOR
AT LEAST 15 MINUTES. GET MEDICAL ADVICE. ING
ESTION: DO NOT INDUCE
VOMITING. GIVE NOTHING BY MOUTH IF UNCONSCIOUS. GET IMMEDIATE
MEDICAL ATTENTION.

=====
===== Fire Fighting Measures =====

Flash Point:NONE
Extinguishing Media:NO FIRE HAZARD.
Fire Fighting Procedures:COOL OUTSIDE OF CONTAINERS WITH WATER IF
EXPOSED TO FIRE. DO NOT PERMIT WATER TO CONTACT ACID AS THIS WILL
CAUSE SPLATTERING, OVERHEATING AND HIGHER CORROSION.
Unusual Fire/Explosion Hazard:STRONG OXIDIZER. MAY CAUSE FIRE WHEN IN

CONTACT WITH OTHER ORGANIC MATERIALS. WILL ATTACK SOME METALS
RELEASING FLAMMABLE AND EXPLOSIVE HYDROGEN.

===== Accidental Release Measures =====

Spill Release Procedures:CONTAIN AND ZONE OFF CONTAMINATED AREA. DO NOT
ALLOW SPILL TO ENTER DRAINS, SEWERS OR WATERWAYS. RECOVER
FREE-LIQUID IF POSSIBLE. NEUTRALIZE RESIDUAL SPILL WITH SODA ASH OR
SLAKE LIME. PLACE IN PROPER CONTAINERS FOR DISPOSAL.
Neutralizing Agent:SODA ASH OR SLAKE LIME.

===== Handling and Storage =====

Handling and Storage Precautions:STORE ONLY IN APPROVED CONTAINERS.
AVOID ROUGH HANDLING OF DRUMS. VENT DRUMS WEEKLY.
Other Precautions:DO NOT GET IN EYES, ON SKIN OR ON CLOTHING. DO NOT
BREATHE VAPOR. KEEP IN TIGHTLY CLOSED CONTAINER. LOOSEN CLOSURE
CAUTIOUSLY. USE WITH ADEQUATE VENTILATION. WASH THOROUGHLY AFTER
HANDLING. IN CASE OF SPILL NEUTRALIZE WITH SODA ASH OR LIME.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE REQUIRED WHERE ADEQUATE VENTILATION
CONDITIONS EXIST. IF AIRBORNE CONCENTRATION EXCEEDS TLV, A NIOSH
APPROVED SELF-CONTAINED BREATHING APPARATUS IS RECOMMENDED.
Ventilation:USE MECHANICAL (GENERAL) OR LOCAL EXHAUST VENTILATION TO
MEET TLV REQUIREMENTS.
Protective Gloves:RUBBER
Eye Protection:SAFETY GOGGLES WITH OPTIONAL FACE SHIELD
Other Protective Equipment:EYE WASH STATION AND SAFETY SHOWER.
INDUSTRIAL-TYPE WORK CLOTHING AND AP
RON AS REQUIRED.
Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND
RECOMMENDED PROCEDURES. LAUNDRY CONTAMINATED CLOTHING BEFORE REUSE.
Supplemental Safety and Health
AVOID PROLONGED OR REPEATED EXPOSURE. DO NOT GET ON SKIN OR IN EYES. DO
NOT BREATHE VAPORS OR MISTS. "NO SMOKING" REGULATIONS MUST BE
ENFORCED BECAUSE OF THE POSSIBLE PRESENCE OF HYDROGEN. NSN HAS BEE
N CANCELLED WITHOUT A REPLACEMENT.

===== Physical/Chemical Properties =====

=====

HCC:C1

Boiling Pt:B.P. Text:535F,279C

Vapor Pres:< 0.5

Spec Gravity:1.8357

Evaporation Rate & Reference: