

BELZONA AMERICA INC -- 1024/0866, BELZONA 1111 BASE -- 8030-00-187-7747

=====
Product Identification
=====

Product ID:1024/0866, BELZONA 1111 BASE

MSDS Date:02/17/1992

FSC:8030

NIIN:00-187-7747

Kit Part:Y

MSDS Number: BTSMS

=== Responsible Party ===

Company Name:BELZONA AMERICA INC

Address:2000 NW 88 COURT

City:MIAMI

State:FL

ZIP:33172

Country:US

Info Phone Num:305-594-4994

Emergency Phone Num:

305-594-4994 OR 305-274-6512

Preparer's Name:J. PARTINGTON

CAGE:0PX05

=== Contractor Identification ===

Company Name:BELZONA INC.

Address:2000 N. W. 88 COURT

Box:City:MIAMI

State:FL

ZIP:33172

Country:US

Phone:305-594-4994

CAGE:0PX05

=====
Composition/Information on Ingredients
=====

Ingred Name:DGBA EPOXY RESINS

CAS:25068-38-6

RTECS #:SL6475000

Fraction by Wt: 10-30%

Other REC Limits:NONE RECOMMENDED

Ingred Name:EPOXIDIZED PHENOL-FORMALDEHYDE NOVOLAC

CAS:28064-14-4

Fraction

by Wt: 10-30%

Other REC Limits:NONE RECOMMENDED

Ingred Name:MODIFIED SILICA

CAS:92797-60-9

Fraction by Wt: 1-5%

Other REC Limits:NONE RECOMMENDED

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: SKIN AND EYE IRRITATION.
CHRONIC: IRRITATION, SENSITIZATION AND DERMATITIS.
Explanation of Carcinogenicity:NOT RELEVANT.
Effects of
Overexposure:SKIN SENSITIZER AND SKIN IRRITATION.
Medical Cond Aggravated by Exposure:SKIN & EYE CONDITIONS.

=====
===== First Aid Measures =====

First Aid:INHALE-REMOVE SOURCE OF CONTAMINATION &/OR MOVE VICTIM TO
FRESH AIR. IF RECOVERY IS DELAYED, OBTAIN MEDICAL ATTENTION.
EYE-FLUSH W/WATER FOR AT LEAST 15 MINS. IMMEDIATE FIRST AID IS
NEEDED TO PREVENT EYE DAMAGE. SEEK PHYSICIAN. SKIN-IMMEDIATELY
REMOVE EXCESS WITH A CLEAN CLOTH & WASH W/SOAP
& WATER. SEE
PHYSICIAN. INGEST-DO NOT INDUCE VOMITING. RINSE MOUTH WITH WATER &
DRINK 1 CUP WATER. SEE DOC.

=====
===== Fire Fighting Measures =====

Flash Point Method:SCC
Flash Point:>392F,>200C
Lower Limits:NIA
Upper Limits:NIA
Extinguishing Media:WATER FOG (NOT A DIRECT STREAM OF WATER), FOAM,
CARBON DIOXIDE & DRY CHEMICAL.
Fire Fighting Procedures:WEAR PROTECTIVE CLOTHING & USE SELF-CONTAINED
BREATHING APPARATUS. FULL BUNKER GEAR SHOULD BE WORN

IN EXTREME

CASES. USE SAND TO CONTAIN BURNING MATERIAL.

Unusual Fire/Explosion Hazard:DECOMPOSITION AND COMBUSTION PRODUCTS MAY BE HAZARDOUS.

===== Accidental Release Measures =====

Spill Release Procedures:ABSORB W/AN INERT MATERIAL (E.G. EARTH/SAND) . SWEEP UP, PLACE INTO SUITABLE LABELLED CONTAINERS, SEAL & DISPOSE OF PROPERLY. FLUSH AREA W/DETERGENT & WATER.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:CONTAINERS SHOULD BE STORED UNDER COOL, DRY CONDITIONS. OVERHEATING MAY CAUSE CONTRS TO RUPTURE. EMPTY CONTRS WILL RETAIN RESIDUE & MAY BE DANGEROUS.

Other Precautions:CHECK ALL CONTAINERS FOR LEAKS AT REGULAR INTERVALS & BEFORE USE. AVOID BREATHING VAPORS & CONTACT W/SKIN & EYES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IN CONFINED AREAS OR WHERE GOOD NATURAL/MECH

VENT IS NOT AVAIL, LEADING TO RISK OF EXCEEDING TLV'S INDICATED, OR WHERE MACHINING/ABRADING OF CURED MATL LEADS TO PRODUCTION OF RESPIRABLE &/OR NUISANCE DUST, AN APPROVED RESPIRATOR WORN.

Ventilation:WHERE ADEQUATE NATURAL VENTILATION IS NOT AVAILABLE PROVIDE SUITABLE LOCAL EXHAUST VENTILATION.

Protective Gloves:IMPERMEABLE GLOVES (NEOPRENE OR PVC).

Eye Protection:SAFETY GLASSES OR GOGGLES.

Other Protective Equipment:WHERE THERE IS RISK OF CONTAM OF FOOTWEAR, SAFETY BOOTS SHO

ULD BE WORN & CLEANED THORO BEFORE REUSE.

Work Hygienic Practices:WHEN USING, DO NOT EAT, DRINK OR SMOKE. REMOVE CONTAMD CLTHG & LAUNDRER BEFORE REUSE. WASH HANDS W/SOAP & WATER.

Supplemental Safety and Health
NONE.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:DECOMPOSES

Vapor Pres:NIA

Vapor Density:NIA

Spec Gravity:2.80

Evaporation Rate & Reference:N.AP

Solubility in Water:NEGLIGIBLE

Appearance and Odor:DARK GRAY PASTE WITH EPOXY ODOR.

Perce

nt Volatiles by Volume:N.AP

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS, ACIDS, BASES AND AMINES.

Stability Condition to Avoid:NOT APPLICABLE.

Hazardous Decomposition Products:GASEOUS COMBINATION OF CARBON,
HYDROGEN, & OXYGEN MAY OCCUR AT ELEVATED TEMPERATURE.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE &
FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to the
ir
particular situation.