

CRAWFORD LABS, INC -- H8-010 -- 8010-01-344-5102

=====  
Product Identification  
=====

Product ID:H8-010  
MSDS Date:12/06/1993  
FSC:8010  
NIIN:01-344-5102  
MSDS Number: BTTDC  
=== Responsible Party ===  
Company Name:CRAWFORD LABS, INC  
Address:4165 S EMERALD AVE  
City:CHICAGO  
State:IL  
ZIP:60609  
Country:US  
Info Phone Num:312-376-7132  
Emergency Phone Num:312-376-7132 800-424-9300(CHEMTREC)  
CAGE:5V430  
=== Co  
ntractor Identification ===  
Company Name:CRAWFORD LABORATORIES, INC  
Address:4165 SOUTH EMERALD AVENUE  
Box:City:CHICAGO  
State:IL  
ZIP:60609  
Country:US  
Phone:312-376-7132  
CAGE:5V430

=====  
Composition/Information on Ingredients  
=====

Ingred Name:NAPHTHA, LIGHT AROMATIC  
CAS:64742-95-6  
Fraction by Wt: 5.3%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:100 PPM (NAPHTHA)  
ACGIH TLV:400 PPM (NAPHTHA)

Ingred Name:1,2,4-TRIMETHYLBENZENE (SARA III)  
CAS:95-63-6  
RTECS #:DC3325000  
Fraction by W

t: 2.6%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:25 PPM  
ACGIH TLV:25 PPM; 9394

Ingred Name:TITANIUM DIOXIDE  
CAS:13463-67-7  
RTECS #:XR2275000  
Fraction by Wt: 19%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:15 MG/M3 TDUST  
ACGIH TLV:10 MG/M3 TDUST; 9394

Ingred Name:SILICA, CRYSTALLINE - QUARTZ  
CAS:14808-60-7  
RTECS #:VV7330000  
Fraction by Wt: 4.4%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:SEE TABLE Z-3  
ACGIH TLV:0.1 MG/M3 RDUST;9394

Ingred Name:VM&P NAPHTHA (LIGROINE)  
CAS:8032-32-4  
RTECS #:OI61  
80000  
Fraction by Wt: 10%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:300 PPM  
ACGIH TLV:300 PPM; 9394

Ingred Name:VOLATILE ORGANIC COMPOUNDS  
RTECS #:9999999VO  
Fraction by Wt: 56.1%  
Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO  
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO  
Health Hazards Acute and Chronic:EYES:MAY CAUSE IRRITATION,POSSIBLE  
DAMAGE.SKIN:MAY CAUSE IRRITA

TION AND DEFATTING.INGEST:MAY CAUSE GI  
TRACT IRRITATION.INHAL:MAY CAUSE RESPIRATORY IRRITATION.

Explanation of Carcinogenicity:SILICON DIOXIDE IS A POTENTIAL  
CARCINOGEN.

Effects of Overexposure:INHAL:HEADACHE,DIZZINESS,NAUSEA,POSSIBLE LOSS  
OF CONSCIOUSNESS.INGEST:VOMITING.SKIN:SENSITIZATION.

Medical Cond Aggravated by Exposure:PERSONS WITH PRE-EXISTING  
RESPIRATORY AILMENTS MAY BE AT INCREASED RISK FROM EXPOSURE.

=====  
First Aid Measures  
=====

=

First Aid:SKIN:REMOVE CONTAMINATED CLOTHING;WASH WITH SOAP AND  
WATER.EYES:FLUSH WITH WATER FOR 15 MINUTES.INHAL:REMOVE TO FRESH  
AIR.GIVE OXYGEN OR ARTIFICIAL RESPIRATION IF NEEDED.INGEST:GET  
PROMPT QUALIFIED ME DICAL ATTENTION.INDUCE VOMITING ONLY UNDER THE  
ADVICE OF A PHYSICIAN.IF SPONTANEOUS VOMITING OCCURS,KEEP HEAD  
BELOW HIPS.

=====  
Fire Fighting Measures  
=====

Flash Point Method:SCC

Flash Point:100F,38C

Lower Limits:0.9

Extinguishin

g Media:FOAM,DRY CHEMICAL,CARBON DIOXIDE.

Fire Fighting Procedures:USE A SELF-CONTAINED BREATHING APPARATUS AND  
FULL PROTECTIVE EQUIPMENT.COOL FIRE EXPOSED CONTAINERS WITH WATER  
FOG.

Unusual Fire/Explosion Hazard:WATER SPRAY MAY SPREAD BURNING  
LIQUID.CONTAINERS MAY BURST FROM HEAT OF FIRE.VAPORS CAN FORM  
EXPLOSIVE MIXTURES WITH AIR.

=====  
Accidental Release Measures  
=====

Spill Release Procedures:ELIMINATE SOURCES OF IGNITION.USE PROPER  
RESPIRATO  
RY AND PROTECTIVE EQUIPMENT.SHUT OFF LEAK IF  
SAFE.DIKE.SOAK UP WITH A NON-COMBUSTIBLE INERT  
ABSORBANT(CLAY,SAND);PLACE IN PROPER CONTAINER FOR DISPOSAL.USE  
NON-SPARKING TOOLS.

Neutralizing Agent:NONE

=====  
Handling and Storage  
=====

Handling and Storage Precautions:STORE IN A COOL,DRY,WELL-VENTILATED  
PLACE.KEEP CONTAINER CLOSED WHEN NOT IN USE.

Other Precautions:USE CAUTION WHEN USING WITH HIGH HEAT;VAPORS CAN FORM  
EXPLOSIVE MIXTURES WITH

AIR.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:WHERE ENVIRONMENTAL CONTROLS ARE LACKING OR IN ENCLOSED SPACES USE A NIOSH/MSHA APPROVED RESPIRATOR FOR ORGANIC VAPORS.

Ventilation:LOCAL VENTILATION AT THE WORKSITE;MECHANICAL(GENERAL) VENTILATION TO MAINTAIN TLV/PEL.

Protective Gloves:RUBBER

Eye Protection:SAFETY GOGGLES.

Other Protective Equipment:PROVIDE A LOCAL EYE WASH STATION AND SAFETY SHOWER.

Work Hygienic Practices:USE REASONABLE CARE IN HANDLING THIS PRODUCT.WASH HANDS AFTER USE AND BEFORE EATING.

Supplemental Safety and Health  
NONE

=====  
===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:308F-396F

Vapor Density:>1

Spec Gravity:1.65

Viscosity:87 KU

Evaporation Rate & Reference:0.13 (N-BUTYL ACETATE=1)

Solubility in Water:SLIGHT

Appearance and Odor:LIQUID;GRAY;SOLVENT ODOR.

Percent Volatiles by Volume:34.2

=====  
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS AND ALKALIES.

Stability Condition to Avoid:HIGH HEAT,SOURCES OF IGNITION.

Hazardous Decomposition Products:CARBON DIOXIDE,CARBON MONOXIDE

=====  
===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH FEDERAL,STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by ele

ments of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.