

CRC CHEMICALS U.S.A./CRC INDUSTRIES, INC. -- 03030, EXTREME DUTY SILICONE AEROSOL --
6850-01-265-3115

===== Product Identification =====

Product ID:03030, EXTREME DUTY SILICONE AEROSOL
MSDS Date:11/12/1992
FSC:6850
NIIN:01-265-3115
MSDS Number: BTTKZ
=== Responsible Party ===
Company Name:CRC CHEMICALS U.S.A./CRC INDUSTRIES, INC.
Address:885 LOUIS DRIVE
City:WARMINSTER
State:PA
ZIP:18974-2820

Country:US
Info Phone Num:215-674-4300
Emergency Phone Num:215-674-4300
Preparer's Name:JON BROWN
CAGE:10136
=== Contractor Identification ===
Company Name:CRC INDUSTRIES, INC.
Address:885 LOUIS DRIVE
Box:City:WARMINSTER
State:PA
ZIP:18974-2820

Country:US
Phone:215-674-4300/800-424-9300
CAGE:10136
Company Name:GENERAL TOOL & SUPPLY CO.
Address:5614 7TH AVENUE SOUTH
Box:80904
City:SEATTLE
State:WA
ZIP:98108-3317

Country:US
Phone:206-762-1500
CAGE:3Z323
Company Name:NETEX INDUSTRIES(FORMER NORTHE

AST TEXAS IND)
Address:1700 NORTH EDWARDS STREET
Box:City: MOUNT PLEASANT
State:TX
ZIP:75455
Country:US
Phone:903-577-0388
CAGE:0WAG0
Company Name:PIONEER VALVE AND FITTING CO INC
Address:93 SEIGAL ST
Box:City:BROOKLYN
State:NY
ZIP:11206-3204
Country:US
Phone:718-387-4724
CAGE:66200
Company Name:SAN DIEGO MARINE HARDWARE INC
Address:1660 LOGAN AVENUE
Box:City:SAN DIEGO
State:CA
ZIP:92113
Country:US
Phone:619-231-8334
CAGE:7F580

=====
===== Composition/Information on Ingredients =====

Ingred Name:SILICONE FLUID (PER MSDS CAS# 58957-05-1).
Fraction by Wt: 2-5%
Other REC Limits:NONE RECOMMENDED

Ingred Name:ISOHEXANE
CAS:107-83-5
RTECS #:SA2995000
Fraction by Wt: 55-65%
Other REC Limits:NONE RECOMMENDED

Ingred Name:HEXANE (N-HEXANE)
CAS:110-54-3
RTECS #:MN9275000
Fraction by Wt: 5-10%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:500 PPM
ACGIH TLV:50 PPM; 9394
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:PROPANE
CAS:74-98-6
RTECS #:TX2275000
Fraction by Wt: 10-20%
Other REC L

imits:NONE RECOMMENDED
OSHA PEL:1000 PPM
ACGIH TLV:ASPHYXIAN; 9394

Ingred Name:ISOBUTANE
CAS:75-28-5
RTECS #:TZ4300000
Fraction by Wt: 10-20%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:1000 PPM
ACGIH TLV:1000 PPM

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE:EYE:BURNING & IRRIT. SKIN:MILD
IRRIT. INHAL:IRRIT OF RESP TRAC
T. CHRONIC:REPEATED OVEREXPOSRES MAY
CAUSE HARM TO NERVOUS SYSTEM.
Explanation of Carcinogenicity:PER MSDS NO CHEM LISTED AS CARCINOGEN OR
POTENTIAL CARCINOGE IN NTP/IARC/OSHA LISTINGS.
Effects of Overexposure:DIZZINESS, HEADACHES, CENTRAL NERVOUS SYSTEM
DEPRESSION.
Medical Cond Aggravated by Exposure:PRE-EXISTING LUNG DISORDERS.

===== First Aid Measures =====

First Aid:IF SYMPTOMS PERSIST CALL DOCTOR. INHAL: REMOVE TO FRESH AIR.
APPLY ARTI
RESP IF NECESSARY. EYE:FLUSH W/LG AMTS OF WATER FOR
15MINS. SKIN:WASH W/SOAP & WATER. REMOVE CONTAMINATED CLOTHING.
INGEST:DO NO T INDUCE VOMITING. CALL PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point: