View NSN Online: https://aerobasegroup.com/nsn/8010-00-286-7731

PRATT & LAMBERT, INC. -- ENAMEL ALKYD GLOSS GRAY 16187 -- 8010-00-286-7731

Product ID: ENAMEL ALKYD GLOSS GRAY 16187

MSDS Date:11/06/1989

FSC:8010

NIIN:00-286-7731

MSDS Number: BTTSJ === Responsible Party ===

Company Name: PRATT & LAMBERT, INC.

Address:16116 E 13TH ST

Box:2153 City:WICHITA State:KS

ZIP:67201 Country:US

Info Phone Num:316-733-1361

Emergency Phone N um:316-733-1361 CAGE:FO127

=== Contractor Identification ===

Company Name: PRATT & LAMBERT, INC/BUFFALO, NY 14240

Box:22

CAGE:FO127

Company Name: PRATT AND LAMBERT INC

Address:Box:6027 City:CLEVELAND

State:OH

ZIP:44101-1027 Country:US

Phone:216-566-2902

CAGE:61196

======= Composition/Information on Ingredients ========

Ingred Name:STODDARD SOLVENT

CAS:8052-41-3


RTECS #:WJ8925000 Fraction by Wt: 30%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:500 PPM

ACGIH TLV:100 PPM; 9394

Ingred Na



Respiratory Protection:RESPIRATOR MAY BE REQUIRED UNDER CERTAIN CONDITIONS, SUCH AS SPRAYING. A PREFILTER MAY ALSO BE REQUIRED. IN CONFINED AREAS USE A NIOSH/MSHA APPROVED AIR SUPPLIED RESPIRATOR.

Ventilation: GENERAL DILUTION & LOCAL EXHAUST VENTILATION IN SUFFICIENT VOLUME AND PATTERN TO MAINTAIN CONCENTRATIONS BELOW LIMITS.

Protective Gloves: SOLVENT IMPERMEABLE GLOVES.

Eye Protection: WEAR SAFETY SPECTACLES.

Other Protective Equipment: NOT LIKELY TO BE NEEDED.

Work Hyg

ienic Practices:WASH HANDS AFTER EACH USE OF THIS PRODUCT Supplemental Safety and Health NONE

======== Physical/Chemical Properties ==========

HCC:F4

Boiling Pt:=135.C, 275.F Vapor Density:>AIR

Evaporation Rate & Deference: SLOWER THAN ETHER

Appearance and Odor: GRAY ENAMEL

Percent Volatiles by Volume:58

======== Stability and Reactivity Data ==========

Stability Indicator/Materials to Avoid:YES STRONG ACIDS OR ALKALINE MATERIALS. Stability Condition t

o Avoid:AVOID EXCESSIVE HEAT AND SOURCES OF IGNITION.

Hazardous Decomposition Products:BURNING/WELDING/CUTTING WILL PRODUCE SMOKE, CARBON MONOXIDE AND CARBON DIOXIDE.

Conditions to Avoid Polymerization: KEEP AWAY FROM HEAT, SPARKS AND FLAME.

======= Disposal Considerations ===========

Waste Disposal Methods:INCINERATE IN EPA PERMITTED FACILITY.
CONTAMINATED ABSORBANT MAY BE DISPOSED OF IN A HAZARDOUS WASTE LANDFILL. DISPOSE IN ACCORDANCE WITH FEDERAL,
STATE AND LOCAL

REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibi

lity for the suitability of this information to their particular situation.	