

BELL FUELS, INC -- #2 DIESEL LOW SULFUR -- 9140-00-286-5296

=====
Product Identification
=====

Product ID:#2 DIESEL LOW SULFUR

MSDS Date:10/01/1993

FSC:9140

NIIN:00-286-5296

MSDS Number: BTWQD

=== Responsible Party ===

Company Name:BELL FUELS, INC

Address:4116 WEST PATERSON AVE

City:CHICAGO

State:IL

ZIP:60646

Country:US

Info Phone Num:312-286-0200

Emergency Phone Num:312-286-0200

CAGE:JO756

=== C

Contractor Identification ===

Company Name:BELL FUELS INC

Address:4116 W PETERSON AVE

Box:City:CHICAGO

State:IL

ZIP:60646-6017

Country:US

Phone:312-286-0200

CAGE:8P539

Company Name:BELL FUELS, INC

Address:4116 WEST PATERSON AVE

Box:City:CHICAGO

State:IL

ZIP:60646

Country:US

Phone:312-286-0200

CAGE:JO756

=====
Composition/Information on Ingredients
=====

Ingred Name:HYDROCARBONS, AROMATIC

Fraction by Wt: 15-45%

Other REC Limits:NONE RECOMMENDED

Ingred Name:OLEFINS (UNSATURATED

HYDROCARBONS)

Fraction by Wt: 1-6%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:5 MG/M3 (OIL MIST)

ACGIH TLV:5 MG/M3 (OIL MIST)

Ingred Name:PARAFFINS & CYCLOPARAFFINS (SATURATED HYDROCARBONS)

Fraction by Wt: 54-85%

Other REC Limits:NONE RECOMMENDED

Ingred Name:COMPLEX MIXTURE OF PARFFINIC, CYCLOPARAFFINIC, OLEFINIC AND AROMATIC HYDROCARBONS

Fraction by Wt: N/GIVEN

Other REC Limits:NONE RECOMMENDED

=====
===== Hazards Identification =====

Routes of Entry: Inhala

tion:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:HARMFUL OR FATAL IF SWALLOWED.

PRODUCES SKIN IRRITATION UPON PROLONGED OR REPEATED CONTACT.

Explanation of Carcinogenicity:PER MSDS:CARCINOGENICITY N/A FOR NTP, IARC, OSHA.

Effects of Overexposure:EYE IRRITATION, SKIN IRRITATION FOLLOWING REPEATED CONTACT. INGESTION MAY CAUSE ACUTE GASTRIC. ACUTE CHEMICAL PNEUMONITIS. ASPIRATION CAN RESULT IN RESPIRATORY DISTRESS

Medical Cond Aggravated by Exposure:N/A.

=====
===== First Aid Measures =====

First Aid:EYE:RINSE THOROUGHLY W/WATER. SKIN:WASH THOROUGHLY W/SOAP & WATER. INHAL:REMOVE FROM CNTAMINATED AREA. GIE FRESH AIR.

INGEST:GIVE VEGETABLE OIL TO RETARD ABSORBTIN. DO NOT INDUCE VOMIT. GET IMMED MED ATTN.

=====
===== Fire Fighting Measures =====

Flash Point Method:PMCC

Flash Point:130F,54C (MIN)

Lower Limits:7.5

Upper Limits:0.6

E

Extinguishing Media: ANY UL APPROVED CLASS B MEDIA SUCH AS FOAM, CARBON DIOXIDE, OR DRY CHEMICAL.

Fire Fighting Procedures: AVOID USE OF SOLID WATER STREAMS. AVOID EXCESSIVE WATER SPRAY APPLICATION. WATER CAN BE USED TO COOL EXPOSED SURFACES.

Unusual Fire/Explosion Hazard: NONE SPECIFIED BY MFG.

===== Accidental Release Measures =====

Spill Release Procedures: KEEP PUBLIC AWAY. SHUT OFF SOURCE W/O HAZ.

ADVISE POLICE & NATL RESPONSE CENTER 800-424-8802 IF SUBSTANCE

ENTERED WATERCOURSE OR SEWER. CONTAIN LIQUID W/EARTH/SAND. RECOVER FREE LIQUID BY PUMPING OR SUITABLE SORBENT.

Neutralizing Agent: NOT APPLICABLE.

===== Handling and Storage =====

Handling and Storage Precautions: STORE IN RELATIVELY COOL PLACE. STORE IN CLEARLY MARKED CNTNR. DO NOT EXPOSE TO HEAT OR FLAME. DO NOT STORE W/OXIDIZERS. USE APPROPRIATE DISPENSING TECHNI

Other Precautions: N/A.

===== Exposure Controls/Personal Protection =====

Respiratory Protection: FOR MISTS AND HIGH VAPOR LEVELS CHEMICAL CARTRIDGE RESPIRATOR OR AIR SUPPLIED EQUIPMENT.

Ventilation: LOCAL EXHAUST VENTILATION IS REQUIRED. USE MECHANICAL VENTILATION EQUIPMENT THAT IS EXPLOSION PROOF.

Protective Gloves: NEOPRENE, NITRILE, PVA GLOVES.

Eye Protection: N/A.

Other Protective Equipment: N/A.

Work Hygienic Practices: WASH HANDS AFTER HANDLING. ANY CONTAMINATED CLOTHING WASH PRIOR TO REUSE.

Supplemental Safety and Health

BOILING PT RAN

GE: 320-700F.

===== Physical/Chemical Properties =====

HCC: F4

Boiling Pt: B.P. Text: 320F, 160C

Spec Gravity: 0.88

Solubility in Water: NEGLIGIBLE.

Appearance and Odor: AMBER TINT LIQUID; AROMATIC.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

NONE SPECIFIED BY MFG.

Stability Condition to Avoid: N/A PER MFG. HOWEVER AVOID SOURCES OF IGNITION.

Hazardous Decomposition Products: NONE SPECIFIED BY MFG.

=====

===== Disposal Considerations =====

Waste Disposal Methods:WHERE SOLID ABSORBENTS ARE USED TO CONTROL SPILLS & USED SORBENT SHOULD BE INCINERATED PER APPLICATION STATE OR LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.