TEXACO INC -- 00423 TEXACO LOW SULFUR DIESEL 1 -- 9140-00-000-0185

Product ID:00423 TEXACO LOW SULFUR DIESEL 1 MSDS Date:09/02/1993 FSC:9140 NIIN:00-000-0185 MSDS Number: BVGFT === Responsible Party === **Company Name: TEXACO INC** Address:1111 RUSK Box:52332 **City:HOUSTON** State:TX ZIP:77052 Country:US Info Phone Num:914-838-7204 Emergency Phone Num:800-424-9300(CHEMT REC) 914-831-3400 Preparer's Name: MANAGER, PRODUCT SAFETY CAGE:3B431 === Contractor Identification === Company Name: TEXACO PIPELINE INC (SUB OF TEXACO INC) Address:9700 RICHMOND AVE Box:42286 City:HOUSTON State:TX ZIP:77242-2286 Country:US Phone:713-953-4260 CAGE:3B431 Company Name: TEXACO REFINING AND MARKETING INC Address:1111 RUSK ST Box:City:HOUSTON State:TX ZIP:77002-3310 Country:US Phone:713-650-5206 CAGE:2R503

Ingred Na

me:STRAIGHT-RUN KEROSENE CAS:8008-20-6 RTECS #:OA5500000 Fraction by Wt: 100% Other REC Limits:NONE RECOMMENDED **OSHA PEL:100 PPM** ACGIH TLV:100 PPM 9091 Ingred Name: BENZENE (SARA III) CAS:71-43-2 RTECS #:CY1400000 Fraction by Wt: 115F.>46C Lower Limits:0.7 **Upper Limits:5** Extinguishing Media:WATER SPRAY, DRY CHEMICAL, FOAM, OR CARBON DIOXIDE. WATER OR FOAM MAY CAUSE FROTHING. Fire Fighting Procedures: WEAR SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE GEAR. USE WATER FOG TO COOL F IRE EXPOSED CONTAINERS AND TO DIPERSE VAPORS. Unusual Fire/Explosion Hazard:NONE SPECIFIED BY MANUFACTURER. 

Spill Release Procedures: VENTILATE AREA. USE SCBA OR SUPPLIED AIR IF CONFINED AREA OR LARGE SPILL. CONTAIN SPILL IF POSSIBLE. WIPE UP OR ABSORB IN SUITABLE MATERIAL AND SHOVEL INTO CONTAINER. PREVENT ENTRY INTO SEWER OR WATER AY. Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

andling and Storage ========H

Handling and Storage Precautions:STORE AWAY FROM HEAT AND IGNITION SOURCES. HANDLE AND STORE IN ACCORDANCE WITH OSHA REG. 1910.106.
Other Precautions:USE ONLY AS A FUEL. THIS PRODUCT IS NOT INTENDED FOR USE IN SPACE HEATERS. DO NOT USE IN AGRICULTURAL SPRAYS. WARNING! THIS PRODUCT CONTAINS DETECTABLE AMOUNTS OF BENZENE AND TOLUENE.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection: USE USE NIOSH/MS

HA APPROVED SELF-CONTAINED

BREATHING APPARATUS OR SUPPLIED AIR RESPIRATOR IF VAPOR, MIST, OR DUST IS GENERATED.

Ventilation:LOCAL EXHAUST VENTILATION RECOMMENDED IF GENERATING VAPOR, DUST OR MIST.

Protective Gloves:NITRILE

Eye Protection:SAFETY GLASSES/CHEMICAL SPLASH GOGGLES

Other Protective Equipment: PROTECTIVE CLOTHING (EG COVERALLS) TO PREVENT PROLONGED OR REPEATED SKIN CONTACT.

Work Hygienic Practices: USE GOOD PERSONAL HYGENE. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

ATTENTION! POSSIBLE CANCER HAZARD. CONTAINS MIDDLE DISTILLATES WHICH MAY CAUSE CANCER BASED ON ANIMAL DATA.

HCC:F4 Boiling Pt:B.P. Text:304F,151C Vapor Pres: