

QPL INC -- VV-P-236 -- 9150-00-250-0926

===== Product Identification =====

Product ID:VV-P-236
MSDS Date:08/01/1993
FSC:9150
NIIN:00-250-0926
MSDS Number: BVGJF
=== Responsible Party ===
Company Name:QPL INC
Address:800 N ACADIA RD
City:THIBODAUX
State:LA
ZIP:70301
Country:US
Info Phone Num:504-449-0660
Emergency Phone Num:504-449-0660
Preparer's Name:NONE
CAGE:KO854

=== Contractor Identification
===

Company Name:QPL INC
Address:800 N ACADIA RD
Box:City:THIBODAUX
State:LA
ZIP:70301
Country:US
Phone:504-449-0660
CAGE:KO854
Company Name:QPL INC, FORMERLY OMNITECH INTERNATIONAL, INC.
Address:800 N. ACADIA ROAD
Box:City:THIBODAUX
State:LA
ZIP:70301
Country:US
Phone:504-394-8440
CAGE:0AD61

===== Composition/Information on Ingredients =====

Ingred Name:PETROLATUM
CAS:8009-03-8
Other REC Limits:NONE RECOMMENDED
OSHA PEL:5 MG/M3 (OIL MIST)
ACGIH TLV:5 MG/M3 (MIST) 9394

=====

===== **Hazards Identification**=====

Routes of Entry: Inhalation:NO Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:NONE SPECIFIED BY MANUFACTURER.
Explanation of Carcinogenicity:NONE
Effects of Overexposure:NONE SPECIFIED BY MANUFACTURER.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== **First Aid Measures**=====

First Aid:EYES: FLUSH WITH LARGE AMOUNTS OF WATER. GET MEDICAL ATTENTION. SKIN: FOR MOLTEN PETROLATUM, FLUSH WITH COLD WATER. GET MEDICAL ATTENTION. FOR SOLID PETROLATUM REMOVE EXCESS WITH PAPER TOWELS. WASH AREA WITH SOAP AND WATER. INHALATION: NO DATA AVAILABLE. INGESTION: GET MEDICAL ATTENTION.

===== **Fire Fighting Measures**=====

Flash Point Method:COC
Flash Point:>400F,>204C
Extinguishing Media:DRY CHEMICAL, CARBON DIOXIDE, FOAM, WATERFOG, SAND/EARTH.
Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA TO PROTECT AGAINST SMOKE INHALATION AND FULL PROTECTIVE EQUIPMENT. WATER SPRAY IS UNSUITABLE EXTINGUISHING AGENT.
Unusual Fire/Explosion Hazard:NONE.

===== **Accidental Release Measures**=====

Spill Release Procedures:SHUT OFF LEAK AND DIKE UP LARGE SPILLS. AFTER COOLING AND SOLIDIFICATION, SCRAP AND/OR SHOVEL UP MATERIAL. FINALLY, CLEAN AREA WITH AN OIL ABSORBENT MATERIAL.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== **Handling and Storage**=====

Handling and Storage Precautions:STORE AWAY FROM FLAME, HEAT (200F MAX) AND STRONG OXIDIZING AGENTS. AVOID SKIN AND EYE CONTACT.
Other Precautions:NONE SPECIFIED BY MANUFACTURER.

===== **Exposure Controls/Personal Protection**=====

Respiratory Protection:NO DATA AVAILABLE.
Ventilation:NORMAL ROOM VENTILATION SHOULD BE ADEQUATE.
Protective Gloves:WEAR IMPERVIOUS GLOVES.
Eye Protec

tion:FACE SHIELD OVER SAFETY GLASSES.

Other Protective Equipment:WEAR OVERALLS.

Work Hygienic Practices:WASH AFTER HANDLING AND BEFORE EATING,
DRINKING, OR SMOKING. LAUNDRY CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

READ ALL LABELS CAREFULLY BEFORE USING.

===== Physical/Chemical Properties =====

HCC:V6

Melt/Freeze Pt:M.P/F.P Text:110 TO 180F

Solubility in Water:NIL

Appearance and Odor:YELLOW OR BROWN, SEMI-SOLID, OIL LIKE, OPAQUE
COLO

R.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:AVOID HEAT ABOVE 200F.

Hazardous Decomposition Products:NONE.

Conditions to Avoid Polymerization:WILL NOT OCCUR.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF WASTE IN ACCORDANCE WITH LOCAL, STATE
AND FEDERAL REGULATIONS.

Disclaimer (provided with this information b
y the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.