

DAP INC -- WELDWOOD ORGINIAL CONTACT CEMENT, DAP -- 8040-00-142-9193

=====
Product Identification
=====

Product ID:WELDWOOD ORGINIAL CONTACT CEMENT, DAP

MSDS Date:09/27/1988

FSC:8040

NIIN:00-142-9193

MSDS Number: BVTVS

=== Responsible Party ===

Company Name:DAP INC

Address:5300 HUBERVILLE RD

Box:277

City:DAYTON

State:OH

ZIP:45401-0277

Country:US

Info Phone Num:800-513-3810

Emergency Phone Num:800

-543-3840 800-535-5053

CAGE:90300

=== Contractor Identification ===

Company Name:DAP INC.

Box:277

City:DAYTON

State:OH

ZIP:45401-0277

Country:US

Phone:513-253-7154/800-543-3840

CAGE:90300

=====
Composition/Information on Ingredients
=====

Ingred Name:METHYL CHLOROFORM (1,1,1-TRICHLOROETHANE) (SARA III)

CAS:71-55-6

RTECS #:KJ2975000

Fraction by Wt: 29%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:350 PPM

ACGIH TLV:350 PPM/450STEL;9394

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Oz

one Depleting Chemical:1

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 20%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:200 PPM; Z-2

ACGIH TLV:S, 50 PPM; 9394

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:1,4-DIOXANE (DIETHYLENE DIOXIDE) (SARA III)

CAS:123-91-1

RTECS #:JG8225000

Fraction by Wt: 1%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:S, 100 PPM

ACGIH TLV:S, 25 PPM; 9394

EPA Rpt Qty:100 LBS

DOT Rpt Qty:100 LBS

Ingred Name:VM & P NAPHTHA

CAS:64742-8

9-8

Fraction by Wt: 50%

Other REC Limits:NONE RECOMMENDED

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYE:IRRIT. SKIN:IRRIT. PROLONG/REPEAT

CONTACT MAY CUASE DEFATTING OF SKIN LEADING TO DERMATITIS.

INGEST:HARMFUL/FATAL. CAUSES VOMIT, DIARR, DEPRESSED RESP. MAY

CAUSE LIVER ABNORMALITIES, KIDNEY DAMAGE & LUNG DAMAGE

IN LAB

ANIMALS. INHAL:MAY AFFECT BRAIN OR NERVOUS SYSTEM DAMAGE.

Effects of Overexposure:EYE/SKIN IRRITANT. DERMATITIS. INGEST:VOMITING,

DIARRHEA, DEPRESSED RESPIRATION. INHAL:MAY AFFECT BRAIN OR NERVOUS

SYSTEM DAMAGE.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MFG.

=====
===== First Aid Measures =====

First Aid:EYE:FLUSH W/WATER FOR 15MINS. CONTACT DR IMMED. SKIN:WASH

IMMED W/SOAP & WATER. INGEST:DO NOT INDUCE VOMIT. CONTACT DR OR

REGIONAL POISON CONTROL CENTER IMMEDIATE. INHALATION: REMOVE TO FRESH AIR.
CONTACT DR IMMEDIATE.

===== Fire Fighting Measures =====

Flash Point: 21.0F, -6.1C

Lower Limits: 1.0

Upper Limits: 7.0

Extinguishing Media: FOAM, CARBON DIOXIDE, DRY CHEMICALS, WATER FOG.

Fire Fighting Procedures: FULL PROTECTIVE EQUIPMENT INCLUDING SCBA IS
RECOMMENDED TO PROTECT FROM COMBUSTION PRODUCTS. COOL EXPOSED
CONTAINERS WITH WATER.

Unusual Fire/Explosion Hazard: CONTAINERS MAY EXPLODE IF EXPOSED TO
EXTREME

HEAT. ELIMINATE IGNITION SOURCES (HEAT/ELECTRIC EQUIPMENT/SPARKS/FLAME). DO NOT
PUT IN CONTACT WITH OXIDIZING OR CAUSTIC MATERIALS.

===== Accidental Release Measures =====

Spill Release Procedures: USE ABSORBENT MATERIAL OR SCRAPE UP DRIED
MATERIAL AND PLACE INTO CONTAINERS.

===== Handling and Storage =====

Handling and Storage Precautions: STORE AWAY FROM CAUSTICS & OXIDIZERS.
KEEP CONTAINERS AWAY FROM EXCESSIVE HEAT & FREEZING. KEEP

CONTAINERS TIGHTLY CLOSED WHEN NOT IN USE.

Other Precautions: KEEP OUT OF REACH OF CHILDREN. DO NOT STORE @
TEMPERATURES ABOVE 120F. INTENTIONAL MISUSE BY DELIBERATELY
CONCENTRATING & INHALING VAPORS MAY BE HARMFUL TO FATAL.

===== Exposure Controls/Personal Protection =====

Respiratory Protection: IF 8HR EXPOSURE LIMIT OR VALUE IS EXCEEDED FOR ANY
COMPONENT USE APPROVED NIOSH/OSHA RESPIRATORY. CONSULT YOUR SAFETY EQUIPMENT
SUPPLIER & OSHA REG 29CFR1910.134 FOR
RESP REQUIREMENTS.

Ventilation: PROVIDE SUFFICIENT MECHANICAL VENTILATION (LOCAL OR GENERAL EXHAUST) TO
MAINTAIN EXPOSURE BELOW PEL/TLV. VAPORS ARE HEAVIER THAN AIR & (SUPPLEMENT)

Protective Gloves: SOLVENT IMPERMEABLE GLOVES

Eye Protection: GOGGLES, SAFETY GLASSES WITH EYE SHIELDS

Other Protective Equipment: NO INFORMATION GIVEN BY MFG.

Work Hygienic Practices: WASH HANDS AFTER HANDLING.

Supplemental Safety and Health

VENTILATION: WILL COLLECT IN LOW AREAS. CHECK ALL LOW
AREAS (BASEMENTS, SUMPS, ETC) FOR VAPOR BEFORE ENTERING.

=====

=== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:200F,93C

Vapor Pres:80MM @100F

Vapor Density:1.0

Spec Gravity:0.91

Solubility in Water:NIGLIGIBLE

Appearance and Odor:TAN PASTE W/HYDROCARBON ODOR.

Percent Volatiles by Volume:80-90

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZERS AND CAUSTICS.

Stability Condition to Avoid:EXCESSIVE HEAT.

Hazardous Decomposition Products:NORMAL COMBUS

TION PRODUCES I.E. COX,

NOX.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSAL MUST BE IN ACCORDANCE W/LOCAL, STATE AND FEDERAL REGULATIONS. DISCARDED MATERIAL SHOULD BE INCINERATED AT A PERMITTED FACILITY. DO NOT REUSE EMPTY CONTAINER.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.