View NSN Online: https://aerobasegroup.co.il/nsn/8010-01-060-7176

DELTA PLASTICS CO (FORMALLY DELTA DPC, INC) -- BODY FILLER COMPOUND A & B -- 8010-01-060-7176

============= Product Identification ========================

Product ID:BODY FILLER COMPOUND A & B

MSDS Date:12/14/1992

FSC:8010

NIIN:01-060-7176

Kit Part:Y

MSDS Number: BVXBX === Responsible Party ===

Company Name: DELTA PLASTICS CO (FORMALLY DELTA DPC, INC)

Address:10513 ROAD 236

City:TERRA BELLA (FORMALLY IN TULARE)

State:CA ZIP:93270 Country:US

Info Phone Num:209-535-1332 / 209-535-3723 (FAX)

Emergency Phone Num:209-535-1332 / 209-535-3723 (FAX)

Preparer's Name: ERIC SKIFF

CAGE:DO191

=== Contractor Identification ===
Company Name:DELTA DPC, INC

Address:983 E. LEVIN AVE.

Box:City:TULARE

State:CA ZIP:93274 Country:US

Phone: 209-686-1644

CAGE:0ND20

Company Name: DELTA PLASTICS CO. Address: 280 MAIN ST. PO BOX 489

Box:489 City:PIXLEY State:CA ZIP:93256

Phone:209-757-2010

CAGE:DO191

====== Composition/Information o

n Ingredients ========
Ingred Name:POLYESTER RESIN Fraction by Wt: 35-39% Other REC Limits:NONE RECOMMENDED
============ Hazards Identification ==============
Routes of Entry: Inhalation:NO Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:ACUTE: MAY CAUSE RESPIRATORY IRRITATION OR NAUSEA. CHRONIC: NONE SPECIFIED BY MANUFACTURER. Explanation of Carcinogenicity:NO INGREDIENT OF A CONCENTRATION OF 0.1% O
R GREATER IS LISTED AS A CARCINOGEN OR SUSPECTED CARCINOGEN. Effects of Overexposure:REDNESS, IRRITATION. Medical Cond Aggravated by Exposure:ALLERGY, SKIN CONDITIONS.
======================================
First Aid:EYES-FLUSH WITH LOTS OF WATER FOR 15 MINUTES. GET MEDICAL ATTENTION. SKIN-REMOVE CONTAMINATED CLOTHES. FLUSH WITH WATER. INHALATION-REMOVE TO FRESH AIR. RESTORE BREATHING IF NEEDED. GET MEDICAL ATTENT ION. INGESTION-INDUCE VOMITING ONLY UN
DER SUPERVISION OF MEDICAL PERSONNEL. NEVER GIVE ANYTHING BY MOUTH TO UNCONSCIOUS PERSON.
======================================
Flash Point Method:TOC Flash Point:210F,99C Extinguishing Media:CARBON DIOXIDE, FOAM, DRY CHEMICAL. Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS. Unusual Fire/Explosion Hazard:KEEP AWAY FROM HEAT AND SOURCES OF IGNITION.
========= Accidental Release Measures ==========
Spill Release Pr

