View NSN Online: https://aerobasegroup.co.il/nsn/6850-01-394-9514

Product ID:TUNER RENU 2000, ES 1661 MSDS Date:10/22/1997 FSC:6850 NIIN:01-394-9514 MSDS Number: BWCLP === Responsible Party === **Company Name: CHEMTRONICS INC** Address:8125 COBB CENTER DRIVE City:KENNESAW State:GA ZIP:30144 Country:US Info Phone Num:800-645-5244 FAX 770-424-4267 **Emergency Phone Num:770** -424-4888/800-424-9300(CHEMTRAK) CAGE:2M589 === Contractor Identification === **Company Name: CHEMTRONICS INC** Address:8125 COBB CENTER DRIVE Box:City:KENNESAW State:GA ZIP:30152 Country:US Phone:770-424-4888/800-645-5244 CAGE:21267 Company Name: CHEMTRONICS INC (CANCELLED USE 21267) City:HAUPPAUGE State:NY ZIP:11760 Country:US CAGE:2M589 Company Name: ELECTRONIC TOOL COMPANY, INC. Address:241 BLEAKLEY AVE Box:158 **City:BUCHANAN** State:NY ZIP:10511 Country:US Phone:914-769-1000 CAGE:51380 Company Name:T

HOMPSON ELECTRONIC SUPPLIES INC Box:UNKNOW CAGE:1F026

Ingred Name:1,1-DICHLORO-1-FLUOROETHANE (SARA 313) CAS:1717-00-6 RTECS #:KI0997000 Fraction by Wt: 45 - 50% Other REC Limits:NONE RECOMMENDED Ozone Depleting Chemical:2

Ingred Name:PERFLUORO COMPOUNDS, C5-18 CAS:86508-42-1 Fraction by Wt: 45 - 50% Other REC Limits:NONE RECOMMENDED

Ingred Name:SYNTHETIC OIL Fraction by Wt: 1 - 5% Other REC Limits:NONE RECOMMENDED

Ingred Name:CARBON DIOXIDE CAS:124-38-9 RTECS #:FF6400000 Fraction by Wt: 1 - 5% Other REC Limits:NONE RECOMMENDED OSHA PEL:5000 PPM ACGIH TLV:5000PPM/30000STEL;96

LD50 LC50 Mixture:LD50(ORAL,RAT)>5G/KG DICHLOROFLUOROETHAN
Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Explanation of Carcinogenicity:THIS COMPOUND CONTAINS NO INGREDIENTS AT CONCENTRATIONS OF 0.1% OR GRE
ATER THAT ARE CARCINOGENS OR SUSPECT CARCINOGENS.
Effects of Overexposure:ASPHYXIATION, IRRITATION, SKIN DEFATTING, DIZZINESS, HEADACHE, UNCONSCIOUSNESS, PAIN
Medical Cond Aggravated by Exposure:INDIVIDUALS WITH PRE-EXISTING DISEASES OF THE EYE, SKIN, RESPIRATORY TRACT, CNS MAY HAVE

INCREASED SUSCEPTIBILITY TO THE TOXICITY OF EXCESSIVE EXPOSURES.

First Aid:GET MEDICAL HELP IF SYMPTOMS PERSIST. INHALED:MOVE TO

FRESH

AIR. PROVIDE CPR/OXYGEN IF NEEDED. EYES:IMMEDIATELY FLUSH WITH WATER FOR 15 MINUTES. HOLD EYELIDS OPEN. SKIN:WASH WITH SOAP & WATER. ORAL:DO NOT INDUCE VOMITING. IF CONSCIOUS, DRINK 2 GLASSES OF WATER. SEEK IMMEDIATE MEDICAL ATTENTION. IF VOMITING OCCURS, KEEP HEAD BELOW HIPS. DO NOT GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

Flash Point Method:TCC Flash Point:NONE Lower Limits:NOT GIVEN U pper Limits:NOT GIVEN Extinguishing Media:USE WATER FOG, CARBON DIOXIDE (CO2), WATER STREAM OR DRY CHEMICAL. USE WATER SPRAY TO COOL FIRE EXPOSED CONTAINERS. Fire Fighting Procedures:AS WITH ANY FIRE, WEAR PROTECTIVE CLOTHING AND NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS TO AVOID INHALATION OF HAZARDOUS DECOMPOSTION PRODUCTS. Unusual Fire/Explosion Hazard:MAY FORM HYDROGEN FLUORIDE, HYDROGEN CHLORIDE, CARBON MONOXIDE, CARBON DIOXIDE.

======= Accidental Releas

e Measures ===============

Spill Release Procedures:REMOVE OPEN FLAMES. VENTILATE AREA. PLACE LEAKING CONTAINERS OUTDOORS, IN AN OPEN CONTAINER. ALLOW PRESSURE TO DISSIPATE. ABSORB LIQUID WITH INERT ABSORBENT MATERIALS AND PLACE IN CONTAINER FOR DISPOS AL. DO NOT FLUSH TO SEWER OR WATERWAYS.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling and Storage Precautions:STORE IN COOL, DRY, WELL-VENTILA TED

AREA AWAY FROM OPEN FLAMES, HOT SURFACES & INCOMPATIBLE MATERIALS. KEEP OUT OF REACH OF CHILDREN.

Other Precautions: AVOID BREATHING VAPORS. AVOID EYE OR SKIN CONTACT. WASH WITH SOAP AND WATER AFTER HANDLING AND BEFORE EATING OR DRINKING. USE WITH ADEQUATE VENTILATION. DO NOT INCINERATE CONTAINERS. FOR INDUSTRIAL US E ONLY.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:WEAR NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS

OPERATED IN POSITIVE PRESSURE MODE OR SUPPLIED-AIR RESPIRATOR WITH FULL FACEPIECE IF VAPOR CONCENTRATIONS ARE HIGH. Ventilation: USE GENERAL OR LOCAL EXHAUST VENTILATION TO KEEP VAPOR LEVELS AS LOW AS POSSIBLE. Protective Gloves: CLOTH-LINED RUBBER GLOVES/PVA Eye Protection: SAFETY GLASSES WITH SIDE SHIELD/GOGGLES Other Protective Equipment: SAFETY SHOWER AND EYE WASH FOUNTAIN SHOULD BE LOCATED NEARBY. WEAR APPROPRIATE PROTECTIVE CLOTHING FOR RISK OF EXPOSURE. Work Hygienic Practice s:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. Supplemental Safety and Health NONE SPECIFIED BY MANUFACTURER. HCC:V2 NRC/State Lic Num:NOT RELEVANT

HCC:V2 NRC/State Lic Num:NOT RELEVANT Boiling Pt:=32.2C, 90.F Melt/Freeze Pt:M.P/F.P Text:NOT GIVEN Decomp Temp:Decomp Text:NOT GIVEN Vapor Pres:NOT GIVEN Vapor Density:NOT GIVEN Spec Gravity:1.57 Viscosity:NOT KNOWN Evaporation Rate & amp; Reference:>1 (N-BUTYL ACETATE=1) Solubility in Water :NEGLIGIBLE Appearance and Odor:CLEAR, COLORLESS LIQUID - ETHEREAL ODOR Percent Volatiles by Volume:100

Stability Indicator/Materials to Avoid:YES POWDERED ALKALI AND ALKALINE EARTH METALS, STRONG OXIDIZING AGENTS Stability Condition to Avoid:OPEN FLAME, EXTREMELY HOT METAL SURFACES, HIGH TEMPERATURES Hazardous Decomposition Products:MAY FORM CARBON MONOXIDE, CARBON DIOXIDE, HYDROGEN FLUORIDE, HYDROGEN CHLORIDE.

=====

Waste Disposal Methods: ALL USED OR UNUSED PRODUCT SHOULD BE DISPOSED OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. WATER RUNOFF CAN CAUSE ENVIRONMENTAL DAMAGE. DO NOT REUSE CONTAINERS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or impl

ied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their

particular situation.