

PRATT AND LAMBERT, INC; INDUSTRIAL COATINGS DIV -- LACQUER C/N GLOSS WHITE, 17875, 786716 -- 8010-00-257-5377

=====
===== Product Identification =====

Product ID:LACQUER C/N GLOSS WHITE, 17875, 786716

MSDS Date:10/13/1994

FSC:8010

NIIN:00-257-5377

MSDS Number: BWDTT

=== Responsible Party ===

Company Name:PRATT AND LAMBERT, INC; INDUSTRIAL COATINGS DIV

Box:2153

City:WICHITA

State:KS

ZIP:67201

Country:US

Info Phone Num:316-733-1361

Emergency Phone Num:716-873-6000/DOT: 800-255-3924

Preparer's Name:W A ELLISON

CAGE:61196

=== Contractor Identification ===

Company Name:PRATT AND LAMBERT INC

Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

=====
===== Composition/Information on Ingredients =====

Ingred Name:ISOBUTYL ACETATE (SOLVENT) (LFL 2.0; UFL 11.0)

CAS:110-19-0

RTECS #:AI4025000

Fraction by Wt: 25%

Other REC Limits:NONE RECOMMENDED

OSHA PEL

:150 PPM; 700 MG/M3
ACGIH TLV:150 PPM; 700 MG/M3
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ISOPROPYL ALCOHOL (SOLVENT) (VAPOR PRESSURE 33 MM HG @ 20C)
(LFL 3.0; UFL 13.0)

CAS:67-63-0
RTECS #:NT8050000
Fraction by Wt: 5%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:400 PPM;STEL 500 PPM
ACGIH TLV:400 PPM;STEL 500 PPM

Ingred Name:NITROCELLULOSE (RESIN)

CAS:9004-70-0
RTECS #:QW0970000
Fraction by Wt: 10%
Other REC Limits:NONE RECOMMENDED

Ingred Name:ISOBUTYL ALCOHOL (SOLVENT) (VAPOR
PRESSURE 10 MM HG @ 20C)

(LFL 1.0; UFL 11.0)
CAS:78-83-1
RTECS #:NP9625000
Fraction by Wt: 10%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:50 PPM; 150 MG/M3
ACGIH TLV:50 PPM; 150 MG/M3
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:TITANIUM DIOXIDE (PIGMENT)

CAS:13463-67-7
RTECS #:XR2275000
Fraction by Wt: 10%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:10 MG/M3
ACGIH TLV:10 MG/M3

Ingred Name:TOLUENE (SARA III) (VAPOR PRESSURE 22 MM HG @ 20C) (LFL
1.7; UFL 7.1) (SKIN)

CAS:108-8

8-3

RTECS #:XS5250000

Fraction by Wt: