View NSN Online: https://aerobasegroup.com/nsn/9150-00-823-8024

Product ID:MOBIL VACUUM PUMP OIL MSDS Date:06/21/1993 FSC:9150 NIIN:00-823-8024 **MSDS Number: BWDYN** === Responsible Party === Company Name: MOBIL OIL CORPORATION Address: BEAUMOUNT REFINERY INTERSTATE 10 Box:3311 City:BEAUMONT State:TX ZIP:77704 Country:US Emergency Phone Num:609-737-4411/800-424-93 00(CHEMTREC) CAGE:19135 === Contractor Identification === Company Name: MOBIL OIL CORPORATION Address: BEAUMOUNT REFINERY INTERSTATE 10 Box:3311 City:BEAUMONT State:TX ZIP:77704 Country:US Phone:609-737-4411/800-424-9300(CHEMTREC) CAGE:19135 Ingred Name:NON HAZARDOUS INGREDIENT Other REC Limits:NONE RECOMMENDED LD50 LC50 Mixture:LD50 ORAL (RATS): 5 G/KG

Rout

First Aid:EYE-FLUSH THOROUGHLY WITH WATER. IF IRRITATION OC CURS, CALL A PHYSICIAN. SKIN-WASH CONTACT AREAS WITH SOAP AND WATER. INHALATION-NOT EXPECTED TO BE A PROBLEM. INGESTION-NOT EXPECTED TO BE A PROBLEM WH EN INGESTED. IF UNCOMFORTABLE SEEK MEDICAL

ASSISTANCE.

Flash Point Method:PMCC Flash Point:>400F,>204C Lower Limits:0.6% Upper Limits:7.0% Extinguishing Media:CO2, FOAM, DRY CHEMICAL & WATER FOG Fire Fighting Procedures:WATER OR FOAM MAY CAUSE FROTHING. USE WAT ER TO KEEP FIRE EXPOSED CONTAINERS COOL. WATER SPRAY MAY BE USED TO FLUSH SPILLS AWAY FROM EXPOSURE. USE SCBA.

Unusual Fire/Explosion Hazard:NONE

Spill Release Procedures: ABSORB ON FIRE RETARDANT TREATED SAWDUST, DIATOMACEOUS EARTH, ETC. SHOVEL UP & DISPOSE OF AT AN APPROPRIATE WASTE DISPOSAL FACILITY.

Handling and Storage Precautions:NONE SP ECIFIED BY MANUFACTURER. Other Precautions:NO SPECIAL PRECAUTIONS REQUIRED.

Respiratory Protection:NO SPECIAL REQUIREMENTS UNDER ORDINARY CONDITIONS OF USE AND WITH ADEQUATE VENTILATION.
Ventilation:NO SPECIAL REQUIREMENTS UNDER ORDINARY CONDITIONS OF USE AND WITH ADEQUATE VENTILATION.
Protective Gloves:GOOD HYGIENE PRACTICES RECOMMENDED
Eye Protection:NORMAL INDUSTRIAL EYE PROTECTION.
Other Protective Equipment:NONE S PECIFIED BY MANUFACTURER. Work Hygienic Practices:WASH HANDS THOROUGHLY AFTER HANDLING. Supplemental Safety and Health NONE

HCC:V6 Boiling Pt:B.P. Text:>600F,>316C Vapor Pres: